

ODC SL75

# ODC SL75, A BESPOKE WINDOW SYSTEM, WITH A SLIMLINE VENT AND FRAME WHICH PERFORMS TO ENHANCED THERMAL INSULATION AND SECURITY STANDARDS.

With the energy efficiency of buildings under increasing scrutiny, specifying the right window systems is critical in modern building design. The ODC SL75 window system's U value from 1.1 and uses a unique polyamide thermal barrier for superior thermal performance, and the system also attains the highest level of weather performance for water tightness, air permeability and wind resistance.

This unique and expertly engineered window suite offers the discerning homeowner the perfect combination of exceptionally slim frames and the highest of levels of performance. With sleek, clean lines, these beautifully designed windows can transform the appearance of any home, adding value to the property whilst also making it warmer, brighter and more secure.

ODC Door & Glass Systems Ltd.

EMAIL: sales@odcglass.co.uk www.odcglass.co.uk













**CLARITY IN DESIGN** 



# ODC SL75



# **CASEMENT SIZES**

# **TOP HUNG**

- Max. vent size 1340mm (H) x 1200mm (W)
- Min. vent size 250mm (H) x 424mm (W)

#### **SIDE HUNG**

- Max. vent size 1300mm (H) x 740mm (W)
- Min. vent size. 424mm (H) x 250mm (W)
- Fixed lights 5m<sup>2</sup>
- Glazing thickness to 34mm
- Vent weight to 40kg

#### **WARM AND COSY**

- Industry-leading thermal insulation
- Double- and triple-glazed options
- Unique thermal insulation profiles
- U-value from 1.1 W/m<sup>2</sup>K

# **AS INDIVIDUAL AS YOU ARE**

All our windows and doors are made to meet your exact requirements. From the design of the window to the colour of the frame and handle, there are almost unlimited options. When you choose ODC Door & Glass Systems, you can make your windows and doors truly individual, a design statement to be proud of.

- Huge range of design options
- SL75 is available in our 3 standard colours of Black,
  Anthracite Grey and White and a full spectrum of
  RAL colours and in anodised or dual finishes to marine grade quality
- Optional trickle vent
- Choice of handles colours

#### **PEACE AND QUIET**

Not only is the frame of the ODC SL75 window designed to help eliminate unwanted noise, the system is also flexible enough to allow a glazed unit up to 34mm thick to be specified. This makes it possible to incorporate some quite sophisticated acoustic glazing, which makes a huge difference if you live near a busy road, a railway or an airport.

# **TRIED AND TESTED**

The ODC SL75 window is purpose-built and has been put through the most stringent test regime, ensuring that it is one of the highest performing and most reliable windows available.

- Premium-quality materials
- Highest levels of performance
- Industry-leading weather resistance

#### Opening Lights:

- Air permeability Class 4 600Pa
- Water-tightness Class 9A 600Pa
- Wind resistance Class C4/1600Pa\*

#### Fixed Lights:

- Air permeability Class 4 600Pa
- Water-tightness Class 9A 600Pa
- Wind resistance Class A5 2000Pa\*
- \* Exposure category varies with Width/Height of window and mullion/transom used, as these are the only unsupported members.

# **SAFE AND SECURE**

- One of the most secure windows available
- Optional enhanced security with hinge-side security brackets
- Multi-point locking mechanism
- Lockable handle

FOR MORE EXAMPLES OF OUR WORK VISIT WWW.ODCGLASS.CO.UK OR VISIT OUR SHOWROOMS:

LONDON: 97 Bollo Lane, London W3 8BN

**POOLE:** Sterte Road Industrial Estate, 145 Sterte Road, Poole, Dorset BH15 2AF

SALES: 03300 586 792 CUSTOMER SERVICES: 03300 586 793













**CLARITY IN DESIGN** 

