

.



NOTES

SYSTEM WINDOWS MANUFACTURED FROM W30 SECTIONS TO BS6510.

FINISH HOT DIP GALVANISED TO BS729 AFTER ALL FABRICATION. POLVESTER POWDER COATED: RAL 9911 HIPPCA WHITE MATT HARDWARE & ATTACHMENTS ALL OPENING LIGHTS ARE DUAL WEATHERSTRIPPED.

SIDE HUNG CASEMENTS: HUNG ON 1 PAIR EASY CLEAN PROJECTION HINGES AND FITTED WITH 1 NO. B158 KEY LOCKING RTD HANDLE AND B375 RTD PEGSTAY.

DOUBLE DOOR OPEN OUT: EACH LEAF HUNG ON 4 NO. SCREW ON BUTT HINGES. IST OPENING LEAF

1 NO. BISB KEY LOCKING RTD HANDLE 2 NO. BBSF FACE FIXED RTD SHOOT BOLTS 150mm LONG AT TOP AND BOTTOM.

1ST CLOSING LEAF 2 NO. 885C CONCEALED RTD SHOOT BOLTS 150mm LONG AT TOP AND BOTTOM.

GLAZING SITE GLAZED USING EXTERNAL PART L COMPLIANT ALUMINIUM EASI-FIT CHAMFERED BEADS (coated to match), GLAZING TAPE AND SILICONE CAPPING

4mm CLEAR TOUGHENED ST.GOBAIN DIAMANT OUTER PANE 10mm KRYPTON GAS FILLED CAVITY WITH WHITE EDGE SUPERSPACER 4mm CLEAR TOUGHENED GUARDIAN CLIMAGUARD A+ CODE L12/SC2 INNER PANE

NOTE: APPLIED 19mm ALUMINIUM PROFILED BARS TO EXTERNAL SURFACE. 19mm FLAT BARS TO INTERNAL SURFACE. WHITE GRID SPACER BETWEEN PANES TO SIMULATE GLAZING BARS.

PIB Primary and 4mm Butyl Secondary Sealants

G RATING = 0.55U RATING = 1.122

GENERAL ALL COUPLED, FIXED AND GLAZED USING MASTICS AND SEALANTS AS SUITED TO AREA OF USE. ALL VISIBLE SEALANTS TO BE (colour to be agreed)



