



ALL NEW STAINS TO BE DARK OAK. STAIN TO APPROVED BY DESIGNER
 FOH ARCHITRAVES - ALL TO MATCH EXISTING
 BOH ARCHITRAVES - TO BE STANDARD CHAMFERED EDGE TYPE 75mm WIDE
 ALL EXISTING DOORS TO BE PRIMED AND RE-PAINTED

NEW DOORS TO BE IN ACCORDANCE WITH THE CLEAR EFFECTIVE DOOR WIDTHS IN TABLE 2, HAVE VISION PANELS LOCATED BETWEEN 500 AND 1500 MM ABOVE FLOOR LEVEL, BE OPERABLE BY USE OF A CLOSED FIST REQUIRING NO GREATER FORCE THAN 30n TO OPEN.



- * ALL DIMENSIONS ARE APPROXIMATE. ACCURATE DIMENSIONS TO BE TAKEN BY MAIN CONTRACTOR POST STRIP OUT.
- * ALL JOINERY TO BE MANUFACTURED AND PRE-FINISHED OFF SITE.
- * ALL MATERIALS MUST BE SUITABLE FOR USE WHERE INDICATED.
- * ANY TIMBER BAR AND BACKFITTING TOPS TO BE TREATED WITH A WATER, HEAT & ALCOHOL RESISTANT 2 PART CLEAR ACID CAT. LACQUER.
- * ALL FINISHES TO BE APPLIED IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. WHERE APPLICABLE, REFER TO WRITTEN SPECIFICATIONS.
- * NO CONTACT ADHESIVES TO BE USED.
- * ALL FIXINGS TO BE SECRET FIXINGS ONLY (i.e. NO CUPS AND SCREWS OR OTHER VISIBLE FIXINGS).
- * MAIN CONTRACTOR / JOINERY CONTRACTOR TO LIAISE WITH ELECTRICAL CONTRACTOR REGARDING FIRST FIX WIRING TO ANY LIGHTING / POWER POINTS TOGETHER WITH SEQUENCING OF WORKS TO ALLOW SECOND FIX OF ANY ELECTRICAL ITEMS.
- * ALL BAR UNDERCOUNTER CARCASSING AND INTERIOR OF CUPBOARDS ETC TO BE LAMINATE CLAD & LIPPED REF: POLYURE 'C116 CHOCOLAT'.
- * CONTRACTOR TO SUPPLY STAIN SAMPLES FOR APPROVAL BY JMDA IN SUFFICIENT TIME FOR PRODUCTION OF JOINERY ELEMENTS.
- * ALL BAR & COUNTER TOPS / WAITER STATIONS ETC TO RECEIVE MORRELLS 440 ACID-CATALYST LACQUER (OR EQUIVALENT APPROVED) FINISH APPLIED IN STRICT ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS / RECOMMENDATIONS.
- * CONTRACTOR TO CONSIDER ACCESS INTO PREMISES & SIZE / WEIGHT OF SECTIONS. SUFFICIENT MAN POWER TO BE AVAILABLE AND OR / SPECIALIST LIFTING EQUIPMENT USED AS DEEMED SUITABLE BY CONTRACTOR TO ENSURE SAFE DELIVERY & INSTALLATION. THE PRINCIPLE DESIGNER / PRINCIPLE CONTRACTOR (CDM) MAY REQUEST A METHOD STATEMENT DETAILING DELIVERY & INSTALLATION PROCEDURES.
- * ALL GLAZING TO COMPLY WITH PART K OF BUILDING REGULATIONS. CONTRACTORS GLASS SUPPLIER TO ADVISE ON TYPE OF GLASS TO EACH LOCATION. ANY QUERIES TO BE ADDRESSED TO JMDA PRIOR TO MANUFACTURE.

SUPPLIER TO MEASURE ON SITE BEFORE MANUFACTURE
NOTE - THIS IS DESIGN INTENT DRAWING ONLY



Scale: 20 @ A1

Inda
Interior Architecture Graphics

JMDA LTD
2 The Holmes Skipwith,
York, YO8 5SL
T: 01757 288 399
info@jmdaltd.co.uk
www.jmdaltd.co.uk