

Classic Folding-Arm Awning





Index

Classic Folding-Arm Awning

- 6 History & Present Day
- 8 Design & Craftsmanshir
- 10 Application & Construction
- 12 Finishing & Customisation

Specification Guide

L5 Overview

Housing

- **18** Wall Mounted
- 10 Top Fixed

Arm

21 Arm

Fixings Specifications

- **23** Fixings
- **24** Bracket and Arm Position
- **25** Extraction Forces

Options

- **27** Operation
- **28** Valanc
- 29 Sensors
- **30** Branding

Finishes

- **32** Fabric
- 35 Metalwork

Classic Folding-Arm Awning



We understand that some customers want benefits of a heavy-duty Folding-Arm awning but wish to conserve budget for other outgoings, and with this in mind, we offer our Classic Folding-Arm system. We will mever compromise the quality of our awnings in order to sell cheaply produced products that are likely to cause the owner nothing but trouble. This is a strong heavy-duty system that comes with a protective hood that sits above the awning and protects it from the elements.


Classic Folding-Arm Awning





History

Morco was founded in London in 1956 by Mr. G.H. Morrison as a specialist manufacturer of canopies, covers, sails and tarpaulins for London's busy waterways. His popularity with employees and customers saw his business grow steadily. In 1967, Morco moved to their current Riverside location on the Greenwich Peninsula. 1978 saw his son George take over the company and he was keen to put his design background to use. George soon began constructingspecialist awning on a much larger scale. With his obsessive eye for detail and quality, Morco soon gained a reputation across the UK for producing outstanding awnings.



Present Day

For over 50 years, we have established ourselves as the London's leading designi and manufacturer of custom-made awnings and canopies. We remain a family run business that prides itself on its heritage. There remaind a dedicated and skilful team of craftsman and designers who all play a vital rola in Morco's success story. The majority of products are still hand-built in our London workshop and a small amount are produced in Germany. Morco are keen to lead and invest heavily in pioneering new techniques or developing materials to both improve our end product and also deliver more options to our customers.







Design

Morco have a talented and experienced design team who are skilled at collaborating with architects, design teams, contractors or working indepentently to produce the best awning solution. We are able to provide sophisticted 3D-modelling on request, as well as supplying fabric samples. Morco also offer clients the opportunity to utilise their cutting-edge RAGS branding and pattern system which has revoliutonised the traditional design paramenters.



Craftsmanship

Our manufacturing team are dedicated and skilled craftsman who are proud of mantaining Morco's on-going reputation for producing awnings of outstanding build quality. Our attention to detail is second to none and is a key element in ensuring every awning manufactured in the workshop is constructed to the highest standard.







Application

The Classic Folding-Arm is a slim but strong non-fully cassetted awning that is suitable for the majority of shop fascias as well as residential homes. It is extremely versatile and can be installed in various ways to fit into all kinds of different structural situations. This is a strong heavy-duty system that comes with a protectove hood that sits above the awning and protects it from the elements. One of our most popular awnings.



Construction

The Classic Folding-Arm awning is a robust and durable option for your homw or commercial property and has a front profile extremely resistant to twist and deflection. All the metalworkis powder coated and the cover and valance can be chosen from a wide range of fabric colours. Both are also suitable for branding application.







Finishing

With a range of fabric colours and metal finishes available, the Classic Folding-Arm awning offers endless possibilities to suit any setting. All finishes also give the Classic greater resilience - metalwork is powder coated and the fabric is solution dyed and protected to mantain resistance throughout the life span of the awning and withstand the most demanding weather conditions. There are a number of colour options and finishes for the metalwork and the canvas can be chosen from a wide range of colours or utilise Morco's RAGS branding and pattern system.



Customisation

The Classic Folding-Arm awning is fully customisable. There is a wide range of colours for the cover fabric which we can further customise using our unique RAGS branding process. For opening and closing operation, the Classic provides two options, either a Soft-Gear Full Winding Control or an Electro-Smart Automated Control. The Classic can also come with weather sensitive sensors. These include a vibration sensor that retracts the awning automatically in windy conditions, or a sensor that can automatically extend the awning in rainy or sunny weather.





Classic Folding-Arm Awning | Specification Guide

Classic Folding-Arm Awning | Overview



Maximum width: 1 section: 7.0 m | 2 sections: 12 m **Maximum projection:** 4.0 m (subject to suitable fixing height).

Pitch: from 10° to 40°.


Operation: electric (either side of the roller) or manual (winding handle).


*Note: if the awning's angle of pitch is less than 25% = 14°, measured from the horizontal, it musto not be opened in the rain. There is a risk of puddles forming in the fabric which could damage the awning or cause it to fall.



Classic Folding-Arm Awning | Overview


Side Profile





Housing

Classic Folding-Arm Awning | Housing | Wall Mounted




Width: Up to 7.0 m (1 sect on). Up to 12 m (2 sect ons).

Projection: Up to 4.0m. **Pitch:** From 10° to 40°.

Fixing positions: Face fixed (see page 23).

Classic Folding-Arm Awning | Housing | **Top Fixed**




Width: Up to 7.0 m (1 section). Up to 12 m (2 sections).

Projection: Up to 4.0m.Pitch: From 10° to 40°.Fixing positions: Top fixed.



Classic Folding-Arm Awning | Arm

Typical Cross Section




Minimum head clearance: 2.1 m Maximum projection: 4.0 m Maximum width: 7.0 m | 12 m Pitch: from 10° to 40°. Fixing Brackets

Face Fixed (standard)




Top Fixed






Classic Folding-Arm Awning | Fixing specifications | Fixings




Fixing: Coach screw

Fixing: Coach screw **Depth:** 75mm (min)




Fixing: Hex bolt

Fixing position: see page 23.



Fixing: Anchor bolt Depth: 100mm (min)




Fixing: Resin bolt / studding M14

Depth: 250mm (min)



Classic Folding-Arm Awning | Fixing Specifications | Bracket & Arm Position

Example: 11500mm x 3000mm - Incl. 6no Brackets and Awning Jockey



A: arm position.LR: rolltex bearing.M: awning width.B: arm position.

MB: bracket fixture range.



Classic Folding-Arm Awning | Fixing Specifications | Extraction Forces

Selection table for wall brackets and anchoring system

Wall installation on C20/25 concrete with up to 200 mm of facing, extraction force in N per upper fixing for wall bracket.


Width in cm	Projection in cm					
	150	200	250	300	350	
250	818 409 205 270	1232 616 308 400	1776 888 444 568			Consult table for extraction force per fixing for selected awning size.
300	939 538 269 312	1419 798 399 462	2042 1129 564 654	2716 1486 743 862		Select a wall bracket/mounting plate for which there is a fastener which can resist the indicated extraction force. Remember to take into account the spacing, the area which will be damaged if the fixing breaks out,
350	1060 610 305 354	1606 906 453 526	2308 1280 640 742	3074 1686 843 978	4055 2200 1100 1276	the type of fi xing used and the assembly base.
400	1181 682 341 396	1792 1014 507 588	2573 1431 716 830	3432 1887 943 1094	4518 2456 1228 1424	1 standard wall bracket (85 mm) plus 1 standard wall bracket (85 mm) as a central bracket from 401 cm, 1 standard wall bracket (85 mm) per awning arm, fasteners: 4 in all
450	1303 652 326 378	1979 990 459 574	2839 1420 710 824	3790 1558 948 1100	4982 2491 1246 1444	1 standard wall bracket (85 mm) plus 1 standard wall bracket (85 mm) as a central bracket from 401 cm, 2 standard wall brackets (85 mm) per awning arm, fasteners: 8 in all or
500	1424 712 356 412	2166 1083 542 628	3104 1552 776 900	4148 2074 1037 1202	6244 3122 1561 1810	1 wall bracket (260 mm) plus 1 standard wall bracket (85 mm) as a central bracket from 401 cm, 1 wall bracket (260 mm) per awning arm, fasteners: 8 in all
550	1545 773 386 448	2352 1176 588 682	3370 1685 843 978	5163 2582 1291 1498	6789* 3395 1697 1968	1 wall bracket (260 mm) plus 1 standard wall bracket (85 mm) as a central bracket from 401 cm, 2 wall brackets (260 mm) per awning arm, fasteners: 16 in all
600	1666 833 417 484	2539 1270 635 736	3635 1818 909 1054	5582 2791 1396 1618	7335* 3668 1834 2128	Mounting plate (280 x 240 mm) incl. 1 standard wall bracket (85 mm), standard wall bracket (85 mm) incl. base plate, fasteners: 8 in all * 2 brackets required per awning arm


Options





Classic Folding-Arm Awning | Options | Operation

Electric Operation (see Electrical Specifications below)









Classic Folding-Arm Awning | Options | Valance

straight
turreted
turreteu
castle
wave
scalloped



Classic Folding-Arm Awning | Options | Sensors

Vibration sensor



Vibration sensor - standard product protection

The integrated vibration sensor retracts the awning automatically when it senses vibrations (e.g. from gusts of wind).

- threshold value adjustable
- comes as standard in most width/projection combinations (with some exceptions)
- energy-saving technology
- battery life 2 years
- automatic battery replacement system on registration
- awning remains in place approx. 20 minutes after retraction

Sun, wind & rain sensors



Sun, wind and rain sensors – automatically protect your product and prevent excess heat (optional)

The remote sensors automatically extend the awning when the sun shines and reliably retract it in the wind or rain.

Classic Folding-Arm Awning | Options | Branding

Cover

Logo



Text

MORCO AWNINGS

Full pattern



Gilding



Valance

Logo



Text

MORCO AWNINGS

Full pattern



Gilding

Classic Folding-Arm Awning | Finishes

Classic Folding-Arm Awning | Plain Fabric



Classic Folding-Arm Awning | Plain Fabric



Classic Folding-Arm Awning | Striped Fabric



Other combinations of colours also available



Classic Folding-Arm Awning | Metalwork

Standard frame colours



Please note, frames can be powdercoated to any RAL colour, however there is a surcharge for any non-standard colour

As a result of the ban on the use of heavy metals in powder coatings, paint manufacturers can no longer guarantee colour stability despite making every effort to do so. It therefore cannot be excluded that colours in general may fade with time. For technical reasons, the colour may appear different when printed.

Classic Folding-Arm Awning

Contact details:

tel: +44 (0)20 8858 2083 info@morcoblinds.co.uk www.morcoawnings.co.uk

Morco Awnings Limited, Riverside, Lombard Wall, London SE//SS

Morco Awnings are part of the Riverside Works Group