

Please note that information used to produce these drawing is based on measured survey supplied by others; Heritage Architecture cannot be held responsible for any inaccuracies that may exist. Please do not scale from the

drawings. All dimensions should be verified on site. Any inconsistencies should be reported to the project architect. Drawing to be read in conjunction with the Heritage and Design & Access Statement by Heritage Architecture Ltd.

307

2023 and datasheets in Appendices. Any dimensions detailed in this drawing are in millimeters.

The drawings is protected by copyright. All copyrights with

Heritage Architecture Ltd and Anslow Partnership.

1. This drawing is an Outline Design showing the relative location of the proposed devices. The final locations of the proposed devices are subject to the final assessment to be carried out by the specialist contractors once listed building consent has been

2. If the proposal materially differs from the outline design included here, a new LBC application will be submitted. Additional details can be provided as a Discharge of Condition if required.

3. This drawing indicates design intent only and shall not be used as an installation or working drawing.

4. All colour finishes to all fire alarm accessories will depend on the final manufacturer (based on tender process), but will be minimally visually intrusive and in keeping with the general colour scheme of the background/ space.

5. Existing routes and penetrations will be utilised wherever feasible. Where new routes/ penetrations are required these have been highlighted in green. Please refer to associated drawings as noted for detailed markups on photographs (included within submitted

6. The proposed Fire Alarm System classification is L2.

7. The system shall be designed, installed, tested and commissioned in accordance with the following BS5839-1 2017, BS5839-6:2013, BS5839-8:2013, BS7629-1:2008 and LP51014:

Issue 5 requirements for Certified Fire Detection and Alarm Systems.

SYMBOL LEGEND Ceiling-mounted Wireless Devices:

s - Smoke Detector

(H) - Heat Detector

Manual call point

Wall-mounted Wireless Devices:

Sounder & Flashing Beacon

Fire Alarm Interface: AC - Access Control LCP - Lighting Control Panel

AV - Audio Visual FS - Fire Shutter **Ceiling-mounted Hardwired Devices:**

s - Smoke Detector

Combined Smoke Detector & Sounder

Combined Smoke Detector, Sounder & Flashing Beacon

Heat Detector (H) - Combined Heat Detector & Sounder

Wall-mounted Hardwired Devices:

FAP - Fire Alarm Panel

Fire Alarm Repeater Panel - Manual call point

Sounder & Flashing Beacon

- Wall mounted sounder

Fire Alarm Interface AC - Access Control

FS - Fire Shutter BMS - Building Management System SS - Sprinkler System MFD - Motorised Fire Dumper

LCP - Lighting Control Panel AV - Audio Visual RT - Retail Units V - Void

 - 13A Unswitched fused connection unit with neon indicator - Fire Alarm Panel (Secure mains voltage

safety isolator with safety key switch) L.I. - Loop Isolator

Lwg - Loop-Powered Wireless Gateway (for wireless devices)

Wall-mounted Refuge Devices:

 Disabled Refuge Remote Unit Disabled Refuge Master Panel

RLB - Remote Lamp Buzzer Surface-mounted cables/conduits:

 25/32mm Galvanised Conduit from Ceiling surface mounted and fixed to a Steel Box (For Fire Alarm

Detectors, Call Points, Electrical accessories etc.) - 25/32mm 1 way Stop-end Galvanised Conduit Box

25/32mm Galvanised Conduit run to surface back steel

- 150mm Galvanised tray within riser.

Senate House Library University of London

FIRE ALARM SYSTEM LAYOUT (Proposed)

FIRST FLOOR - TOWER & NORTH BLOCK

DRAWN BY CHECKED BY SCALE (@A0) DATE 1:100 MAY/23

STEPHEN LEVRANT HERITAGE ARCHITECTURE





E-mail: info@heritagearchitecture.co.uk T: 020 8748 5501

The Anslow Partnership Consulting Engineers

