

M40 Natural stone/ ceramic tiling/ mosaic

115 NATURAL STONE FLOORING

- **Stone slabs to BS EN 12058** : For compliance to the Construction Products Regulations, a current CE Certificate and Declaration of Performance data sheet is available from Albion Stone which include declared values for each test listed below, based on at least 10 years of testing, and authorised by a company director.
 - Reaction to fire Class A1
 - Flexural Strength BSEN 13161
 - Slip Resistance BSEN 14231
 - Tactility (surface treatment)
 - Apparent Density BSEN 1936
- **Face dimensions, length (l) x width (b):**
- **Thickness (d):** Stone thickness is 20mm for sizes ≤ 600mm x 600mm.
- **Petrographic name to BS EN 12407:** Jurassic Limestone, Portland Whitbed from Jordans Mine
- **Denomination to BS EN 12440:** Heritage Portland Stone
 - Colour: Off white / creamy buff.
 - Origin: Portland, Dorset, UK
- **Finish:** The indicative sample provided shows the surface finish.
-
- **Supplier:** Albion Stone plc, Easton Street, Portland Dorset DT5 1BW. 01737 771772
- **Quality:** A Factory Production Control system will ensure the stone are free from vents, cracks, fissures, discolouration, or other defects deleterious to strength and durability. Tolerances as stated in BSEN 12058.
 - Quality Management: compliance with ISO 9001
- **Environmental impact.**
 - Environmental Management: compliance with ISO 14001
 - Responsible Sourcing of the stone: compliance with BES 6001 - 'Excellent certification'
 - Environmental Product Declaration (EPD) Cradle to gate for the extraction and manufacture of the stone
- *Note – all further sections to the specification should be in accordance with best practice as set out in the standard NBS clauses.*