

GENERAL NOTES:

1. REFER TO DRAWING HSC-REN-ZZ-XX-DR-S-00010 FOR GENERAL NOTES AND REINFORCEMENT ESTIMATES.

ROOF STRUCTURE DEFLECTION

THE COMPOSITE STEEL FRAME WILL DEFLECT UNDER IT'S OWN SELF-WEIGHT, FINISHES AND PLANT LOADING. COMPOUND SLAB DEFLECTIONS AT MIDSPAN BETWEEN COLUMNS WILL BE UP TO SPAN/250. FOR THE ARRANGEMENT SHOWN MIDSPAN DEFLECTION COULD IN THE RANGE OF 25-30mm.

IF THE ARCHITECT, ROOFING CONTRACTOR, OR ROOFING SUPPLIER REQUIRE A 'FLAT' ROOF WITH NO NEGATIVE FALLS THEN THIS SHOULD BE FORMED WITHIN THE TAPERED ROOF INSULATION AND AGREED BETWEEN THE ABOVE PARTIES AND THE MAIN CONTRACTOR.

STEEL STAIRS

ALLOW FOR STEEL STAIRCASE'S TO ARCHITECTS DESIGN INTENT AND SPECIALIST SUPPLIERS DESIGN AND DETAIL, INCLUDING FIXINGS BACK TO PRIMARY FRAME

COLUMN SETTING OUT ALL COLUMNS TO BE LOCATED CONCENTRICALLY ON GRIDLINES UNLESS NOTED OTHERWISE

FAÇADE SUPPORT

FOR FAÇADE PRINCIPLES, INCLUDING MASONRY SUPPORT, SECONDARY STEELWORK ETC. REFER TO FAÇADE CONSULTANTS INFORMATION

CAST-IN CHANNELS, FIXINGS AND BRACKETRY

FOR ALL CAST-IN CHANNEL, FIXINGS AND BRACKETRY REQUIREMENTS, INCLUDING SPECIFICATION AND DETAILED SETTING OUT, REFER TO CLADDING CONTRACTORS, LIFT MANUFACTURES AND BALUSTRADE

WHERE CAST-IN CHANNEL AND FIXINGS ARE INDICATED ON THE RENAISSANCE DRAWINGS, THESE ARE INDICATIVE AND FOR COORDINATION PURPOSES ONLY. REFERENCE SHOULD BE MADE TO THE RELEVANT CONTRACTOR DRAWINGS FOR DETAILED REQUIREMENTS.

FLOOR LEVEL - TOLERANCE & SURFACE REGULARITY

THE CONCRETE FRAME IS TO BE CONSTRUCTED IN ACCORDANCE WITH THE NATIONAL STRUCTURAL STEELWORK SPECIFICATION TOLERANCES. IN ADDITION FLOOR WILL DEFLECT AT MID-SPAN UP TO SPAN/250. WHERE

FINISHES REQUIRE AN ENHANCED SURFACE REGULARITY (I.E. SR1, SR2 OR SR3) ALLOW FOR SELF LEVELLING SCREED OR COMPOUND

SERVICE PENETRATIONS & RISER

ALL SERVICE OPENING TO THE BUILDING SERVICES CONSULTANTS REQUIREMENTS. REFER TO THE ARCHTIECTS DRAWINGS FOR DETAILED SETTING OUT OF SLAB EDGE AND SERVICE OPENINGS.

ALL SVP & RWP ARE TO BE SET OUT BY THE BUILDING SERVICES CONSULTANT AND ARCHITECT. CONTRACTOR TO ALLOW FOR CASTING FIRE COLLARS TO ALL SVP & RWP PENETRATIONS AND ALL OTHER SERVICE OPENINGS WHERE FEASIBLE

DENOTES SPAN OF 140mm RC32/40 NORMAL WEIGHT REINFORCED CONCRETE SLAB ON 0.9mm GAUGE SMD 60 + (450 GRADE) DECKING.
PROVIDE 1No. LAYER A193 REINFORCEMENT MESH TOP OF SLAB WITH 30mm COVER. ALLOW 5kg/m² ON PLAN OF LOOSE REINFORCEMENT TO COVER REQUIREMENTS AT SLAB EDGES ETC.

> FINAL DESIGN AND DETAILING BY SUPPLIER TO ACCOMMODATE MAXIMUM IMPOSED CONSTRUCTION LOAD OF 1.5kN/m² AND 1 HOUR FIRE RESISTANCE. MAXIMUM ALLOWABLE POINT LOADING TO BE CONFIRMED BY SUPPLIER FOR CONSTRUCTION ACTIVITIES. ALLOW FOR 19DIA X 105mm L.A.W STUDS AT 300mm SPACING TO EVERY BEAM SUPPORTING THE SLAB.

SCHEDULE

C01 - 254x254x89 UC

C02 - 203x203x86 UC

C03 - 203x203x46 UC C04 - 100x100x10 PFC

P03	UPDATED PROPOSALS - STAGE 2	06.09.23	EM	Al
P02	UPDATED ARCHITECTURAL PROPOSALS	14.06.23	EM	Al
P01	STAGE 2	31.03.23	EM	Al
Rev:	Description:	Date:	Ву:	Chkd:

HARRINGTON SQUARE CAMDEN

ROOF PLAN

STAGE 2

Size:	Date:	Drawn by:	Designed by:	Checked bv:		
A1	MAR '23	EM	EM	AI		
Scale: 1:100	ale: 1:100 Project No: 2202-03					

Project: Originator: Volume: Level: Type: Role: Category/Number: Rev:

HSC-REN-XX-05-DR-S-01105 P03