



GENERAL NOTES

THE BASE INFORMATION SHOWN IS THAT PROVIDED TO US BY THE CLIENT.

GENERAL SITE CONDITIONS TO BE VERIFIED BY CONTRACTOR AND ANY DISCREPANCIES OR CONCERNS TO BE BROUGHT TO THE ATTENTION OF THE CLIENT AND DESIGN TEAM.

ALL DIMENSIONS TO BE CHECKED ON SITE PRIOR TO MANUFACTURE AND CONSTRUCTION.

INFORMATION PROVIDED IS DESIGN INTENT ONLY.

MAIN CONTRACTOR TO ENSURE COORDINATION WITH M&E CONSULTANT.

ALL MATERIALS TO BE FIRE RATED TO MEET BRITISH STANDARD REGULATIONS.

CONTRACTOR TO PROVIDE FULL SAMPLES AND DRAWINGS FOR SIGN-OFF BY CLIENT AND DESIGNER PRIOR TO MANUFACTURE AND INSTALLATION.

REFER TO SCOPE OF WORK SPECIFICATION DOCUMENT FOR DETAILED PRODUCT AND INSTALLATION INFORMATION.

SUSTAINABLE NOTES:

ALL FINISHES, MATERIALS AND EQUIPMENT TO MEET BREEAM 'VERY GOOD' RATING.

ALL TIMBER, HARDWOOD AND MDF COMPONENTS MUST BE RECLAIMED OR COME WITH A CHAIN OF CUSTODY FROM THE RSC, PEFC, SFI OR CSA FOREST CERTIFICATION SCHEMES.

PRODUCTS TO BE SUPPLIED WITH ONE OF THE FOLLOWING:

- EPD
- CRADLE TO CRADLE
- DECLARE
- HAVE MORE THAN 40% RECYCLED CONTENT

PRODUCTS ARE ACCEPTABLE IF THEY ARE SUPPLIED WITH AN ENVIRONMENTAL PRODUCT DECLARATION (EPD), WRITTEN IN ACCORDANCE WITH ISO 14025:2010



OUT OF SCOPE / CIRCULATION AREA

P02 CT CA 14/09/2023 PAPER SIZE CHANGED TO A1

P01 CT CA 17/07/2023 FIRST ISSUE

Rev DB CB Date Revision Notes

Project Title

**London Film School
39-41 Parker Street, London
WC2B 5PQ**

Drawing Title

**Third Floor
Proposed Plan (Planning)**

Drawing No.

8192-ID-PS-03-DR-I-1002


Proj.No. Originator Scale Rev
8192 CT 1:50@A1 P02

Suitability
S2 SUITABLE FOR INFORMATION

PROPOSED PARTITION KEY:

PARTITION TYPE 07 - BOX IN BOX ACOUSTIC PARTITION - V2
NOM. 340MM THK 2 X LAYER OF 15MM SOUNDBLOC, 280MM CAVITY WITH 90MM GYPSUM C STUDS AT 600MM CENTRES.
NOT LESS THAN 73 Rw dB. 100mm ISOWOOL 1200 INSULATION. SEAMLESS JOINTING AND RIGID BEADS/STOPS. PRIMER TO PAINTED AREAS. PLANTED ON SKIRTING DESIGN TO MATCH EXISTING. PARTITION TO RECEIVE ADDITIONAL ACOUSTIC TREATMENT ON BOTH SIDES +100MM.

PARTITION TYPE 05 - ACOUSTIC SLAB TO SLAB PARTITION
NOM. 212MM THK 2 X LAYER OF 15MM SOUNDBLOC EACH SIDE OF 1GYPFRAME 146 AS 50 ACOUSTUDS AT 600MM CENTRES.
NOT LESS THAN 63 Rw dB (AIRBOURNE). 50MM ISOVER ACOUSTIC PARTITION ROLL (APR 1200) IN THE CAVITY. SEAMLESS JOINTING AND RIGID BEADS/STOPS. PRIMER TO PAINTED AREAS. PLANTED ON SKIRTING DESIGN TO MATCH EXISTING. PARTITION TO RECEIVE ADDITIONAL ACOUSTIC TREATMENT ON ONE SIDE ONLY +50MM.



FLOOR 03

CDM regulations 2015 apply
© IDEA (Thinkidea Ltd). All rights reserved
Do not scale from drawing.
Dimensions to be checked on site
Drawing to be read in conjunction with all relevant schedules, specifications & consultants information