


**1** South West Elevation 1

Ref.05034





**SETTING OUT** - DO NOT SCALE from this drawing, use figured dimensions ONLY. If in doubt, ASK! Dimensions are shown to structural face generally, or to finished face of ducts and lining. All dimensions are shown in millimeters unless otherwise indicated. Angular dimensions are shown in decimal degrees to the nearest whole degree. Where items are to be fabricated off-site, site dimensions are to be used and confirmed prior to ordering or

elements refer to Structural Engineers drawings. **SERVICES** - For design, detailing & setting out of services, including SVP's, Gas, Water, Electrics & Telecoms etc refer to M&E Engineers and Structural Engineers drawings. FINISHES - For external wall finishes & wall types refer to Series

Type 4 El 30/15 Closed State Vertical Cavity Barrier (Compartment Wall)

Type 7 EI 30/15 Closed State Horizontal Cavity Barrier (Compartment Floor)

Type 2 El 30/15 Closed State Cavity Barrier Movement Joints within Masonry
Horizontal movement joints to be co-ordinated with masonry support. To be reviewed to conform with

Bat boxes within Masonry Bat boxes within Masonry

MVHR Vent

NOTE: FIRE RATING TO FACADES PROVIDED BY SHAFT

Denotes 60 min Fire Resistant Facade Denotes 90 min Fire Resistant Facade

Drawing to be read in conjunction with Setting Out Plans Cavity barriers will be included in any cavity where there is a

The areas that require cavity barriers are as follows:At the junction between an external cavity wall and a compartment wall that separates buildings; and at the top of such an external cavity wall;

At the junction between an external cavity wall and every compartment floor and compartment wall; At the junction between a cavity wall and every compartment floor, compartment wall, or other wall or door assembly that forms a fire-resisting barrier; Within the void behind the external face of rain screen

walls abutting the external wall;
At the edges of cavities (including around openings, i.e. All horizontal cavity barriers to be installed with a suitable cavity tray immediately above All vertical cavity barriers to be installed with a DPC

extending a minimum of 25mm into the cavity either

## To be read in conjunction with Elementa (Introba) Fire Strategy,

Facade Consultants' Specification & MTT Drawings &

Refer to Elementa (Introba) Fire Strategy for full information on alarm & detection systems, fire suppression systems, fire doors &

materials and components please refer to Façade Consultant's Refer to relevant **PTAL / DDU** series, including:

Series 21 - External Setting Out Plans
Series 22 - Internal Setting Out Plans
Series 35 - Reflected Ceiling Plans
Series 32 - Doors
Series 60 - Electrical Plans Series 67 - Fire Strategy Plans Series 70 - Apartment Plans Series 71 - Signage Where DDU drawing issued, this should supersede equivalent

PTAL drawing with the same number. Any issues please contact

Cavity barrier updates CONSTRUCTION ISSUE

17.10.23 CS ACS 24.02.23 CS ACS design delivery

77 Endell Street London WC2H 9DZ T +44 (0)20 7240 7766 W designdeliveryunit.com

St George North London Limited



Camden Goods Yard

Building B Setting Out Elevations SW Sheet7

As indicated @A0

20226

Practice Project No.

Client Project No. Originator Volume Level Type Role Number CGYB0-DDU-B0-ZZ-DR-A-05207

Description CONSTRUCTION

© Design Delivery Unit Ltd retain copyright of this drawing. It may not be copied, altered or reproduced in any way without their written authority.

Previous Drawing Number
CGYB0 - PTA - XXX - XX - DR - A - 05207 P1, Work in progress issue, 04.03.22