
QU	OT	AT	10	N	IS
BL	AC	KE	ED	0	UT

CERTASS




L1



- 1. Type: Flush Casement 89/69 ThermoTech (A), Ovolo
- 2. Sash profile: Ovolo
- 3. Glazing bead: Ovolo
- 4. Wood: Finger jointed pine
- 5. Finish: White paint "Teknos" RAL9016
- 6. Glass: 4 gr mat -16- 4 GNP gr (Low-E double glazing with sandblast and both toughened glass, Ug=1.1) (warm edge TGI white RAL 9016)
- 7. Glass sealing: Transparent silicone
- 8. Decorative transoms: 25mm Ovolo wooden bars glued on glass with duplex
- 9. Weight 81 kg.
- 10. $Uw \le 1.35$.

1800x990mm 1.78m² pcs 1





View from the outside L2 (1pcs)

- 1. Type: Flush Casement 89/69 ThermoTech (A), Ovolo
- 2. Sash profile: Ovolo
- 3. Glazing bead: Ovolo
- 4. Wood: Finger jointed pine
- 5. Finish: White paint "Teknos" RAL9016
- 6. Glass: 4 gr -16- 4 GNP gr (Low-E double glazing with both toughened panes, Ug=1.1) (warm edge TGI white RAL 9016)
- 7. Glass sealing: Transparent silicone
- 8. Fittings: window handle
- 9. Decorative transoms: 25mm Ovolo wooden bars glued on glass with duplex
- 10. Weight 47 kg.
- 11. Uw <= 1.38.

970x990mm 0.96m² pcs 1