



C4-N-03 1.10

Notes

 Do not scale this drawing.
 All dimensions must be checked on site and any discrepancies verified with the architect.

3. Unless shown otherwise, all dimensions are to structural surfaces. 4. Drawing to be read with all other issued information. Any discrepancies to be brought to the

attention of the architect. 5. This drawing is the copyright of Levitt Bernstein and may not be copied, altered or reproduced in any form, or passed to a third party without license or written consent.

This is not a construction drawing, it is unsuitable for the purpose of construction and must on no account be used as such.

Thermal Fabric Improvements

- Existing timber frames to be re-used where in good condition. Where repairs are required, damaged timber will be spliced with Douglas fir of the same grade and quality as the
- Existing glazing to be replaced with double glazing within existing frame and existing
- Sliding door to be re-used and glazing replaced with double glazing. Sliding mechanism is expected to take the weight of the double glazing. Where required the mechanism will be refurbished to keep it in good running order.
- Sealing around sliding door to be made good to improve air tightness
- Plywood opening vent to be insulated and repaired or replaced to improve thermal performance. Draught seals to be made good
- All windows to be re-finished with matching stain to existing

Notes: Dimensions are approximate and required to be checked and confirmed on site.

KEY:

Single glazing to be replaced with double vacuum glazing within existing douglas fir frame. Refer to Spec. L10 / 270

Review and re-seal window or door where Insulate plywood opening vent, replace

> openable panel. Refer to Spec. L10 / 280 Fixed secondary glazing to retained wire glass. Refer to Spec. L10 / 275

handle and re-seal and install secondary

Insulate plywood fixed panel. Refurbish and replace where required. Refer to Spec. L10 / 285

where required. Refer to Spec. L10 / 285

Refurbish or replace Plywood Fixed Panel

Replace louvred glass with top hung window

Refurbish operation and seals of window where broken Refer to Spec. L10 / 340

on winder. Refer to Spec. L10 / 290

Refurbish secondary glazing where missing, difficult to operate or broken.
Refer to Spec. L10/ 340

P3 10.11.23 - Planning & Listed Building Consent P2 07.04.22 - For comment P1 15.01.21 - Planning & Listed Building Consent CM

Drawing number

Alexandra Rd Estate

Emitter & Fabric Thermal Improvements

3467_LB_333008

Proposed - Unit Types C4 -Timber Frame North Elevation

Purpose of issue Date **PLANNING** 10.11.23 Drawn KS 1:10 @ A1 Checked PM Camden CC

levittbernstein.co.uk

London Thane Studios 2-4 Thane Villas London N7 7PA +44 (0)20 7275 7676

Manchester Bonded Warehouse Grape Street Manchester M3 3JE +44 (0)16 1669 8740

P3