



## Twinfix 2mm Solid Aluminium Roof System.



### Detailed description

Twinfix 2mm Solid Aluminium Roof.

This roof system is light weight, weather resistant, and easy to install. Can be powder coated to any RAL colour.

### Product guidance - As Standard

#### Material:

- 2mm pressed aluminium
- Extruded aluminium to BS 1474.

#### Finish:

Polyester powder coating to BS 6496.

#### Panel width:

250-350mm

#### Fire performance:

Aluminium is non-combustible  
The panel is not fire rated

#### Primary cladding fixings:

Stainless steel self-tapping screws as recommended by Twinfix.

#### Maximum unsupported span:

1500 mm down the slope, 250-350 mm panel width (assumed loadings; wind - 0.9 kN/m<sup>2</sup>; snow - 0.5 kN/m<sup>2</sup>).

#### Maximum unsupported overhang:

150 mm.

#### Minimum Pitch:

3°.

#### General:

- Polyester powder coating on both sides of sheet.

**Twinfix Limited**  
201 Cavendish Place  
Birchwood Park  
Birchwood  
Warrington  
Cheshire  
WA3 6WU

Tel: +44 (0)1925 811311

[www.twinfix.co.uk](http://www.twinfix.co.uk)  
[enquiries@twinfix.co.uk](mailto:enquiries@twinfix.co.uk)



## Product specification

### Manufacturer

- Name: Twinfix Limited
- Web: [www.twinfix.co.uk](http://www.twinfix.co.uk)
- Email: [enquiries@twinfix.co.uk](mailto:enquiries@twinfix.co.uk)
- Tel: +44 (0)1925 811311
- Fax: +44 (0)1925 852955
- Address: 201 Cavendish Place, Birchwood Park, Birchwood, Warrington, Cheshire WA3 6WU

**Product reference** Twinfix 2mm Solid Aluminium Roof System.

**Type** SA3

**Colour**

**Accessories** [None]

