

SOLID CONSERVATION

APPLICABLE

In public and residential buildings, where vintage looks from both inside and outside are required
 In heated, inhabited rooms
 In roof pitch range of 15°-90°

Suitable on all common roofings with proper flashing

FEATURES

Centre pivot wooden roof window
 Vintage design with black cladding elements and glazing bar
 Ventilation valve
 Toughened outer glass
 Elegant bottom handle
 Two passive ventilation positions via handle
 Double gasket system between frame and sash
 Double Low-e coating

Easy installation

10 year guarantee

MATERIAL | WOOD AND FINISHING

Kiln-dried laminated pine wood
 Timber from FSC certified forests
 Fungicide protection
 Water based lacquer

COVER PARTS

Aluminium, lacquered, black colour (RAL 9005)

HANDLE

Ergonomically designed moulded zinc handle, lacquered

HINGE

Pivot hinge



CVY B901

PANE

Construction	4-16-4H
Thickness of glazing (mm)	24
Low E	■ ■
Gas	Argon
Toughened	■
U _g (W/m ² K)	1.0
Total solar energy transmittance	0.55

WINDOW

U _w (W/m ² K)	1.3
Water tightness	E1350
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 (-1;-5) dB

COLOUR

Natural wood	■
--------------	---

MEASURES

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m ²
C4A	55 x 98 cm	55 cm	97,8 cm	39,8 cm	84,9 cm	37,3 cm	79 cm	0.295
F6A	66 x 118 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
M6A	78 x 118 cm	78 cm	117,8 cm	62,8 cm	104,9 cm	60,3 cm	99 cm	0.597

FLASHING RANGE FOR DIFFERENT ROOFING MATERIALS*



UNIVERSAL VINTAGE
 Suitable for high profiled tiles and profiled materials between 16-120 mm



PLAIN TILE
 For installation into plain tiles, max. overlapped thickness is 28 mm (2x14 mm), max. length is 340 mm. Suitable for a roof pitch range of 25° - 90°.



FLUSH FLASHING FOR SLATE
 For 40 mm recessed installation into slates and flat roofing, up to 8 mm (max overall thickness is 16 mm)

* Combi solutions are also available, please contact your dealer for details.

BLIND RANGE*




BLACKOUT



ROLLER



AWNING



ROLLER SHUTTER

contrio.com

*For the right product code of blinds, please take the type of blind, size of RW and colour code, e.g. DUA C2A 4219