



EN 14351-1:2006 + A2:2016

UAB „DOLETA“
Vilnius str. 52, Jieznas LT-59422, Lithuania

PRODUCT: Timber - aluminum *Doleta SCA68A* glass door

INTENDED TO USE: for application in residential and commercial construction

FRAME MATERIAL: SOFTWOOD (400 kg/m³ - 450 kg/m³)

GLASS UNIT (IGU): 38 mm (4mmXN-12Arg-4mm-14Arg-4mmXN)

EDGE SPACER: Swisspacer

REFERENCE WINDOW: 1230 mm x 2050 mm

DECLARED PERFORMANCE:

1	EN 12567-1	<i>Thermal transmittance</i>	U _w	1,1 W/m ² •K
2	EN 12207	<i>Air permeability</i>		Class 4
3	EN 12208	<i>Water tightness</i>		Class E1200
4	EN 12210	<i>Wind load resistance</i>		Class C5
5	EN 12400	<i>Mechanical durability</i>		Class 5
6	EN 12758	<i>Airborne sound insulation</i>		29 (-1;-5)
7	EN 410	<i>Solar energy transmission</i>	g	54%
8	EN 410	<i>Light transmission</i>		74%
9		<i>Frame thermal transmittance</i>	U _f	1,8 W/m ² •K
10		<i>Glass thermal transmittance</i>	U _g	0,7 W/m ² •K
11		<i>Spacer thermal conductivity</i>	Psi _g	0,04