





Reference	Location	Image	Description	Manufacturer	Cataloge No	IP Rating	Lamp	Colour	Dimensions	Efficacy	Notes
A	Bike Storage/Bin/Plantroom		Waterproof Surface Mounted	Whitecroft Lighting	ACL Industry	IP66 IK08	W LED 27.8W / 3970 lm	4000K	Length 1282 mm / Width 145 mm / Height 101mm	143 lm/W	DALI 2
A/E	Bike Storage/Bin/Plantroom		Waterproof Surface Mounted / Emergency	Whitecroft Lighting	ACL Industry	IP66 IK08	W LED 27.8W / 3970 lm	4000K	Length 1282 mm / Width 145 mm / Height 101mm	143 lm/W	DALI 2
B	Office Area		Surface Suspended	Orlight Lighting	SUS-BL-4K-1624 - Suspended Linear Fixture	IP20	LED 36W / 4129 lm	4000K		115 lm/W	DALI 2
B/E	Office Area		Surface Suspended / Emergency	Orlight Lighting	SUS-BL-4K-1624 - Suspended Linear Fixture	IP20	LED 36W / 4129 lm	4000K		115 lm/W	DALI 2
C	Stairs		Surface Mounted	XAL Lighting	VELA 450 direct	IP40	1 x LED 30 W / 3720 lm	4000K	ø 450mm / Height 92mm	124 lm/W	DALI 2
C/E	Stairs		Surface Mounted / Emergency	XAL Lighting	VELA 450 direct	IP40	1 x LED 30 W / 3720 lm	4000K	ø 450mm / Height 92mm	124 lm/W	DALI 2
D	External Lighting		Wall Mounted	Orlight Lighting	TOWER-2-BL	IP65	1 x LED from 3W	2700K			not DIM
D/E	External Lighting		Wall Mounted / Emergency	Orlight Lighting	TOWER-2-BL	IP65	1 x LED from 3W	2700K			not DIM
F	Coridor		Recessed	XAL Lighting	SASSO 40 048-2820417F 048-2896317 002-90745	IP20	1 x LED 9.9 W / 490 lm	2700K	ø 60mm / Height 50mm	49.49 lm/W	DIM/ DALI 2
F/E	Coridor		Recessed	XAL Lighting	SASSO 40 048-2820417F 048-2896317 002-90745	IP20	1 x LED 9.9 W / 490 lm	2700K	ø 60mm / Height 50mm	49.49 lm/W	DIM/ DALI 2
F1	Corridor/ Bathrooms		Recessed	XAL Lighting	SPADO 100 round down light		1 x LED 9.3 W / 935 lm	3000K		101 lm/W	not DIM/ DALI 2
F1/E	Coridor		Recessed / Emergency	XAL Lighting	SPADO 100 round down light		1 x LED 9.3 W / 935 lm	3000K		101 lm/W	not DIM/ DALI 2
F2	Apartment / Bedroom		Recessed	Orlight Lighting	ORL6009-HS-AW-9016	IP20	1 x LED 9.3 W / 935 lm	3000K		lm/W	DIM
F3	Apartment / Bathrooms		Recessed	Orlight Lighting	ORL6009-HS-AW-9016-IP44	IP44	1 x LED 7 W / 962 lm	3000K		lm/W	not DIM
G	Living Room / Kitchen		Ceiling Mounted	Orlight Lighting	HOXTON-1-BR-E27	IP20	TBC	TBC		lm/W	not DIM
EXIT 1	Coridor		Emergency Light	Whitecroft Lighting	EX3SWM/EP	IP20	1 x LED 4.8W	N/A		Length 237 mm / Width 46 mm / Height 246mm	DALI 2