

## **TECHNICAL DATA SHEET**

Revision: V2 22/11/2022

## **BauderGREEN KS ALU 250 inspection chamber system**

#### **DESCRIPTION**

The KS ALU 250 inspection chamber is fabricated from a perforated aluminium sheet with opening/lockable lid and is used for intensive and extensive soft landscaping, as well as ballasted inverted roofs. A simple on-site modification allows the unit to be used over outlets that are located close to wall or kerb abutments.

The KS ALU 250 is suitable for landscaping depths of less than 100mm. Where landscaping is deeper than 100mm, the 50mm or 100mm height adaptors can be added as necessary to achieve the required height to be level with or slightly proud of the surrounding landscaping.

#### **TECHNICAL DATA:**

### KS ALU 250 inspection chamber

Material: 1.5mm aluminium (2mm lid)

Length: 250mm Width: 250mm Height: 100mm Weight: 950g

Colour: Silver grey (RAL 9006)

# KS AE 50 chamber height adaptor (50mm)

Material: 1.5mm aluminium

Length: 250mm Width: 250mm Height: 50mm Weight: 250g

Colour: Silver grey (RAL 9006)

#### KS AE 250 chamber height adaptor (100mm)

Material: 1.5mm aluminium

Length: 250mm Width: 250mm Height: 100mm Weight: 450g

Colour: Silver grey (RAL 9006)



