

UKCA Marking Performance Document

This mark has been drafted in accordance with **BS EN 14782**. See the supporting technical file for how values are derived. Products intended use for self-supporting steel cladding for external walls and roofing supplies.

Product: HSL-32/1000 Box Profile - Plastisol

Gauge: 0.65mm

Top Side: 193µm Plastisol Leathergrain **Bottom Side:** 7µm Epoxy

Reaction to Fire: C-s2, d0

External Fire Performance: Class Broof (t1), (t2), (t3), (t4)

Resistance to Concentrated Force: 1.2kN at **2.2m** Span

<u>Essential Characteristics</u>	<u>Performance</u>	<u>Harmonised Technical Spec</u>
Mechanical Resistance: (Roofing Only): Water Permeability: Dimensional Change: Dimensional Tolerance: Release of Regulated Substances: External Fire Performance: (Roofing Only): Reaction to Fire:	1.2kN at 2.2m Span Deemed to Satisfy Steel 12 x 10 ⁻⁶ K-1 In Accordance with EN508-1 NPD Class Broof (t1), (t2), (t3), (t4) C-s2, d0	<u>BS EN 14782</u> 'Self-supporting metal sheet for roofing, external cladding and internal lining – Product Specification and Requirements.'
Identification of the construction product as required pursuant to Article 11(4):	Profile Depth (32mm), Gauge (0.65mm) Class 1, Steel (S220GD + AZ150). EN508-1	
Intended use or uses of the construction product, in accordance with the manufacturer:	Self-supporting steel sheet for use as roofing, external cladding and internal lining.	
Registered trade name and contact address of the manufacturer as required pursuant to Article 11(5):	Hornsey Steels Ltd, Riverlea, Bedstone Road, Bucknell, Shropshire, UK, SY7 0AQ.	
System of assessment and verification of constancy of performance of the construction product as set out in Annex V:	AVCP 4	
In case of the declaration of performance concerning a construction product covered by a harmonised standard:	The manufacturer has taken responsibility for initial type testing and implementation of factory production control in accordance with AVCP level 4.	

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Mr Samuel Hornsey
Company Director

Signature: 

Version: 3

Dated: May 2022



Southern Sheeting

ROOFING, CLADDING & SHEETING SUPPLIERS

Anthracite
Plastic Coated Leathergrain
Colour Ref: RAL 7016
www.southernsheeting.co.uk