

SRHG GLAZED ROOF HATCH

by [Surespan Limited](#)

Leamore Close

Walsall

United Kingdom

WS2 7NL

P: 01922711185

<https://surespancovers.com>

Surespan SRHG Glazed Roof Hatches are manufactured using thermally broken extruded sections as standard, offering clients excellent energy conservation properties and substantially reducing internal condensation or frost formation. Bespoke Made to any size. These glazed roof hatches can be operated by manual gas spring assisted up to 1200 x 1200mm or 24V DC actuators for larger sizes. Actuators can be offset and concealed for a seamless finish.

Surespan glazed roof access hatches incorporate a frameless design eliminating water ponding. The low profile frame with triple seals is structurally bonded to the 35.5mm sealed double glazed unit will comprise Pilkington 6mm toughened K polished all round outer pane, 20mm Warm Edge silver spacer Bar argon filled, Pilkington 9.5mm toughened & laminated inner pane.

Note: We recommend all glazed hatches to be installed on a 5° Pitch to stop water ponding.

Specifications

Standard

Glass Thickness	35.5 mm
Height	300 mm
Length	3000 mm
Width	3000 mm
Uniclass Code	Pr_30_59_36_74
Uniclass Name	Roof hatches
Insulating Glass Configurations	6-20-9.5
Noise Rating (Achievable)	35 dB
U-value (overall)	1.5 W/m ² k
Glazing Type	Double Glazed
Material	Aluminium, Stainless steel
Typical Use	Plant access, Roof Access, Roof maintenance

*Please note that these product properties are not a replacement for the manufacturer's literature and it is always recommended that Surespan Limited is consulted before specifying.

[Contact manufacturer](#)