





NEW 3000X6429MM WHITE POWDER COATED ALUMINUM BULKHEAD WITH FOLDED EDGES AND RETURN ON SIDES APPLIED TO EXISTING BULKHEAD STRUCTURE. ALLOW FOR 100MM WIDE HIDDEN LED CHANEL FRAME TO OUT SIDE EDGES AND SHINE LIGHT ON BULKHEAD. 50K LEDS FINISHED BLACK TO MATCH SIGNAGE. FINISH:9002 SIGNAL WHITE

REF: S1 - NEW 'ZEN' SIGN 600MM H X 50MM PROJECTION BLACK ALUMINUM POWDER COATED LETTERS WITH MATCHING SIDE REVEALS RAL: RAL 9005

DESIGN NARRATIVE.

IN ACCORDANCE WITH PLANNING REFUSAL OF EXISTING SIGNAGE, THE NEW SIGNAGE HAS BEEN DESIGN WITH A MAT WHITE POWDER COATED BULKHEADS TO REDUCE GLARE. REVISED SIGNAGE WITH BLACK NON ILLUMINATED AND REDUCED SIZE SIGNS TO MEET THE REQUIREMENTS OF SCALE TO SYMPATHETICALLY SUIT LOCAL STREET SCENE AND SHOP FRONT DESIGN.







REFERENCE IMAGE

EXISTING SIGNAGE PHOTOGRAPHS

AUI drawings to be read in conjunction with Structural Engineer's details & any relevant sub-contractor's details. All works to comply with current Building Regulations, British Standards & Codes If arwings to be read in conjunction with Structural Engineer's details & any relevant sub-contractor's details. All works to comply with current Building Regulations, British Standards & Codes If Practice. The Main Contractor & Sub-Contractor where applicable will be responsible for checking all dimensions on site & reporting any discrepancies to all relevant consultants. The Main Contractor & Sub-Contractor where applicable will be responsible for checking all dimensions must be verified on site prior to manufacture of any joinery or works on or off It. All dimensions to be in millimeters. I. All dimensions to be in millimeters. S. Contractor to ensure that all work meets the requirements of the EHO, Building Control, Fire Authority and all other statutory bodies. A. all shape if decoration to achieve Class O' surface spread of flame in accordance with B5476, Part 7, A. all stape if decoration to achieve Class O' surface spread of flame. A. all stape if decoration to achieve Class O' surface spread of flame. A. all stape if decoration to achieve Class O' surface spread of flame. A. all stape indecoration to achieve class O' surface corated are prepared for to the BHO in BENCH achieve Class O' surface spread of flame. A. Mile stand indecorating a schorece with thermoguard or similar to achieve	REV DATE	DESCRIPTION		DATE SCALE	DRG TITLE
				MAY 24 1:50@A1	ZEN HAPSTEAD
				JOB NO DRG NO 2367 01	PROJECT SIGNAGE DETAILS
Il new timber to be pressure impregnated with preservative prior to delivery to site. Where subsequent cutting & bonding is necessary all exposed faces to be coated with Protim.					