

APPENDIX B

33 CLEVELAND STREET, LONDON W1T 4HX

Flush Mount Ceiling Loudspeakers

Crestron Excite IC6-W-T

EXCITE IC6-W-T

Excite® 6.5" 2-Way In-Ceiling Speakers,
White Textured, Pair

Discontinued

This product has been discontinued. Please contact
Creston True Blue Support at 1-888-CRESTRON for a
replacement solution or more information.

Excite® speakers by Creston® offer great sound quality,
excellent value, and flexible installation in a range of popular
sizes and configurations.

Have a question?

Download PNG

Download JPEG

Resources

+ Specifications

+ Downloads & documentation



Find a Dealer

Features & Performance

Woofers	6.5 inch (165 mm) polypropylene w/rubber surround & steel basket
Tweeter	0.79 inch (20 mm) treated cloth dome w/swivel
Crossover	2nd order Linkwitz-Riley
Impedance	8 Ohms nominal
Frequency Response	55 Hz to 20 kHz (-3 dB)
Power Handling	75 Watts program
Sensitivity	89 dB @ 1W/1m
Coverage	100° conical (nominal)

Controls

LF	(1) 3-position low-frequency contour switch
HF	(1) 3-position high-frequency contour switch

Connections

Input	(2) spring terminals
-------	----------------------

Environmental

Temperature	41° to 104°F (5° to 40°C)
Humidity	10% to 90% RH (non-condensing)
For indoor use only	

Construction

Baffle	ABS plastic, white textured outer flange with black inner baffle, paintable
Grille	Perforated aluminum, white textured, paintable
Mounting	Flush ceiling mount using 4 integral toggle clamps, 1.5 in (39 mm) maximum surface thickness, 4.38 in (112 mm) minimum mounting depth, 8.4 in (214 mm) diameter recommended cutout

Dimensions

Diameter	9.67 in (246 mm)
Depth	4.66 in (119 mm)
Dimensions shown are per speaker	

Weight

4.1 lb (1.8 kg)