

elliott**wood**

Kingsway House Sustainable Drainage Strategy

KGH-EWP-ZZ-XX-RP-C-000001

Planning

P1

19.07.24

**Engineering a
Better Society**

© Elliott Wood



Document Control

	Remarks:	Issued for Information				
Revision: P1	Prepared by:	Folarin Awogbemila BEng	Checked by:	Tim Kenning BSurv	Approved by:	Tim Kenning BSurv
Date: 19.07.24	Signature:		Signature:		Signature:	

This report is for the sole use of GMS Estates for whom the report is undertaken and cannot be relied upon by third parties for any use whatsoever without the express authority of Elliott Wood.

Table of Contents

1.	Executive Summary	1
2.	Introduction	1
3.	Site Context	1
4.	Existing Drainage	3
5.	Existing Surface Water Run-off Rate	3
6.	Proposed Development	3
7.	Proposed Drainage and SuDS	4
8.	Pollution Prevention and Surface Water Treatment	5
9.	Operation and Maintenance Requirements	5
10.	Conclusion	6

Appendices

Appendix A:	Greenhatch Topographical Survey	A
Appendix B:	Thames Water Asset Records	B
Appendix C:	Clearview CCTV Report	C
Appendix D:	Modified Rational Method Calcs	D
Appendix E:	Greenfield Run-off Calc	E
Appendix F:	Blue Roof Calcs, Detail and Extents	F
Appendix G:	Camden Drainage Proforma	G
Appendix H:	Thames Water Pre-Dev Response	H

1. Executive Summary

Elliott Wood Partnership Ltd has been commissioned by GMS Estates to provide a Drainage Strategy Report to support the full planning application for the proposed redevelopment of Kingsway House, 99-103 Kingsway, London, WC2B 6QX.

The proposal is to develop the existing building to an apart hotel (Hotel Class C1). The objective is to retain the external envelope and the major structural elements utilizing the plan form to deliver a more environmentally and economically responsible proposal. This will consist of removing the internal floor plates and supporting the internal structure to allow for the installation of a RC frame with open floor plates and a new servicing core. The existing masonry façade and party wall would be retained with the introduction of a further storey at roof level as part of a newly constructed mansard.

The proposed surface water strategy will be to incorporate a blue roof on a section of the new roof which will be restricted to a maximum rate of approximately 1 l/s (for all storm returns up to and including the 1 in 100 year + 40% climate change event), which will provide a betterment to the existing surface water runoff rate. A blue roof system cannot be incorporated on the mansard roofs and was deemed unsuitable for locating under the proposed mechanical plant space on the roof due to potential future access/maintenance restrictions. As a result, the other roofs and small terraces will drain unrestricted as per the existing arrangement. Some of the blue roof areas are proposed to be overlain with green roofs. Green roofs increase the time of entry for surface water runoff entering the drainage network, reduce the volume of rainfall discharged off site and provide biodiversity and amenity benefits.

All foul drainage below ground floor level will be pumped by a submersible packaged pumping station which will protect the basement level from the risk of flooding from sewer surcharge.

2. Introduction

Elliott Wood Partnership Ltd has been commissioned by GMS Estates to provide a Drainage Strategy Report to support the full planning application for the proposed development of Kingsway House, 99-103 Kingsway, London, WC2B 6QX.

The purpose of this report is to explain the approach taken with regards to the below ground drainage strategy for the proposed development. It evaluates the selection of SuDS and highlights how the drainage disposal hierarchy has been followed.

The following documents have been reviewed during preparations for this SuDS Report:

- National Planning Policy Framework (NPPF) (2023)
- Planning Practice Guidance (PPG)
- The London Plan 2021
- Camden Local plan
- London Borough of Camden Strategic Flood Risk Assessment (SFRA), January 2024
- London Borough of Camden Local Flood Risk Management Strategy (LFRMS) 2022-2027
- CIRIA SuDS Manual

3. Site Context

3.1 Site Location

Kingsway House is located within the London Borough of Camden and sits centrally within the Kingsway Conservation Area. The site is located approximately 120m south of Holborn London Underground Station, along Kingsway. The site is bound by Parker Street to the north, Kingsway to the east and Great Queen Street to the south. Refer to Figure 1 for the site location plan.




Figure 1: Site Location

3.2 Existing Development

Kingsway House is an existing 9 storey (including lower ground floor) building located on the west side of the Kingsway between High Holborn and the Strand. It was constructed in approximately 1906-07. The ground and lower ground floors were previously occupied by retail and storage whilst the uppers were office usage. The whole building is currently let to charities on a meanwhile basis whilst the building is being marketed for an office let. The building is not listed.



Figure 2: Existing Development

3.3 Existing Site Topography

A topographic survey was undertaken by Greenhatch in August 2014 and a copy of this is included in **Appendix A**. The survey confirms that the external footway levels fall away from the site and towards Great Queen Street to the south of the site, Parker Street to the north of the site and Kingsway to the east of the site.

3.4 Underlying Site Geology and Hydrology

3.4.1 Geology

An intrusive site-specific ground investigation is yet to be completed on site. According to British Geological Survey (BGS) mapping, the sites bedrock geology is made up of clay, silt and sand which forms part of the London Clay Formation shown in Figure 3. BGS maps also suggest that most of the site is underlain by superficial deposits of sand and gravel referred to as Lynch Hill Gravel Member shown in Figure 4.




Figure 3: Bedrock Geology (BGS Records)




Figure 4: Superficial Geology (BGS Records)

3.4.2 Hydrology

The closest watercourse to the site is The River Thames, which runs approximately 750m south of the site. The site is not located near any Source Protection Zones or above any aquifers.

3.5 Flood Risk

Flood Zone 1 (low risk) is defined as land assessed as having a less than 1 in 1,000 annual probability of river or sea flooding in any given year. Flood Zone 2 (medium risk) is land assessed as having between a 1 in 100 and 1 in 1,000 annual probability of river flooding or between 1 in 200 and 1 in 1,000 annual probability of sea flooding in any given year. Flood Zone 3 (high risk) is land assessed as having 1 in 100 or greater annual probability of river flooding or a 1 in 200 or greater annual probability of sea flooding in any given year.

In accordance with the GOV.uk flood maps for planning, the site is located in Flood Zone 1, which is defined as land and property assessed as having less than a 0.1% (1 in 1,000) annual probability of flooding in any given year. The Environment Agency (EA) Flood Map for Planning can be found in Figure 5. After review of the relevant information, this development is considered to be at a **low risk** of flooding from rivers and the sea.




Figure 5: EA Flood Map

Surface water flooding may occur during intense or prolonged rainfall events where there is insufficient capacity within the ground or the existing drainage infrastructure which leads to overland flows.

Figure 6 is an extract from the Environment Agency Flood Risk from Surface Water and shows that there is a low risk of flooding within Kingsway and Parker Street and a medium risk of flooding in Great Queen Street to the south of the development. As noted in section 3.3 the external footway levels fall away from the site and towards to the surrounding roads.




Figure 6: Surface Water Flood Map

Reservoirs are artificially created lakes that are usually formed by building a dam across a river. If one of the dams failed then water could escape from the reservoir, resulting in land or property being flooded.

Figure 7 from the Environment Agency's online mapping indicates that the development site is located outside the maximum extent of flooding from reservoirs.




Figure 7: Reservoir Flood Map

4. Existing Drainage

4.1 Public Sewers

Thames Water asset maps show that there are several public sewers in the vicinity of the site as follows:

- A 1676x914mm combined sewer running from west to east beneath Parker Street north of the site.
- Two 1397x813mm combined sewers running from north to south beneath Kingsway east of the site.
- Two combined sewers sized 1219x813mm and 1219x762 running from west to east beneath Great Queen Street south of the site.




Figure 8: Thames Water Asset Records

Refer to **Appendix B** for a copy of the Thames Water asset location search.

4.2 Existing Drainage

A CCTV drainage survey of the existing below ground drainage was undertaken by Clearview Surveys Ltd in May 2024. The survey identified that the existing site drainage is combined and drains by gravity into the combined Thames Water sewers via three outfalls on the northern, eastern and southeastern areas of the site. All three outfalls are 150mm diameter vitrified clay pipes. Refer to **Appendix C** for a copy of the CCTV drainage plan.

5. Existing Surface Water Run-off Rate

The existing area breakdown for the development is shown in **Table 1**.

Table 1: Existing Area Breakdown

	Area (m ²)	Hectares (ha)	% of site
Existing Hardstanding	413	0.0413	100
Existing Soft Landscaping	0	0	0
Total	413	0.0413	100

The existing surface water run-off rates have been calculated based on the existing impermeable areas and using the Modified Rational Method as set out below.

$$Q = 2.78 \times I \times A \times C_v \times C_r$$

Where: I – Rainfall intensity (mm/h)

A – Drained areas (ha)

C_v – Volumetric Run-off Coef = 0.75

C_r – Routing Coefficient = 1.3

The full calculations are attached as **Appendix D**

Table 2: Existing Surface Water Discharge Rates

	Rate (l/s)
1 in 1-year event	3.6
1 in 30-year event	9.0
1 in 100-year event	11.4

5.1 Greenfield Run-off Rates

The Greenfield run-off rates have been calculated in line with the SuDS Manual C753 and the non-statutory standards for SuDS using the IH124 approach. The results are shown in **Table 3** below and are based on a site area of 0.0413ha. The calculations can be found in **Appendix E**

Table 3: Existing Greenfield Run-off Rate

Return Period	Rate (l/s)
Q _{bar}	0.16
1 in 1-year event	0.13
1 in 30-year event	0.36
1 in 100-year event	0.50

6. Proposed Development

6.1 Development Proposals

The proposal is to develop the existing building to an apart hotel (Hotel Class C1). The objective is to retain the external envelope and the major structural elements utilizing the plan form to deliver a more environmentally and economically responsible proposal. This will consist of removing the internal floor plates and supporting the internal structure to allow for the installation of a RC frame with open floor plates and a new servicing core. The existing masonry façade and party wall would be retained with the introduction of a further storey at roof level as part of a newly constructed mansard. Improvements to the building will consist of:

- New fire escape stairs
- Redesigned floor layout to provide spacious apart hotel rooms, FOH and lobby areas.
- BOH provided on each floor.
- Improved accessibility and circulation

7. Proposed Drainage and SuDS

7.1 SuDS / Surface Water Drainage

The surface water drainage system has been designed in accordance with the GOV.UK *Sustainable Drainage Systems: Non-statutory Technical Standards* and the London Plan.

The following drainage hierarchy has therefore been considered:

- Store rainwater for later use
- Use infiltration techniques, such as porous surfaces in non-clay areas
- Attenuate rainwater in ponds or open water features for gradual release
- Attenuate rainwater by storing in tanks or sealed water features for gradual release
- Discharge rainwater direct to a watercourse
- Discharge rainwater to a surface water sewer/drain
- Discharge rainwater to a combined sewer

7.1.1 Appraising the use of Rainwater Re-Use

Incorporating a rainwater harvesting system in this development has been discounted as there is insufficient space to locate the required tanks and associated equipment within the plant rooms.

7.1.2 Appraising the use of Infiltration Techniques

Infiltration is not possible as the building occupies the whole site.

7.1.3 Appraising the use of Open Water Features

Attenuating rainwater in open water features is not possible as the building occupies the whole site.

7.1.4 Appraising the use of Green/Blue Roofing

A green roof is proposed on a section of the main roof. Green roofs are not included as part of the storage strategy for surface water run-off, however green roofs provide interception benefits such as absorbing the first flush event and reduce water discharging from the site in low level storms, particularly intense short duration events in the summer months.

Green roofs can provide water quality, water quantity, amenity, and biodiversity improvements, along with reducing the urban heat island effect and can lead to CO2 removal associated with the natural processes of the vegetation.




Figure 9: Green Roof SuDS Pillars

A Blue roof is proposed on a section of the main roof. Flow control outlets within the blue roof system will release rainwater at a restricted rate.

7.1.5 Appraising the use of Permeable Surfacing

The proposed building footprint (including basement) occupies the full site area which precludes the use of permeable surfacing.

7.2 Evaluation of SuDS Techniques

Table 4: Evaluation of SuDS Techniques

SuDS technique	Included?	Comment
Rainwater reuse	N	Rainwater harvesting has been omitted from the scheme due to the lack of available plant space for such a system
Infiltration devices	N	The proposed building footprint (including basement) occupies the full site area which precludes the use of infiltration devices.
Attenuation in green infrastructure (i.e. green roofs, rain gardens etc.)	Y	Green roof overlays are proposed over the blue roof
Blue Roofs	Y	A Blue roof system is proposed on a section of the main roof. Flow control outlets within the blue roof system will release rainwater at a restricted rate.
Rainwater discharge direct to a watercourse	N	There are no watercourses located within the vicinity of the development.
Controlled rainwater discharge to a surface water sewer or drain	N	There are no surface water sewers located in the vicinity of the development.
Controlled rainwater discharge to a combined sewer	Y	It is proposed to discharge surface water to the combined sewer network via the existing outfalls.

7.3 Proposed Surface Water Drainage Strategy

The proposed surface water strategy is to incorporate a blue roof on a section of the new roof. This section of roof will be restricted to a maximum rate of approximately 1 l/s (for all storm returns up to and including the 1 in 100 year + 40% climate change event). The other roofs and terraces will drain unrestricted as per the existing arrangement. The introduction of the blue roof on the main roof will provide betterment to the existing surface water run-off rate, shown in Table 5.

Table 5: Existing and Proposed Surface Water Run-off Rates

	Existing Runoff (l/s)	Proposed Runoff Unrestricted (l/s)	Proposed Blue Roof Discharge Rate (l/s)	Total Proposed Runoff (l/s)
1 in 1	3.6	2.1	1.0	3.1
1 in 30	9.0	5.3	1.0	6.3
1 in 100	11.4	6.7	1.0	7.7
1 in 100 + 40%CC	N/A	9.4	1.0	10.4

A blue roof system on this scheme will allow rainwater to be captured and stored at high level in a shallow crate system, providing temporary attenuation at roof level, which can then be released at a controlled rate via the rainwater outlets to the below ground drainage network. Flow rates from the blue roofs are calculated by a blue roof manufacturer based on FEH22 rainfall data. These calculations and a preliminary drainage strategy layout can be found in **Appendix F**. A typical blue roof system is shown in Figure 10.




Figure 10: Typical Blue Roof Build up & Outlet

Some of the blue roof areas are proposed to be overlain with green roofs. Green roofs increase the time of entry for surface water runoff entering the drainage network and can subsequently reduce the volume of rainfall discharged off site. During dry periods green roofs can capture the first few millimetres of rainfall and attenuate it on site, however this cannot be quantified as it is assumed that the planted medium is saturated. Where green roofs are accessible or will be overlooked, they can provide an amenity benefit as they provide an aesthetically pleasing environment amongst an urban landscape. Green roofs also provide an area of biodiversity and aid with the urban greening effect. Inclusion of a variety of planting and vegetation on a green roof provides a natural environment for birds, bees, butterflies and invertebrates.



Figure 11: Example Green Roof

Refer to **Appendix G** for a copy of the completed London Borough of Camden Drainage proforma.

7.4 Proposed Foul Water Drainage Strategy

The existing below ground foul drainage network will be removed and replaced as part of the new development proposals.

All foul water drainage from ground floor and above will offset at high-level within the building, as designed by the M&E engineer, and drop to the existing sewer outfalls.

All foul water drainage serving the basement level will be pumped by a submersible packaged pumping station. The pumping station will include non-return valves to protect the basement level against sewer surcharge. The pumping station will include dual pumps in a duty/standby arrangement, alarms and control panel telemetry / links to a BMS system if available.

7.5 Pre – Planning Enquiry

A pre-planning enquiry has been submitted to Thames Water to check that the offsite sewers have sufficient capacity to accommodate the proposed development. Thames Water have confirmed that there is sufficient capacity. A copy of their response is contained within **Appendix H**.

8. Pollution Prevention and Surface Water Treatment

As part of the CIRIA SuDS Manual C753, Section 26 provides guidance regarding methods for managing pollution risks from surface water run-off. The development has been assessed in line with Table 26.2 of the SuDS Manual for the pollution hazard indices for different land use classifications. Refer to Figure 12.

TABLE 26.2 Pollution hazard indices for different land use classifications				
Land use	Pollution hazard level	Total suspended solids (TSS)	Metals	Hydrocarbons
Residential roofs	Very low	0.2	0.2	0.05
Other roofs (typically commercial/ industrial roofs)	Low	0.3	0.2 (up to 0.8 where there is potential for metals to leach from the roof)	0.05
Individual property driveways, residential car parks, low traffic roads (eg cul de sacs, homezones and general access roads) and non-residential car parking with infrequent change (eg schools, offices) ie < 300 traffic movements/day	Low	0.5	0.4	0.4
Commercial yard and delivery areas, non-residential car parking with frequent change (eg hospitals, retail), all roads except low traffic roads and trunk roads/motorways ¹	Medium	0.7	0.6	0.7
Sites with heavy pollution (eg haulage yards, lorry parks, highly frequented lorry approaches to industrial estates, waste sites), sites where chemicals and fuels (other than domestic fuel oil) are to be delivered, handled, stored, used or manufactured; industrial sites; trunk roads and motorways ²	High	0.8 ²	0.8 ²	0.9 ²

Figure 12: Table 26.2 Showing Pollution Hazard Indices

Table 26.3 of C753 reproduced below sets out the mitigation indices provided by SuDS features for discharge to surface water.

TABLE 26.3 Indicative SuDS mitigation indices for discharges to surface waters			
Type of SuDS component	Mitigation indices ¹		
	TSS	Metals	Hydrocarbons
Filter strip	0.4	0.4	0.5
Filter drain	0.4 ²	0.4	0.4
Swale	0.5	0.6	0.6
Bioretention system	0.8	0.8	0.8
Permeable pavement	0.7	0.6	0.7
Detention basin	0.5	0.5	0.6
Pond ⁴	0.7 ²	0.7	0.5
Wetland	0.8 ³	0.8	0.8
Proprietary treatment systems ^{5,6}	These must demonstrate that they can address each of the contaminant types to acceptable levels for frequent events up to approximately the 1 in 1 year return period event, for inflow concentrations relevant to the contributing drainage area.		

Figure 13: SuDS Mitigation Methods

Table 6: SuDS Mitigation Indices for Green Roofs (taken from the SuDS Manual Annex 5)

SuDS component	Total suspended solids (TSS)	Metals	Hydrocarbons
Green roofs	0.8-0.9	0.7-0.9	0.9

8.1 Roof Areas

The roof is considered to have a “very low” pollution hazard, generating 0.2 total suspended solids, 0.2 metals and 0.05 hydrocarbons.

The above tables show that green roofs are sufficient on its own to adequately treat runoff from commercial roofs. Mitigation indices for green roofs are shown to be higher than the pollution indices for commercial roofs.

9. Operation and Maintenance Requirements

Regularly inspecting of the surface water drainage network for blockages and clearing unwanted debris/silt from the system should improve the performance of the surface water network and decrease the need for future repairs.

The level and frequency of maintenance required on site to maintain the system is dependant on the type of facility. The type of maintenance will fall into one of three categories “regular maintenance”, “occasional” and “remedial maintenance”.

The drainage and SuDS elements used should after an initial inspection following completion be inspected monthly for the first 12 months and after significant storms, thereafter the following maintenance regime should be implemented and adjusted if the 12-month monitoring process has identified any issues.

Following completion of the development a management company will be set up/appointed to maintain all drainage services on site. It will be their responsibility to maintain the drainage network and SuDS elements.

The following sections tabulates the requirements for each SuDS element.

9.1 Blue Roofs

Maintenance of a blue roof system is critical to the viability of its function.

Table 7: Blue Roof Maintenance Schedule

Maintenance Schedule	Required Action	Typical Frequency
Regular inspections	Visually inspect the outlets to ensure no blockage has occurred	Quarterly and after severe storms
	Visually inspect the waterproofing system at all upstands, to ensure that it is firmly adhered to the detail that it is waterproofing	Annually and after severe storms
	Visually inspect underside of roof for evidence of leakage	Annually and after severe storms
	Remove debris and litter to prevent clogging of inlet drains	Six monthly and annually or as required
Regular maintenance	Cut back tree limbs that overhang the roof to give at least 1m clearance.	Annually
	If drain inlet has settled, cracked or moved, investigate and repair as appropriate	As required

The specific blue roof maintenance requirements shall be confirmed with the specialist manufacturer.

9.2 Green Roofs

Table 8: Green Roof Maintenance Schedule

Maintenance Schedule	Required Action	Recommended Frequency
Regular inspections	Inspect all components including soil substrate, vegetation, drains, irrigation systems (if applicable), membranes and roof structure for proper operation, integrity of waterproofing and structural stability	Annually and after severe storms
	Inspect soil substrate for evidence of erosion channels and identify any sediment sources	Annually and after severe storms
	Inspect drain inlets to ensure unrestricted runoff from the drainage layer to the conveyance or roof drain system	Annually and after severe storms
	Inspect underside of roof for evidence of leakage	Annually and after severe storms
Regular maintenance	Remove debris and litter to prevent clogging of inlet drains and interference with plant growth	Six monthly and annually or as required
	During establishment (ie year one), replace dead plants as required	Monthly (but usually responsibility of manufacturer)
	Post establishment, replace dead plants as required (where > 5% of coverage)	Annually (in autumn)
	Remove fallen leaves and debris from deciduous plant foliage	Six monthly or as required
	Remove nuisance and invasive vegetation, including weeds	Six monthly or as required

	Mow grasses, prune shrubs and manage other planting (if appropriate) as required – clippings should be removed and not allowed to accumulate	Six monthly or as required
Remedial actions	If erosion channels are evident, these should be stabilised with extra soil substrate similar to the original material, and sources of erosion damage should be identified and controlled	As required
	If drain inlet has settled, cracked or moved, investigate and repair as appropriate	As required

10.Conclusion

This Drainage Strategy report has been prepared by Elliott Wood Partnership on behalf of GMS Estates in support of a planning application submitted to the London Borough of Camden (“LBC”) application for the proposed redevelopment of Kingsway House, 99-103 Kingsway, London, WC2B 6QX.

The SuDS Hierarchy has been followed in order to employ the most suitable and practicable SuDS techniques to improve surface water run off rates from the site. The development will provide benefits to surface water runoff, water quality, amenity space and biodiversity through the incorporation of blue and green roofs.

Through the use of blue roof systems, the total peak surface water discharge rate from the site will be restricted to 10.4 l/s for all events up to and including the 1 in 100 year + 40% climate change allowance event, without flooding.



All foul drainage below ground floor level will be pumped by a submersible packaged pumping station which will protect the basement level from the risk of flooding from sewer surcharge.

There are three existing combined water connections to the Thames Water combined sewer network. It is proposed that foul and surface water from the development will discharge via these existing sewer outfalls. Thames Water have confirmed that there is sufficient capacity within their local sewer network to accommodate the estimated discharge from the development.

Appendices

Appendix A: Greenhatch Topographical Survey

Site Plan



OS Note:
Some services may have been omitted due to parked vehicles.
The Ordnance Survey tile is to be used as a guide only.

OS Buildings  Surveyed Buildings 

This survey has been orientated to the Ordnance Survey (O.S) National Grid (OSGB36) via Global Navigational Satellite Systems (GNSS) and the O.S. Active Network (OS Net).

The survey has been correlated to this point and a further one or more OSG36 points established to create a true O.S. bearing for angle orientation.

No scale factor has been applied to the survey therefore the coordinates shown are arbitrary & not true O.S. Coordinates which have a scale factor applied.

Please refer to Survey Station Table to enable establishment of the on-site grid.

Building Survey Legend:

Sht 1.00	Sill Height from FFL
Hht 2.12	Head Height from FFL
Sl 51.03m	Sill Level from defined datum.
HL 52.82m	Head Level from defined datum.
Susp Ceil: 2.00	Suspended Ceiling Height from FFL.
Struct Ceil: 3.00	Structural Ceiling Height from FFL.
Susp Ceil: 30.00m	Suspended Ceiling Level from datum.
Struct Ceil: 31.00m	Structural Ceiling Level from datum.
IFL: 100.00m	Internal Floor Level (General).
+100.00m	Internal Floor Level (Specific).

Legend:

	Buildings		Overhead Crane		CC	Imperial chamber	IMR	Reactor
	Conveyor Belt		Conveyor		PWC	Water	AW	Automatic balancer
	Crane		Crane		RQ	Roller	RL	Roller
	Grain		Grain		DQ	Down pipe	GP	Vertical pipe
	Lift machine		Conveyor Overhaul		BQ	Belt pump	GP	Granular gases
	Lift machine		Conveyor Overhaul		BQ	Belt pump	GP	Granular gases
	Lift machine		Conveyor Overhaul		BQ	Belt pump	GP	Granular gases
	Lift machine		Conveyor Overhaul		BQ	Belt pump	GP	Granular gases
	Lift machine		Conveyor Overhaul		BQ	Belt pump	GP	Granular gases
	100,000		Station and Name		WA	Water level	SL	Slip
	Water		WA		Water level	SL	Slip	Slip
	Air		Air		Air		Air	Air
	Time of Day		Time of Day		Time of Day		Time of Day	Time of Day
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air		Air		Air	Air
	Air		Air					

Rev	Date	Description	Drawn	Q. Ref.
-----	------	-------------	-------	---------



greenhatch
group

- Topographical Surveys
- Site Engineering
- Utility / CCTV Surveys
- Measured Building Surveys
- 3D Laser Scanning
- Revit & BIM Models

Rowan House
Duffield Road
Little Eaton
Derby

DE21 5DR

Tel (01332) 830044 Fax (01332) 830055
admin@greenhatch-group.co.uk
www.greenhatch-group.co.uk

St Albans Unit B, The Courtyard Alban Park St Albans Hertfordshire AL4 0LA	Newcastle 24 Riverside Studios Amethyst Road Newcastle Bus. Park Newcastle-U-Tyne NE4 7YL	Poland ul. Panewnicka 91 40-761 Katowice Poland
t. (01727) 854481	t. (01912) 736391	t. 0048 32 202 2292 www.greenhatch.pl

CLIENT

EMRYS
Architects

PROJECT

**Kingsway House
London**

TITLE

Existing Site Plan

SCALE A1@ 1: 100	DATE 05.08.14
DRAWN PG	QUALITY REF

Level datum	GPS
Grid orientation	GPS
Job number	20370

Drawing No.	Rev.
20370_01_P	0

Comment


"his plan should only be used for its original purpose. Greenhatch Group accepts no responsibility for this plan if supplied to any party other than the original client."

Drainage information (where applicable) has been visually inspected from the surface and therefore should be treated as approximate only.

Notes:

Appendix B: Thames Water Asset Records

Asset Location Search Sewer Map - ALS/ALS Standard/2014 2766004



The width of the displayed area is 500 m and the centre of the map is located at OS coordinates 530533,181402
The position of the apparatus shown on this plan is given without obligation and warranty, and the accuracy cannot be guaranteed. Service pipes are not shown but their presence should be anticipated. No liability of any kind whatsoever is accepted by Thames Water for any error or omission. The actual position of mains and services must be verified and established on site before any works are undertaken.

Based on the Ordnance Survey Map with the Sanction of the controller of H.M. Stationery Office, License no. 100019345 Crown Copyright Reserved.

NB. Levels quoted in metres Ordnance Newlyn Datum. The value -9999.00 indicates that no survey information is available

Manhole Reference	Manhole Cover Level	Manhole Invert Level
6103	20.46	15.8
6101	19.39	n/a
5101	20.68	16.78
5103	20.68	16.2
5102	20.65	15.7
6104	n/a	n/a
7104	19.18	14.84
6105	n/a	n/a
7103	18.98	n/a
7105	19.33	15.2
6211	n/a	n/a
7210	19.65	14.97
5202	20.92	17.51
5204	n/a	n/a
7202	n/a	n/a
7203	20.56	16.36
6201	n/a	14.6
6202	n/a	14.59
5501	23.29	19.58
5413	n/a	n/a
5405	23.48	19.04
5414	n/a	n/a
5415	n/a	17.56
5594	n/a	n/a
6515	n/a	n/a
651A	n/a	n/a
6514	23.7	21.1
6407	23.03	18.16
6513	23.45	20.17
641D	n/a	n/a
6411	n/a	n/a
6406	22.58	17.06
6511	23.71	n/a
6412	n/a	n/a
6413	n/a	n/a
641A	n/a	n/a
641B	n/a	n/a
641C	n/a	n/a
7402	n/a	n/a
7401	22.85	17.99
6512	24.12	n/a
6502	23.93	19.35
7510	24.18	n/a
5533	25.19	n/a
6602	n/a	n/a
6601	25.09	20.83
6604	24.71	n/a
46DH	n/a	n/a
46EC	n/a	n/a
46EB	n/a	n/a
4502	n/a	n/a
46DG	n/a	n/a
46DF	n/a	n/a
46DE	n/a	n/a
46DD	n/a	n/a
46DC	n/a	n/a
4501	n/a	n/a
4503	n/a	n/a
4504	n/a	n/a
4604	n/a	n/a
4506	n/a	n/a
5502	n/a	n/a
5503	n/a	n/a
5505	n/a	n/a
5506	n/a	n/a
5531	n/a	n/a
5602	25.05	n/a
5532	23.55	18.77
5504	n/a	n/a
5603	24.89	20.42
36BC	n/a	n/a
36BD	n/a	n/a
3605	24.74	20.67
3403	23.9	20.21
3502	n/a	n/a
3416	24.38	19.26
3503	n/a	n/a
3504	25.02	9.36
35DE	n/a	n/a
3417	n/a	n/a
3406	23.87	20.31
35DD	n/a	n/a
3501	n/a	n/a
3407	n/a	n/a
3405	n/a	n/a
35DG	n/a	n/a
3404	22.89	20.95
35DH	n/a	n/a
3604	n/a	n/a
4505	n/a	n/a
451A	n/a	n/a

Manhole Reference	Manhole Cover Level	Manhole Invert Level
46DJ	n/a	n/a
46DI	n/a	n/a
46ED	n/a	n/a
5203	22.28	n/a
321A	n/a	n/a
4215	n/a	9.65
3217	23.43	19.23
5205	21.26	16.61
4204	n/a	n/a
421A	n/a	n/a
2308	n/a	19.3
4303	n/a	n/a
3301	23.05	19.03
5302	n/a	n/a
5329	n/a	n/a
3303	n/a	n/a
3304	22.68	n/a
5303	21.4	n/a
53EG	n/a	n/a
53EF	n/a	n/a
43BD	n/a	n/a
53EE	n/a	n/a
4304	22.1	18.09
53DG	n/a	n/a
53DF	n/a	n/a
53DE	n/a	n/a
3306	22.7	18.79
5304	n/a	n/a
4401	n/a	18.95
2402	n/a	n/a
411A	n/a	n/a
3104B	24.26	n/a
3103B	n/a	9.75
4103B	23.59	19.65
311A	n/a	n/a
3103A	24	19.51
2101	22.93	18.43
5201	22.1	17.6
22BJ	n/a	n/a
22CA	n/a	n/a
4222	23.46	18.18
The position of the apparatus shown on this plan is given without obligation and warranty, and the accuracy cannot be guaranteed. Service pipes are not shown but their presence should be anticipated. No liability of any kind whatsoever is accepted by Thames Water for any error or omission. The actual position of mains and services must be verified and established on site before any works are undertaken.		



ALS Sewer Map Key

Public Sewer Types (Operated & Maintained by Thames Water)

	Foul: A sewer designed to convey waste water from domestic and industrial sources to a treatment works.
	Surface Water: A sewer designed to convey surface water (e.g. rain water from roofs, yards and car parks) to rivers or watercourses.
	Combined: A sewer designed to convey both waste water and surface water from domestic and industrial sources to a treatment works.
	Trunk Surface Water
	Trunk Foul
	Storm Relief
	Trunk Combined
	Vent Pipe
	Bio-solids (Sludge)
	Proposed Thames Surface Water Sewer
	Proposed Thames Water Foul Sewer
	Gallery
	Foul Rising Main
	Surface Water Rising Main
	Combined Rising Main
	Sludge Rising Main
	Proposed Thames Water Rising Main
	Vacuum

Notes:

- 1) All levels associated with the plans are to Ordnance Datum Newlyn.
- 2) All measurements on the plans are metric.
- 3) Arrows (on gravity fed sewers) or flecks (on rising mains) indicate direction of flow.
- 4) Most private pipes are not shown on our plans, as in the past, this information has not been recorded.
- 5) 'na' or '0' on a manhole level indicates that data is unavailable.

Sewer Fittings

A feature in a sewer that does not affect the flow in the pipe. Example: a vent is a fitting as the function of a vent is to release excess gas.

	Air Valve
	Dam Chase
	Fitting
	Meter
	Vent Column

Operational Controls

A feature in a sewer that changes or diverts the flow in the sewer. Example: A hydrobrake limits the flow passing downstream.

	Control Valve
	Drop Pipe
	Ancillary
	Weir

End Items

End symbols appear at the start or end of a sewer pipe. Examples: an Undefined End at the start of a sewer indicates that Thames Water has no knowledge of the position of the sewer upstream of that symbol, Outfall on a surface water sewer indicates that the pipe discharges into a stream or river.

	Outfall
	Undefined End
	Inlet

Other Symbols

Symbols used on maps which do not fall under other general categories

	Public/Private Pumping Station
	Change of characteristic indicator (C.O.C.I.)
	Invert Level
	Summit

Areas

Lines denoting areas of underground surveys, etc.

	Agreement
	Operational Site
	Chamber
	Tunnel
	Conduit Bridge

Other Sewer Types (Not Operated or Maintained by Thames Water)

	Foul Sewer
	Surface Water Sewer
	Combined Sewer
	Gully
	Culverted Watercourse
	Proposed
	Abandoned Sewer

- 6) The text appearing alongside a sewer line indicates the internal diameter of the pipe in millimetres. Text next to a manhole indicates the manhole reference number and should not be taken as a measurement. If you are unsure about any text or symbology present on the plan, please contact a member of Property Insight on 0845 070 9148.

Appendix C: Clearview CCTV Report

Appendix D: Modified Rational Method Calcs

Modified Ration Method for Brownfield Runoff

Project Number: 2220217
Project Name: Kingsway House
Date: 13/05/2024

Area (Ha) 0.0413

$Q = 2.78 \times C_v \times C_r \times I \times A$

Q = flow rate (l/s)
Cv = Volumetric Runoff Coefficient
Cr = Routing Coefficient
I - Rainfall intensity
A = Area (Ha)

Storm Return Period	Existing Discharge (L/S)
1yr	3.6
30yr	9.0
100yr	11.4
100yr+40%	16.0

Under summer rainfall conditions Cv ranges from 0.6 - 0.9, for fully impermeable areas value of 0.75 should be used.

The routing coeffieint varies between 1 and 2 and accounts for the effect of rainfall characterisits and catchment shape on the peak runoff magnitude.
The SuDS manual recommends a fixed value for Cr of 1.3 for design.

Rainfall intensity is calculated following Walling Procedure Volume 4 and is as follows:

1.0 Determination of M5-60 min and r

60 minute, 5 year storm (M5-60) has a rainfall depth

M5-60 20.000
Ratio r 0.4

2.0 Determination of M5-D

M5-D = Z1 (M5-60min)
Z1 is taken from A3.a or A.3b for values between 0.12 and 0.45 and for durations between 5 minutes and 48 hours read to 0.01.

Assuming 1yr 15min, 30yr 15 min, 100yr 15min

Z1 0.64
M5-15 12.8 mm

3.0 Determination of MT-D

MT-D is obtained from the relationship:
MT-D = Z2(M5-D)

Taken from Table A1 for 1yr return period 15min storm

Z2 = 0.62
M1-15= 7.9

Taken from Table A1 for 30yr return period 15min storm

Z2= 1.57
M30-15= 20.1

Taken from Table A1 for 100yr return period 15min storm

Z2= 1.99
M100-15= 25.5

4 Determination of point rainfall intensities

i= 31.744 mm/hr

i= 80.384 mm/hr

i= 101.888 mm/hr

5 Application of areal reduction factor

From chart A4 where area is less than 1km2
ARF= 1

Average 1yr intensity
31.7

Average 30yr intensity
80.4

Average 100yr intensity
101.9

Average 100yr+40% intensity
142.6

Appendix E: Greenfield Run-off Calc

Calculated by: folarin Awogbemila

Site name: Kingsway House

Site location: London

Site Details

Latitude: 51.51641° N

Longitude: 0.11998° W

Reference: 75643826

Date: May 21 2024 15:16

This is an estimation of the greenfield runoff rates that are used to meet normal best practice criteria in line with Environment Agency guidance “Rainfall runoff management for developments”, SC030219 (2013) , the SuDS Manual C753 (Ciria, 2015) and the non-statutory standards for SuDS (Defra, 2015). This information on greenfield runoff rates may be the basis for setting consents for the drainage of surface water runoff from sites.

Runoff estimation approach

IH124

Site characteristics

Total site area (ha): 0.1

Methodology

Q_{BAR} estimation method: Calculate from SPR and SAAR

SPR estimation method: Calculate from SOIL type

Notes

(1) Is Q_{BAR} < 2.0 l/s/ha?

When Q_{BAR} is < 2.0 l/s/ha then limiting discharge rates are set at 2.0 l/s/ha.

Soil characteristics

	Default	Edited
SOIL type:	2	2
HOST class:	N/A	N/A
SPR/SPRHOST:	0.3	0.3

(2) Are flow rates < 5.0 l/s?

Where flow rates are less than 5.0 l/s consent for discharge is usually set at 5.0 l/s if blockage from vegetation and other materials is possible. Lower consent flow rates may be set where the blockage risk is addressed by using appropriate drainage elements.

Hydrological characteristics

	Default	Edited
SAAR (mm):	611	611
Hydrological region:	6	6
Growth curve factor 1 year:	0.85	0.85
Growth curve factor 30 years:	2.3	2.3
Growth curve factor 100 years:	3.19	3.19
Growth curve factor 200 years:	3.74	3.74

(3) Is SPR/SPRHOST ≤ 0.3?

Where groundwater levels are low enough the use of soakaways to avoid discharge offsite would normally be preferred for disposal of surface water runoff.

Greenfield runoff rates	Default	Edited
-------------------------	---------	--------

Q_{BAR} (l/s):	0.16	0.16
1 in 1 year (l/s):	0.13	0.13
1 in 30 years (l/s):	0.36	0.36
1 in 100 year (l/s):	0.5	0.5
1 in 200 years (l/s):	0.58	0.58

This report was produced using the greenfield runoff tool developed by HR Wallingford and available at www.uksuds.com. The use of this tool is subject to the UK SuDS terms and conditions and licence agreement , which can both be found at www.uksuds.com/terms-and-conditions.htm. The outputs from this tool are estimates of greenfield runoff rates. The use of these results is the responsibility of the users of this tool. No liability will be accepted by HR Wallingford, the Environment Agency, CEH, Hydrosolutions or any other organisation for the use of this data in the design or operational characteristics of any drainage scheme.

Appendix F: Blue Roof Calcs, Detail and Extents

BLUE ROOF ATTENUATION AND OUTFLOW SUMMARY

PRIVATE & CONFIDENTIAL - NOT FOR DISTRIBUTION

Project Name:	99-103 Kingsway, Holborn, WC1B 6QY - Main Roof (<1 l/s) - Rev2		
Prepared for:	Elliott Wood		
Date:	17/06/2024		
ABG Project ID:	99-103KW	Calculator version:	1.35
Prepared by:	Matt Gledhill, matthew.gledhill@abgltd.com		
Notes/description:	Mix of green roof, soft and hard landscaping - TBC. Maintenance or pedestrian/amenity access only - TBC. Warm/inverted roof construction, with zero falls - TBC.		

Document/Drawing references:

Input Parameters - Rainfall Information (FEH22)

Return period:	100 years	As supplied by Client
Allowance for Climate Change:	40 %	As supplied by Client
OS grid reference selected for FEH data:	TQ 30250 81436	

Input Parameters - Roof Information

Total catchment area:	116 m ²	As supplied by Client
Attenuation area:	63 m ²	As supplied by Client
Maximum allowable runoff:	0.9 l/s	As supplied by Client

Output - Rainfall Calculation

Duration	Time to Empty	Restricted Outflow (l/s)
15 mins	2 hours and 30 minutes	0.8
30 mins	2 hours and 50 minutes	0.8
1 hour	2 hours and 50 minutes	0.9
2 hours	2 hours and 50 minutes	0.9
4 hours	2 hours and 20 minutes	0.7
6 hours	1 hour and 30 minutes	0.5
10 hours	0 hours and 20 minutes	0.2
24 hours	0 hours and 0 minutes	0.0
48 hours	0 hours and 0 minutes	0.0

Total attenuation required: 6 m³
Half empty time: 1 hours and 10 minutes.

Output - Recommended Blue Roof System

System Name:	ABG bluerroof VF HD 108mm
Description:	Blue roof depth of 108mm. No. of control positions TBC by design team, and also cross-referenced with the structural engineer's long-term deflection analysis. Additional 'tell-tale' parapet overflow outlets, may also be added by the architect.

Total attenuation capacity:	6.1 m ³
Number of Blue Roof outlets:	2

- Notes:
1. This document contains an estimate which has been prepared by ABG Ltd and is illustrative only and not a detailed design.
 2. Further details on the theories used in this estimate are available upon request from ABG. The values given for the performance of the system relate to testing, modelling and analysis of our systems obtained from laboratories and testing institutes. In line with our policy of continuous improvement the right is reserved to make changes to our systems without notice at any time.
 3. The estimate given in this report is based on the stated parameters as per the brief. If these parameters are not correct or have changed, ABG should be contacted to provide a revised estimate.
 4. This estimate is specific to the characteristics of ABG products/systems and is not applicable to other competitor products. The substitution of the whole or any component of this design for a material supplied from another source renders this estimate invalid.
 5. Final determination of the suitability of any information is the sole responsibility of the user. ABG will be pleased to discuss the use of this or any other product but responsibility for selection of a material and its application in any specific project remains with the user.

Blue Roof Estimate

1. DEFINITIONS

‘Consultant’ means ABG Geosynthetics Ltd and its legal successors. ‘Client’ means the person, firm, company or organisation for whom the Consultant is performing the Services. ‘Agreement’ means the contract referred to in Clause 2. ‘Services’ means the services to be performed by the Consultant in accordance with the proposal from the Consultant. ‘Project’ means the project or works for which the Client has commissioned the Services.

2. GENERAL

Unless and until a formal agreement is entered into, the Client’s acceptance of the proposal for Services from the Consultant or a request for some or all the Services to be performed by the Consultant, shall constitute a binding contract between the Client and the Consultant which contract will be subject to any terms and conditions contained or referred to in the aforementioned proposal and these terms and conditions. In the event of any conflict, the terms and conditions in the proposal shall prevail over these terms and conditions. The Agreement so formed shall supersede all previous understandings, commitments or agreements whether written or oral between the Client and the Consultant relating to the subject matter hereof. No person or entity shall have any rights in relation to this Agreement, whether as third parties or otherwise, save the parties to this Agreement. Should any term or condition of this Agreement be held to be unenforceable or invalid by the courts of any jurisdiction to which it is subject then such term or condition shall be disregarded and the remaining terms and conditions shall remain in full force and effect.

3. PERFORMANCE OF SERVICES AND SCOPE

The Consultant shall perform the Services using the degree of skill care and diligence to be expected from a consultant experienced in the provision of services of similar scope size and complexity. The Consultant shall use reasonable endeavours to complete the Services within the time or programme agreed but shall not be responsible for any delay beyond the reasonable control of the Consultant. The fee contained in the proposal is for the scope of services as defined therein. If not already contained in the proposal the Consultant and the Client shall agree as an initial activity an integrated project services programme to include the activities of all the parties to the Project relevant to the Services to be supplied by the Consultant. The aforesaid programme shall show the key dates for final information and the delivery of such to the Consultant so as to enable the Consultant to carry out the services in an efficient once through manner to achieve the programme delivery dates for the Services.

The Consultant provides various services including Design and Product use advice which is distinct from a Design Service. The Design Service may or may not attract a fee.

Where the Consultant’s services are of an advisory nature and dependent upon the degree of information and release thereof by the Client then the Client agrees that any reliance placed on the services by the Client shall take due account of such constraints.

4. CONFIDENTIALITY AND INTELLECTUAL PROPERTY RIGHTS

i. The Consultant and the Client shall keep confidential all information pertaining to the Services.
ii. Copyright for all reports, documents and the like produced by the Consultant in the performance of the Services shall remain vested with the Consultant but the Consultant shall grant an irrevocable royalty free license to the Client to use such reports, documents and the like for any purpose in connection with the Project.

5. LIABILITY

i. The Consultant shall be liable to pay compensation to the Client arising out of or in connection with this Agreement only if a breach of the duty of care in Clause 3 is established against the Consultant.
ii. Notwithstanding any other term to the contrary in this Agreement or any related document and whether the cause of action for any claim arises under or in connection with the Agreement in contract or in tort, in negligence or for breach of statutory duty or otherwise the Consultant shall have no liability to the Client in respect of any claim for loss or damage arising from acts of war or terrorism or arising from flooding, burst water mains or failed drainage or arising from any incidence of toxic mould or asbestos but otherwise in relation to any cause of action as aforesaid the total liability of the Consultant in the aggregate for all claims shall be limited to a sum equivalent to ten (10) times the fee payable under this Agreement or £50,000, whichever is the lesser, or such other sum as may be expressly stated in the Consultant’s proposal, and further but without prejudice to the aforesaid limit of liability any such liability of the Consultant shall be limited to such sum or sums as it would be just and equitable for the Consultant to pay having regard to the Consultant’s responsibility for the same and on the basis that all other parties appointed or to be appointed by the Client to perform related services in connection with the Project shall be deemed to have provided undertakings on terms no less onerous than this Agreement and shall be deemed to have paid to the Client such contribution as it would be just and equitable for them to pay having regard to their responsibility for any loss or damage and providing that it shall be deemed that such other parties have not limited or excluded their liability to the Client for such loss or damage in any way which may be prejudicial to the Consultant’s liability under this clause. Nothing in this clause shall operate to exclude or limit the Consultant’s liability for death or personal injury.
iii. The Client shall indemnify and keep indemnified the Consultant from and against all claims, demands, proceedings, damages, costs and expenses arising out of or in connection with this Agreement or the Project arising from acts of terrorism or arising otherwise in excess of the liability of the Consultant under this Agreement or which may be made in respect of events occurring after the expiry of the period of liability stated in this Agreement.
iv. No action or proceedings under or in connection with this Agreement shall be commenced against the Consultant after the expiry of one year from completion of the Services.
v. ABG Geosynthetics Ltd is not responsible for consequential, indirect or incidental losses.

6. INSURANCE

The Consultant shall arrange Professional Indemnity Insurance cover for the amount stated in Clause 5(ii). The Consultant will use all reasonable endeavours to maintain Professional Indemnity Insurance cover for the period stated in 5(iv) above, providing such insurance remains available to the Consultant at commercially reasonable rates.

7. CLIENT’S OBLIGATIONS

The Client shall supply, without charge and in such time so as not to delay or disrupt the performance of the Consultant in carrying out the Services, all necessary and relevant information, in his possession or available to him from his other agents or consultants and all necessary approvals or consents. Any deviation on any information from the proposal shall be confirmed in writing and any attendant consequential fees will be forwarded for approval by the Client before any changes are made. The Consultant shall not be liable for any consequential delays on site. Every reasonable effort will be made to mitigate against delays, however no liability for losses and costs will be accepted. The approval or consent by the Client to the Services shall not relieve the Consultant from any liability under this Agreement. All work undertaken by the Consultant must be ratified and signed off by the Client.

8. PAYMENT

i. The Client shall pay the Consultant for the Services in accordance with the proposal and this Agreement. If the Consultant performs any additional services or if the Services are delayed or disrupted for reasons beyond the reasonable control of the Consultant then the Consultant shall be entitled to such additional fees as are fair and reasonable in the circumstances. The Consultant may render an invoice at monthly intervals for services properly performed. The agreed invoice, or in the event of a dispute the undisputed element, shall be paid within 28 days of receipt of the invoice by the Client. Any invoice paid after this period will attract interest at 3% above the base rate of the central bank of the country of the currency of payment along with any collection costs which may occur.
ii. The Client shall not withhold any payment of any sum or part of a sum due to the Consultant under this Agreement by reason of claims or alleged claims against the Consultant unless the amount to be withheld has been agreed between the Client and the Consultant as due to the Client or such sum arises from an award in adjudication, arbitration or litigation in favour of the Client and arises under or in connection with the Agreement. Save as aforesaid all rights of set off at common law, in equity or otherwise which the Client may otherwise be entitled to exercise are hereby expressly excluded.

9. TERMINATION

If a party is in breach of a material term of this Agreement and despite written notice from the other party fails to remedy such breach within 30 days or such other period as may be agreed between the parties, then the other party shall be entitled to terminate this Agreement forthwith. The Consultant may seek to recoup costs incurred for works completed prior to termination.


10. DISPUTE RESOLUTION

Any dispute between the parties that cannot be settled by mutual agreement shall be referred for final settlement to the arbitration of a person agreed between the parties or failing such agreement appointed upon the application of either party by the President of the Chartered Institute of Arbitrators and the said arbitration shall be carried out in accordance with the Construction Industry Model Arbitration Rules 1998 or such other version current at the time of the referral under this clause. Where the Agreement is subject to a governing law other than that of England and Wales then any dispute between the parties that cannot be settled by mutual agreement shall be finally settled by arbitration in accordance with the UNCITRAL Arbitration Rules by one arbitrator appointed in compliance with the said Rules. In either case such rules as appropriate are deemed to be incorporated into this Agreement by reference.


11. COMPLIANCE WITH LAWS

This Agreement shall be governed by and construed in accordance with the law of England and Wales unless stated otherwise in the proposal for services from the Consultant.


Changes to the above terms and conditions will only be considered if agreed in writing as part of the appointment process prior to ABG Geosynthetics commencing work.



Rev:	Comments:	By:	Date:
Project: Blue Roof - Warm			
Title: Parapet Restrictor Chamber, SVP & Green Roof Detail			
Drawn by: RH		Date: 13/01/20	
Scale: NTS		Drawing Ref: BRST08	Rev: 1.03



Rev:		Comments:	
By:		Date:	
Project: Blue Roof - Inverted			
Title: Restrictor Chamber & Green Roof / Paved Details			
Drawn by: RH		Date: 07/07/23	
Scale: NTS		Drawing Ref: BRST02	Rev: 1.04
abg creative geosynthetic engineering ABG Ltd E7 Meltham Mills Road Meltham HD9 4DS West Yorkshire UK Tel: +44(0)1484 852096 Fax: +44(0)1484 851562 Email: geo@abgltd.com www.abgltd.com			
Retaining Walls Erosion Control Landfill Tunnels Green Roofs Landscaping Highways			



THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL RELEVANT ARCHITECTS, ENGINEERS AND SPECIALISTS DRAWINGS AND SPECIFICATIONS.

DO NOT SCALE FROM THIS DRAWING.

ALL DRAWINGS TO BE PRINTED IN COLOUR

- LEGEND
- EXISTING COMBINED WATER MANHOLE
 - EXISTING COMBINED WATER
 - PROPOSED BLUE ROOF EXTENT
 - EXISTING BUILDINGS
 - LOWER GROUND FLOOR EXTENT

NOT FOR CONSTRUCTION

P01	25.06.24	FAW	TKe	Issued for Information
Rev	Date	By	Chk	Description

ElliottWood

Fitzrovia • Wimbledon • Nottingham

• info@elliottwood.co.uk
• +44(0)20-7499-5888

Project

Kingsway House

London

Drawing Title

Proposed SuDS Strategy

Scale	EWP Project	Date	Drawn
1:100 @ A1	2230217	June 2024	FAW
Design Phase	Status	Revision	
For Information	S2	P01	
[Project]-[Origin]-[Function]-[Spatial]-[Form]-[Discipline]-[No.]			
2230217-EWP-ZZ-ZZ-DR-C-15000			

Appendix G: Camden Drainage Proforma

1. Project & Site Details	Project / Site Name (including sub-catchment / stage / phase where appropriate)	Kingsway House
	Address & post code	Kingsway House, 103 Kingsway, London, WC2B 6QX
	OS Grid ref. (Easting, Northing)	E 530545 N 181395
	LPA reference (if applicable)	
	Brief description of proposed work	Refurb of existing building to an Extended Stage Hotel use (Hotel Class C1)
	Total site Area	413 m ²
	Total existing impervious area	413 m ²
	Total proposed impervious area	413 m ²
	Is the site in a surface water flood risk catchment (ref. local Surface Water Management Plan)?	No
	Existing drainage connection type and location	Drains via gravity to a combined sewer
	Designer Name	Folarin Awogbemila
	Designer Position	Civil Engineer
Designer Company	Elliott Wood Partnership	

2. Proposed Discharge Arrangements	2a. Infiltration Feasibility		
	Superficial geology classification	N/A	
	Bedrock geology classification	London Clay Formation	
	Site infiltration rate	m/s	
	Depth to groundwater level	m below ground level	
	Is infiltration feasible?	No	
	2b. Drainage Hierarchy		
		<i>Feasible (Y/N)</i>	<i>Proposed (Y/N)</i>
	1 store rainwater for later use	N	N
	2 use infiltration techniques, such as porous surfaces in non-clay areas	N	N
	3 attenuate rainwater in ponds or open water features for gradual release	N	N
	4 attenuate rainwater by storing in tanks or sealed water features for gradual release	Y	Y
	5 discharge rainwater direct to a watercourse	N	N
	6 discharge rainwater to a surface water sewer/drain	N	N
	7 discharge rainwater to the combined sewer.	Y	Y
	2c. Proposed Discharge Details		
	Proposed discharge location	TW combined water sewer	
Has the owner/regulator of the discharge location been consulted?	Yes		

3. Drainage Strategy	3a. Discharge Rates & Required Storage				
		Greenfield (GF) runoff rate (l/s)	Existing discharge rate (l/s)	Required storage for GF rate (m ³)	Proposed discharge rate (l/s)
	Qbar	0.16			
	1 in 1	0.13	3.6		3.1
	1 in 30	0.36	9		6.3
	1 in 100	0.5	11.4		7.7
	1 in 100 + CC				10.4
	Climate change allowance used		40%		
	3b. Principal Method of Flow Control		Orifice		
	3c. Proposed SuDS Measures				
		Catchment area (m ²)	Plan area (m ²)	Storage vol. (m ³)	
	Rainwater harvesting	0		0	
	Infiltration systems	0		0	
	Green roofs	0	0	0	
	Blue roofs	116	63	6.8	
	Filter strips	0	0	0	
	Filter drains	0	0	0	
	Bioretention / tree pits	0	0	0	
	Pervious pavements	0	0	0	
	Swales	0	0	0	
	Basins/ponds	0	0	0	
	Attenuation tanks	0		0	
	Total	116	63	6.8	

4. Supporting Information	4a. Discharge & Drainage Strategy	Page/section of drainage report
	Infiltration feasibility (2a) – geotechnical factual and interpretive reports, including infiltration results	Section 7
	Drainage hierarchy (2b)	Section 7
	Proposed discharge details (2c) – utility plans, correspondence / approval from owner/regulator of discharge location	Appendix F & H
	Discharge rates & storage (3a) – detailed hydrologic and hydraulic calculations	Appendix F
	Proposed SuDS measures & specifications (3b)	Section 7
	4b. Other Supporting Details	Page/section of drainage report
	Detailed Development Layout	Appendix F
	Detailed drainage design drawings, including exceedance flow routes	Appendix F
	Detailed landscaping plans	Appendix F
	Maintenance strategy	Section 9
	Demonstration of how the proposed SuDS measures improve:	
	a) water quality of the runoff?	Section 7
	b) biodiversity?	Section 7
	c) amenity?	Section 7

Appendix H: Thames Water Pre-Dev Response



Mr Folarin Awogbemila
Elliott Wood Ltd
241 The Broadway
Wimbledon
Greater London
SW19 1SD



16 July 2024

Pre-planning enquiry: Confirmation of sufficient capacity

Site: Kingsway House, 103 Kingsway, Holborn, Greater London, WC2B 6QX

Dear Mr Awogbemila,

Thank you for Pre-planning application for the conversion of **2446sqm office & 364sqm commercial premises** for the use of **58 bed hotel & 126sqm commercial premises**.

We have completed the assessment of the foul water flows and surface water run-off based on the information submitted in your application with the purpose of assessing sewerage capacity within the existing Thames Water sewer network.

This confirmation is valid for 12 months or for the life of any planning approval that this information is used to support, to a maximum of three years.

You'll need to keep us informed of any changes to your design – for example, an increase in the number or density of homes. Such changes could mean there is no longer sufficient capacity.

If your proposals progress in line with the details you've provided, we're pleased to confirm that there will be sufficient sewerage capacity in the adjacent combined sewer network to serve your development.

Combined (foul & surface) Water discharge

Foul Units	Surface water flow	Sewer
Outfall 1: 19 beds	3.1 litres/sec	1219x813mm combined sewer in Great Queen Street
Outfall 2: 19 beds	4.1 litres/sec	1676x914mm combined sewer in Parker Street
Outfall 3: 20 beds & 126sqm commercial premises	3.1 litres/sec	1397x813mm combined sewer in Kingsway

When developing a site, policy 5.13 of the London Plan and Policy 3.4 of the Supplementary Planning Guidance (Sustainable Design And Construction) states that every attempt should be made to use flow attenuation and SuDS/Storage to reduce the surface water discharge from the site as much as possible.



In accordance with the Building Act 2000 Clause H3.3, positive connection of surface water to a public sewer will only be consented when it can be demonstrated that the hierarchy of disposal methods have been examined and proven to be impracticable.

Before we can consider your surface water needs, you'll need written approval from the LLFA (Lead Local Flood Authority) that you have followed the sequential approach to the disposal of surface water and considered all practical means.

The disposal hierarchy being:

1. rainwater use as a resource (for example rainwater harvesting, blue roofs for irrigation)
2. rainwater infiltration to ground at or close to source
3. rainwater attenuation in green infrastructure features for gradual release (for example green roofs, rain gardens)
4. rainwater discharge direct to a watercourse (unless not appropriate)
5. controlled rainwater discharge to a surface water sewer or drain
6. controlled rainwater discharge to a combined sewer.

Where connection to the public sewerage network is still required to manage surface water flows, we will accept these flows at a discharge rate in line with CIRIA's best practice guide on SuDS or that stated within the sites planning approval.

More detailed surface water hierarchies can be found within Local Planning Policies.

If the above surface water hierarchy has been followed and if the flows are restricted to a total of **10.3 litres/sec** for all storm events up to and including 1:100yr+40%CC, then Thames Water would not have any objections to the proposal.

Diversion

From our records we don't anticipate that any wastewater assets need to be diverted to accommodate your proposals.

Please see our [FAQ's leaflet](#) for additional information.

What happens next?

If not already done so, please submit your **S106 Connection Application**, giving us at least 21 days' notice of the date you wish to make your new connection(s).

If you've any further questions, please do not hesitate to contact me.

Yours sincerely,

A handwritten signature in black ink, appearing to read "Colins Akemche".

Colins Akemche

Clean & Waste Pre-Planning Engineer
Adoption Team - Service Delivery

elliottwood

Central London
The Building Society
55 Whitfield Street
London W1T 4AH
+44 207 499 5888

Wimbledon
The Building Society
241 The Broadway
London SW19 1SD
+44 208 544 0033

Nottingham
St Mary's Hall
17 Barker Gate
Nottingham NG1 1JU
+44 1158 223 148

www.elliottwood.co.uk
[@elliottwood_partnership](#)
[@the_building_society](#)

Engineering a Better Society

© Elliott Wood

