	access requirements to be con								
tem Code	Item	Quantity	Unit	Item Reference	Description	Finish	Accessories	Notes	Indicative Image
XT-001	Electronic lock & handle	14	pair	TBC	Salto XS4 Original+, DIN configuration, standard line Washington handle, with mechanical override (Euro profile cylinder)	Black chrome finish (BHMA687), black reader finish (RAL 7021)	Suitable intumescent pads to be installed on all fire- rated doorsets		
XT-002	Hinges (Jansen)	TBC	pair	From manufacturer's standard range to suit door requirements	Jansen	Polyester powder coated, to match door frame and leaf	-	-	-
XT-003	Hinges (Sunray)	TBC	pair	From manufacturer's standard range to suit door requirements	Sunray	Polyester powder coated, to match door frame and leaf	-	-	-
XT-004	Slide arm door closer	6	only	DC700A+DA /SS	Assa Abloy adjustable power size 3 to 6 door closer, delayed action, featuring Cam-Motion technology and guide rail	Polyester powder coated, to match door frame and leaf	Suitable intumescent pads to be installed on all fire- rated doorsets	Note 2	The second second
XT-005	Swing door operator	1	only	Assa Abloy SW300	Assa Abloy SW300 swing door operator, IP20	Polyester powder coated, to match door frame and leaf	Finger trap protection device (flatscan sensor), battery backup unit, push/ pull arm system as required double acting kit as required.	Note 2	
XT-006	Narrow profile mortice lockcase (deadlatch)	14	only	4750-X00-X (backset and handing to be confirmed)	Assa Abloy 4750 Euro profile cylinder deadlatch, narrow profile, square faceplate, backset TBC.	Steel with corrosion- resistant plating, satin aluminium finish faceplate and strike plate.	Intumescent kit jacket where fire-rated	Note 1; compatibility of lockcase with door systems to be confirmed	
XT-007	Narrow profile mortice lockcase (deadbolt)	3	only	2200-XXX (bolt type and backset to be confirmed)	Assa Abloy 2200 Euro profile cylinder deadlock, narrow profiel, square faceplate, backset TBC.	Steel with corrosion- resistant plating, satin aluminium finish faceplate and strike plate.	Intumescent kit jacket where fire-rated	Note 1; compatibility of lockcase with door systems to be confirmed	
XT-008	Intumescent kit (to suit narrow profile lockcases)	4	only	TBC	Assa Abloy intumescent kit to El120 doors	Graphite	To suit fire-rated mortice lockcases	Note 1; compatibility of lockcase with door systems to be confirmed	
XT-009	Electric strike and strike plate	1	only	TBC	Assa Abloy	TBC	TBC	Specification to be confirmed subject to client security requirements	_
XT-010	Espagnolette	3	only	555.466	Jansen espagnolette, travel 14mm, connecting thread M5	Face plate stainless steel ground and brushed	Fixings as required; compatible shoot bolts (as EXT-014 and EXT-015); espagnolette keeps (as EXT-016)	-	
XT-011	Shoot bolt (top)	3	only	555.418 (1.5m) or 555.499 (2.0m)	Jansen shoot bolt (top), Ø10 x 1.5mm, M5 thread, with locking spring	Galvanised steel	To be compatible with espagnolette (as EXT-013)	Bolt lengths to suit size of doors	
XT-012	Shoot bolt (bottom)	3	only	555.419 (1.42m)	Jansen shoot bolt (bottom) ø10, M5 thread	Galvanised steel	To be compatible with espagnolette (as EXT-013)	Bolt lengths to suit size of doors	
XT-013	Espagnolette keeps	3	only	555.475	Jansen additional set for secondary leaf, use in combination with espagnolette	Stainless steel	Fixings as required; to be compatible with espagnolette (as EXT-013)	-	:=:
XT-014	Shoot bolt set (Sunray)	4	pair	From manufacturer's standard range to suit door requirements	Sunray	Polyester powder coated, to match door frame and leaf	-	-	-
XT-015	PROTEC2 deadlock cylinder	14	only	TBC	Assa Abloy PROTEC2, Euro profile	To match lockcase	-	Dummy cylinders to be supplied by contractor.	_
XT-016	PROTEC2 90mm cylinder & turn	3	only	TBC	Assa Abloy PROTEC2, Euro profile	To match lockcase		Dummy cylinders to be supplied by contractor.	