



Simulation Settings

Rainfall Methodology	FEH-22	Analysis Speed	Normal	Additional Storage (m³/ha)	0.0
Summer CV	1.000	Skip Steady State	x	Check Discharge Rate(s)	x
Winter CV	1.000	Drain Down Time (mins)	240	Check Discharge Volume	x

Storm Durations

15	60	180	360	600	960	2160	4320	7200	10080
30	120	240	480	720	1440	2880	5760	8640	

Return Period (years)	Climate Change (CC %)	Additional Area (A %)	Additional Flow (Q %)
2	0	0	0

Results for 2 year Critical Storm Duration. Lowest mass balance: 98.35%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
15 minute summer	EX S9	10	23.808	0.018	1.0	0.0203	0.0000	OK
15 minute summer	EX S10	10	23.589	0.017	1.0	0.0198	0.0000	OK
15 minute summer	EX S11	10	23.533	0.083	5.7	0.0899	0.0000	OK
15 minute summer	2.000:50%	10	23.539	0.204	11.9	0.0000	0.0000	OK
15 minute summer	EX S12	10	23.539	0.319	24.8	0.3606	0.0000	SURCHARGED
15 minute summer	TW 1372mm SEWER	1	23.446	1.372	25.9	0.0000	0.0000	OK

Link Event (Outflow)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
15 minute summer	EX S9	1.000	EX S10	1.0	0.862	0.029	0.0066	
15 minute summer	EX S10	1.001	EX S12	1.0	0.089	0.029	0.0858	
15 minute summer	EX S11	2.000	2.000:50%	6.8	0.429	0.126	0.2714	
15 minute summer	EX S11	2.000	EX S12	10.9	0.342	0.201	0.4115	
15 minute summer	EX S12	1.002	TW 1372mm SEWER	25.9	0.650	0.262	1.2780	8.6