

## YORK STONE PAVING

SPECIFICATION
SALVAGED OR RECLAIMED YORK STONE PAVING TO MATCH EXISTING
APPROX 50MM THICK
LAID IN COURSES OF VARYING WIDTHS & LENGTHS
JOINTS
WASHED SHARP SAND JOINTS OR
LIME MORTAR JOINTS, BRUSHED BACK, COLOUR TO MATCH STONE OR SLIGHTLY
LIGHTER, WITH ECORIGHT PREMIXED JOINTING LIME MORTAR OR SIMILAR
AREAS
TERRACES



**GRAVEL** SPECIFICATION
HOGGIN: BREEDON GOLDEN AMBER GRAVEL
MADE FROM NATURAL HARD LIMESTONE, CRUSHED & GRADED
WITH RECESSED PLY EDGES
AREAS
PATHS



## **BRICK PAVING**

SPECIFICATION
VANDE MOORTEL ANCIENNE BELGIQUE COPPER BROWN (UNSANDED TUMBLED)
CLAY PAVER (183X43X83MM)
BUTT JOINTED WITH MIN. GAP
BRUSH SURFACE WITH KILN DRIED SAND AFTER LAYING
AREAS
PATHS



EG2 Norway Whad, 24 Heriford Road, N1 5GT T. 626 7275 7778 E. mall@lisashellarchiteds.co.uk

www.lisashellarchitects.co.uk

7 THE GROVE, LONDON N6 6JU

## HARD LANDSCAPING MATERIALS GRO7L/PH/101

N. T. S. @ A 3 DO NOT SCALE FROM THIS DRAWING REFER ALL DISCREPANCIES TO ARCHITECT

## **REVISIONS/ ISSUE**

27/09/24 ISSUE TO PLANNING FOR DOC APPROVAL