

FTXM-R / RXM-R

R-32 BLUEEVOLUTION

Indoor Units			FTXM20R	FTXM25R	FTXM35R	FTXM42R	FTXM50R	FTXM60R	FTXM71R
Capacity	UK Total Cooling	kW	1.95	2.44	3.32	4.11	4.89	5.86	6.94
	UK Sensible Cooling	kW	1.95	1.73	2.31	2.74	3.55	3.84	4.57
	Nominal Cooling	kW	2.0	2.5	3.4	4.2	5.0	6.0	7.1
	Nominal Heating	kW	2.5	2.8	4.0	5.4	5.8	7.0	8.2
Seasonal Efficiency (EN14825) COOLING	Energy Label		A+++	A+++	A+++	A++	A++	A++	A++
	Pdesign	kW	2.0	2.5	3.4	4.2	5.0	6.0	7.1
	SEER		8.65	8.65	8.65	7.85	7.41	6.90	6.2
	Annual Energy Consumption	kWh	81	101	137	187	236	304	401
Seasonal Efficiency (EN14825) HEATING	Energy Label		A+++	A+++	A+++	A++	A++	A+	A+
	Pdesign	kW	2.3	2.4	2.5	4.0	4.6	4.8	6.2
	SCOP		5.10	5.10	5.10	4.71	4.71	4.30	4.10
	Annual Energy Consumption	kWh	631	659	686	1189	1368	1562	2117
Air Flow Rate (Cooling)	High / Med / Low / Silent	m ³ /sec	0.175 / 0.125 / 0.095 / 0.072	0.175 / 0.127 / 0.095 / 0.068	0.188 / 0.130 / 0.100 / 0.070	0.198 / 0.150 / 0.108 / 0.072	0.263 / 0.233 / 0.190 / 0.138	0.278 / 0.233 / 0.197 / 0.152	0.282 / 0.250 / 0.203 / 0.167
Dimensions	Height	mm	295	295	295	295	299	299	299
	Width	mm	778	778	778	778	998	998	998
	Depth	mm	272	272	272	272	292	292	292
Weight		kg	10	10	10	10	14.5	14.5	14.5
Sound Pressure (Cooling)	High / Med / Low / Silent	dBA	41 / 33 / 25 / 19	41 / 33 / 25 / 19	45 / 33 / 29 / 19	45 / 39 / 30 / 21	44 / 40 / 36 / 27	46 / 42 / 37 / 30	47 / 43 / 38 / 32
Sound Pressure (Heating)	High / Med / Low / Silent	dBA	39 / 34 / 26 / 20	39 / 34 / 27 / 20	39 / 35 / 28 / 20	45 / 39 / 29 / 21	43 / 39 / 34 / 31	45 / 41 / 36 / 33	46 / 42 / 37 / 34
Sound Power (Cooling)		dBA	57	57	58	60	58	60	60

Outdoor Units			RXM20R9	RXM25R9	RXM35R9	RXM42R	RXM50R	RXM60R	RXM71R
Dimensions	Height x Width x Depth	mm	550 x 765 x 285	550 x 765 x 285	550 x 765 x 285	734 x 870 x 373	734 x 870 x 373	734 x 870 x 373	734 x 954 x 401
Weight		kg	32	32	32	49	49	49	55
Electrical Details	Power Supply		1ph	1ph	1ph	1ph	1ph	1ph	1ph
	Maximum Input Current (MCA)	A	8.93	9.71	9.76	10.36	14.54	15.09	19.78
	Max Fuse Size	A	10	16	16	16	16	16	20
Interconnection Wiring	Core / Cable size		3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 5/8 (15.9)
Pipework	Maximum Length	m	20	20	20	30	30	30	30
	Maximum Vertical Rise	m	15	15	15	20	20	20	20
	Precharged to	m	10	10	10	10	10	10	10
	Additional Charge	g/m	20	20	20	20	20	20	20
	Holding Charge	kg	0.76	0.76	0.76	1.10	1.15	1.15	1.15
Sound Pressure (Cooling)	Nominal	dBA	46	46	49	48	48	48	47
Sound Pressure (Heating)	Nominal	dBA	47	47	49	48	49	49	48
Sound Power (Cooling)		dBA	59	58	61	62	62	63	66
Operating Range (Cooling)	Min / Max	°CDB	-10 / 50	-10 / 50	-10 / 50	-10 / 50	-10 / 50	-10 / 50	-10 / 46
Operating Range (Heating)	Min / Max	°CWB	-21 / 18	-21 / 18	-21 / 18	-21 / 18	-21 / 18	-21 / 18	-15 / 18
Air Flow Rate (Cooling)	Nominal	m ³ /sec	0.600	0.472	0.600	0.777	0.777	0.777	0.817
Meets ETL criteria			•	•	•	•	•	•	

Accessories:

Accessory Ref	Description
EKRS21	Wire harness for S21 port for all marked (*) options
BRC073*	Wired remote control - connection cable required
BRCW901A03	3m extension cord required for wired remote controller BRC073
BRCW901A08	8m extension cord required for wired remote controller BRC073
K.CGM	Condensing unit guard (1150 x 1150 x 650)
K.CGS	Condensing unit guard (750 x 1150 x 460)
K.CWB90-2	Wall bracket (90kg, 500mm support arm)
K.DT1	Condensate drip tray for use with K.CWB90-2
KLIC-DDV3*	KNX interface for Split type systems
KRP413A15*	Adaptor PCB for remote on/off control - constant/pulse contact
KRP928A25*	Adaptor PCB for interface to Daikin centralised control systems
RTD-RA*	Adaptor PCB for Modbus connection and/or extended system functions

Notes & Features:

- › All fan coils are supplied with infrared remote controller ARC466A67 (7-day schedule timer)
- › All fan coils have auto restart after power failure
- › Wired controller, KLIC-DI and RTD-RA options cannot be combined
- › Night set mode
- › Air purification using Flash Streamer technology
- › Presence sensor and 2-area intelligent eye
- › 5 fan speeds can be selected; from high to super low
- › Heat boost function to reach set point quicker during start-up
- › Can be connected with R410A Mini VRV using BPMK boxes
- › RXM20-35R9 can reduce the sound power by a further 6 dB(A)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com