
2.4 ISS

The ISS is located at the northwest corner of the White Wing, where a combined below-ground drainage run exits the site and connects to the Montague Street public sewer. The existing run collects surface and foul water from the White Wing, Hirayama Studio, and possibly the neighbouring 1A Montague Street property. However, the record survey information in this area is incomplete, and the CCTV survey is needed to confirm the arrangement here, which is currently concealed by the portacabins.

The proposed ISS will be connected into the existing combined below-ground drainage network. Manholes that are currently beneath the portacabins must be diverted to accommodate the new ISS, as shown in the adjacent diagram.

For the ISS site, external water butts are also not considered appropriate either internally to the building, as it contains only electrical switchrooms where water tanks would present a hazard, nor externally, where their visual appearance would have a negative impact on the setting of the Museum in a highly visible public area. With that said, significant investment will be made within the proposals in re-landscaping the external space adjacent the new ISS and White Wing. This includes both paved and gravelled landscaped areas served by local run-off, and new trees planted within tree pits. This will therefore introduce new green landscaped infrastructure without requiring additional water from a water butt. The Museum acknowledges that additional prevention and control measures such as the removal of leaves in lightwells will be required as a result, but have committed to this in order to introduce further green infrastructure as part of the development.

The below-ground attenuation system by the SWEC building described in section 2.3 will provide attenuation for an volume of surface water equivalent to that falling on the proposed ISS roof, so the overall discharge from the Museum estate is reduced by an equivalent amount.









Fig. 9: ISS proposed below ground drainage drawing

Appendix A Below-ground drainage drawings








note

This drawing is to be read in conjunction with all relevant Architect's and Engineer's drawings and the specification.



<u>Notes</u>

- All proposals are to be verified following receipt of CCTV survey.

Α	31.08.23	UPDATED FOR PLANNING	LI
-	28.07.23	ISSUED FOR STAGE 3	Ė

BRITISH MUSEUM SOUTH WEST ENERGY CENTRE

PROPOSED
BELOW-GROUND DRAINAGE
ATTENUATION

drawn	checked
CM	LK
date	scale (original - A1)
JULY '23	1:100

Alan Baxter


75 Cowcross Street London EC1M 6EL tel 020 7250 1555 email aba@alanbaxter.co.uk

www.alanbaxter.co.uk

drg. no.	
1910/41/131	


Α

© COPYRIGHT



notes

 This drawing is to be read in conjunction with all relevant Architect's and Engireer's drawings and the specification.



2. All proposed below ground drainage alternations shown on this drawing are to be confirmed following receipt of the CCTV survey. A suitable contingency should be allowed for at this stage for additional diversions and manholes.

BRITISH MUSEUM SWEC AND ISS

- 28.07.23 ISSUED FOR STAGE 3

LK

Proposed ISS below ground drainage plan


Alan Baxter

75 Cowcross Street London EC1M 6EL tel 020 7250 1555 email aba@alanbaxter.co.uk


www.alanbaxter.co.uk


1910/041/420

10/041/420



Plan - Part 1





<u>Thames Water Utilities Ltd</u>, Property Searches, PO Box 3189, Slough SL1 4W, T 0800 009 4540 E searches@thameswater.co.uk I www.thameswater-propertysearches.co.uk

Appendix B Camden Council SuDS Proforma

13



GREATER **LONDON** AUTHORITY



	Project / Site Name (including subcatchment / stage / phase where appropriate)	British Museum, Energy Centre Programme
	Address & post code	Great Russell Street, London WC1B 3DG
	OS Grid ref. (Easting, Northing)	E 530020
	Os Grid Fel. (Easting, Northing)	N 181635
tails	LPA reference (if applicable)	
1. Project & Site Details	Brief description of proposed work	The British Museum is progressing with its strategy for transitioning to sustainable, low-carbon infrastructure. 2 new infrastructure buildings, the South West Energy Centre (SWEC) and a new Intake Substation (ISS), are proposed.
	Total site Area	530 m ²
	Total existing impervious area	530 m ²
	Total proposed impervious area	530 m ²
	Is the site in a surface water flood risk catchment (ref. local Surface Water Management Plan)?	The site is within Critical Drainage Area Group 3_005.
	Existing drainage connection type and location	Into existing combined drainage run on Museum site.
	Designer Name	Cara Malcolm
	Designer Position	Engineer
	Designer Company	Alan Baxter Ltd

	2a. Infiltration Feasibility			
	Superficial geology classification River		Terrace sands & gravels	
	Bedrock geology classification	London Clay		
	Site infiltration rate N/A		m/s	
	Depth to groundwater level 3.85 - 3.9		m below ground level	
	Is infiltration feasible?		No	
	2b. Drainage Hierarchy			
ements			Feasible (Y/N)	Proposed (Y/N)
ange	1 store rainwater for later use		N	N
ırge Arr	2 use infiltration techniques, such surfaces in non-clay areas	N	N	
d Discha	3 attenuate rainwater in ponds or open water features for gradual release		N	N
2. Proposed Discharge Arrangements	4 attenuate rainwater by storing in tanks or sealed water features for gradual release		Υ	Υ
2. P	5 discharge rainwater direct to a watercourse		N	N
	6 discharge rainwater to a surface water sewer/drain		N	N
	7 discharge rainwater to the comb	Υ	Υ	
	2c. Proposed Discharge Details			
	Proposed discharge location Existing combined drainage run on s		e run on site.	
	Has the owner/regulator of the discharge location been Yes - owned by consulted?		owned by app	licant.



These are the theoretical storage volumes required to limit flows to greenfield rates. However, it is not possible to limit flows to greenfield rates.

	3a. Discharge Rates & Required Storage				
		Greenfield (GF) runoff rate (I/s)	Existing discharge rate (I/s)	Required storage for GF rate (m ³)	Proposed discharge rate (I/s)
	Qbar	0.08			><
	1 in 1	0.1	8.4	12	2
	1 in 30	0.2	20	30	2
	1 in 100	0.3	25.4	42	2
	1 in 100 + CC		><	50	2
	Climate change allowance used		40%		
rategy	3b. Principal Method of Flow Control		Vortex flow control device (Hydrobrake or similar), subject to detailed design.		
e Stı	3c. Proposed SuDS Measures				
Drainage Strategy			Catchment area (m²)	Plan area (m²)	Storage vol. (m ³)
3. [Rainwater harvesting		0		0
	Infiltration systen	ns	0		0
	Green roofs		0	0	0
	Blue roofs		0	0	0
	Filter strips		0	0	0
	Filter drains		0	0	0
	Bioretention / tre	· ·	0	0	0
	Pervious paveme	nts	0	0	0
	Swales		0	0	0
	Basins/ponds		0	0	0
	Attenuation tanks		530		24
	Total		530	0	24

GREATER **LONDON** AUTHORITY



	4a. Discharge & Drainage Strategy	Page/section of drainage report
	Infiltration feasibility (2a) – geotechnical factual and interpretive reports, including infiltration results	Pages 3-4
	Drainage hierarchy (2b)	Pages 3-4
no	Proposed discharge details (2c) – utility plans, correspondence / approval from owner/regulator of discharge location	Appendix A
4. Supporting Information	Discharge rates & storage (3a) – detailed hydrologic and hydraulic calculations	Appendix C
ting Inf	Proposed SuDS measures & specifications (3b)	Page 4
ğ	4b. Other Supporting Details	Page/section of drainage report
Sup	Detailed Development Layout	Appendix D
4. Sup	Detailed Development Layout Detailed drainage design drawings, including exceedance flow routes	Appendix D Appendix A
4. Sup	Detailed drainage design drawings,	
4. Sup	Detailed drainage design drawings, including exceedance flow routes	Appendix A
4. Sup	Detailed drainage design drawings, including exceedance flow routes Detailed landscaping plans	Appendix A
4. Sup	Detailed drainage design drawings, including exceedance flow routes Detailed landscaping plans Maintenance strategy Demonstration of how the proposed SuDS	Appendix A
4. Sup	Detailed drainage design drawings, including exceedance flow routes Detailed landscaping plans Maintenance strategy Demonstration of how the proposed SuDS measures improve:	Appendix A N/A Page 5

Appendix C Discharge Rate Calculations