





Appendix A



SCHEDULE of LUMINAIRES

Communal							
Ref	Luminaire Description/ Control Gear	Manufacturer	Details	Mounting/ Suspension Type	Lamp Type/ Temperature/ Colour	Remarks	Location
A	LED surface mounted luminaire c/w a spun aluminium base with opal diffuser.	Ansell Lighting Eclipse MultiLED CCT Ref: AECLED/W	Dimensions: 435mm dia x 100mm	Surface	Complete with 4000K LED. Luminaire input power: 25 W Luminaire luminous flux: 2800 lm		Corridors & Stairs
AE	As Type A however, E denotes c/w integral self-test, emergency lighting circuit	Ansell Lighting Eclipse MultiLED CCT Ref: AECLED/W	As Type A	As Type A	As Type A however, E denotes with emergency output	As Type A	Corridors & Stairs
B	LED IP65 Surface Mounted Luminaire	Ansell Lighting Tornado Evo Ref: ATORE	Dimensions: 1500mm x 80mm x 96mm	Surface	Complete with 4000K LED. Luminaire input power: 30 W Luminaire luminous flux: 4700 lm		Refuse Stores, Mobility scooter storage, Plant Room, Cycle Store & Risers
BE	As Type B however, E denotes with integral self-test, emergency lighting circuit	Ansell Lighting Tornado Evo Ref: ATORE	As type B	As type B	As Type B however, E denotes with emergency output	As Type B	Refuse Stores, Mobility scooter storage, Plant Room, Cycle Store, Riser Access Room





TOTTENHAM MEWS

C	Surface IP65 LED Bulkhead	Ansell Lighting ARX Bulkhead REF: ARXB	Dimensions: 350mm dia x 110mm	Surface	Complete with 4000K LED. Luminaire input power: 18 W Luminaire luminous flux: 2200 lm		External Walkway
CE	As Type C however, E denotes with self-test, emergency lighting circuit	Ansell Lighting ARX Bulkhead REF: ARXB	As type C	As type C	As type C, but E denotes with emergency output	As Type C	External Walkway
D	Suspended Linear Luminaire c/w 30W LED Lamps (or Equivalent)	Thorlux Lighting Hi-Bar Low Glare Individual REF: HB18692	Dimensions: 1516mm x 57mm x 100mm	Suspended	Complete with 4000k LED Luminaire input power: 30 W Luminaire luminous flux: 2975 lm		Office
DE	As Type D however, E denotes with self-test, emergency lighting circuit	Thorlux Lighting Hi-Bar Low Glare Individual REF: HB18692	As type D	As type D	As type D, but E denotes with emergency output	As type D	Office
F	Recessed IP65 LED Downlighter C/W 7W GU10 LED Lamp	Thorlux Lighting GT15085	G3 8W 1120 Lumen Output LED IP65 Clear Glass	Recessed	4000K		External Areas – Under Canopies

TOTTENHAM MEWS

FE	As Type F however, E denotes with self-test, emergency lighting circuit	Thorllux Lighting EGT15085L	As F Type	Recessed	As F Type		External Areas – Under Canopies
G	Surface Mounted IP65 LED Luminaire			Surface			External Areas
GE	As Type G however, E denotes with self-test, emergency lighting circuit		As type G	As type G	As type C, but E denotes with emergency output	As Type G	External Areas
Residential							
Ref	Luminaire Description/ Control Gear	Manufacturer	Details	Mounting/ Suspension Type	Lamp Type/ Temperature/ Colour	Remarks	Location
A	Recessed Downlighter c/w 7W LED lamps (Minimum Output)	As Electrical Contractors Technical Submission		Recessed			Bedrooms, Hallways, Kitchens & Living Rooms

TOTTENHAM MEWS

B	Ceiling Mounted IP65 Bulkhead c/w LED Lamp	As Electrical Contractors Technical Submission		Surface			WCs & Accessible Shower Rooms
C	Bulkhead Luminaire c/w LED Lamp	As Electrical Contractors Technical Submission		Surface			Wheelchair Changing
D	Wall Mounted IP65 External Luminaire c/w GU10 LED Lamp (Min 5W)	As Electrical Contractors Technical Submission		Surface			Flat Entrances
E	Overmirror LED Light	As Electrical Contractors Technical Submission		Surface			Bathrooms

TOTTENHAM MEWS

Notes

1. Samples of all luminaires and signage to be provided to the client. All samples to be agreed and signed off with the client, architect, and services engineer.

