



All hardware to be black finish, colour shown on hardware on elevation drawing for illustrative purposes

Frame Colour	
External/Internal	Ral 9016 (White)
Sash Colour	
External	Ral 5013 Blue
Internal	Ral 5013 Blue
Frame & Sash Material	
Frame	Hardwood Frame
Sash	Flamebreak Door Sash FD30
Lippings	8mm Hardwood lippings all around
Threshold	Exitex MXS-15-72 Aluminium
Rain Deflector	Accoya rain deflector
Glass Spec Door Sash	
External Pane	8.8mm Optilam KS Reeded
Spacer Bar	Aluminium Spacer bar
Internal Pane	7mm Pyrodur 30-105 Clear
Glazing Tape	Ceramic Fiber Tape White
Mastic Pointing	Pointed external side only (External doors)
Glass Spec Fanlight	
External Pane	6.8mm Laminated Low-E
Spacer Bar	Aluminium Spacer bar
Internal Pane	7mm Pyrodur 30-105 Clear
Glazing Tape	Ceramic Fiber Tape White
Mastic Pointing	Pointed external side only (External doors)
Intumescent & Hardware	
Intumescent	10x4 Pyroplex Fitted In Frame
Intumescent	15x4 Pyroplex Fitted In Door Sash Head
Intumescent	10x4 Pyroplex Fitted bottom of sash
Intumescent	25x4 Pyroplex fitted in threshold
Gasket	Aquatex A10 White Weather Seal
Handle	Black Lever/Lever Door Handle
Cylinder	1 Star Cylinder thumb turn
Cylinder Guard	Winkhaus Armor shield
Hinge	4No S5 Zoo Butt Hinges
Lock	Winkhaus AV2 Lock
Door Viewer	Black Door Viewer
Door Knocker	Black Door knocker
Letterplate	Black Letterplate with internal security cowl
Door chain	Black door chain (Sent loose to site)
Door closer	Rutlands TS.11205 cam action closer (SILVER)
Door Plugs & Labels	
All door fitted with Yellow core plug and fitted with the inner trees listed below	
Silver Tree	Factory hung doorset
Orange Tree	Factory fitted glass
PAS24 Label	Fitted to all doors
NFC Tag	Fitted to all doors



Client: 

Project: Camden Ref Bourne Estate

Type Ref: Flat 14 Buckridge Pilot Plot Door 1 Example of Reeded Glass

Dwg No: 01 Date: 08-04-25 Rev:



Example of Reeded Glass, Lines to be vertical door sash Only

Glass make up
 External Pane: Pilkington Texture Reeded
 4mm-Clear PVB Interlayer-Pilkington Optifloat
 Clear BF 4mm
 Spacer Bar :8mm Aluminium spacer bar
 Internal Pane :7mm Pyrodur 30-105 Clear

Glass Integrity 30min Fire/15min Insulation

All Elevations Viewed Externally