



SYNTEGRA CONSULTING
Intelligent & Green Building Solutions

Energy Strategy Report – Planning Application

14th November 2013

**The Lion, 2 Britannia Street, London,
WC1X 9JE**

Table of Contents

1. EXECUTIVE SUMMARY.....	5
2. INTRODUCTION.....	7
3. THE DEVELOPMENT CONFIGURATION SCHEME	10
4. BASELINE CO2 EMISSIONS	12
5. BE LEAN – ENERGY EFFICIENT DESIGN.....	14
6. BE CLEAN – CHP & DECENTRALISED ENERGY NETWORKS	16
7. BE GREEN – RENEWABLE ENERGY.....	19
8. CONCLUSION.....	23
9. APPENDIX.....	24

The Lion, 2 Britannia Street, London, WC1X 9JE



1 Elevation scale 1:50



1 Elevation scale 1:50

Revision:	-			
Date:	14/11/2013			
Prepared by:	RN			
Checked by:	NP			
Authorised by:	AWK			

Limitations

Syntegra Consulting Ltd ("SC") has prepared this Report for the sole use of **Little Venice Developments** ("Client") in accordance with the Agreement under which our services were performed. No other warranty, expressed or implied, is made as to the professional advice included in this Report or any other services provided by SC. This Report is confidential and may not be disclosed by the Client or relied upon by any other party without the prior and express written agreement of SC.

The conclusions and recommendations contained in this Report are based upon information provided by others and upon the assumption that all relevant information has been provided by those parties from whom it has been requested and that such information is accurate. Information obtained by SC has not been independently verified by SC, unless otherwise stated in the Report.

The methodology adopted and the sources of information used by SC in providing its services are outlined in this Report. The work described in this Report was undertaken in **November 2013** and is based on the conditions encountered and the information available during the stated period of time. The scope of this Report and the services are accordingly factually limited by these circumstances.

This renewable report and SAP pre-assessment modelling were generated based on the provided drawings and building information assumptions. Although every effort has been made to provide accurate content within this report, SC makes no warranty or assumes no legal liability or responsibility for the accuracy or completeness of information contained in this report.

SC also wishes to make aware that this document is guidance only on energy strategy and should not be seen as a building design document. It is the responsibility of the APPOINTED BUILDING SERVICES / Design Team to develop, select and implement appropriate energy efficiency measures to ensure compliance.

Where assessments of works or costs identified in this Report are made, such assessments are based upon the information available at the time and where appropriate are subject to further investigations or information which may become available.

SC disclaim any undertaking or obligation to advise any person of any change in any matter affecting the Report, which may come or be brought to SC's attention after the date of the Report.

Certain statements made in the Report that are not historical facts may constitute estimates, projections or other forward-looking statements and even though they are based on reasonable assumptions as of the date of the Report, such forward-looking statements by their nature involve risks and uncertainties that could cause actual results to differ materially from the results predicted. SC specifically does not guarantee or warrant any estimate or projections contained in this Report.

Costs may vary outside the ranges quoted. Whilst cost estimates are provided for individual issues in this Report these are based upon information at the time which can be incomplete. Cost estimates for such issues may therefore vary from those provided. Where costs are supplied, these estimates should be considered in aggregate only. No reliance should be made in relation to any division of aggregate costs, including in relation to any issue, site or other subdivision.

No allowance has been made for changes in prices or exchange rates or changes in any other conditions which may result in price fluctuations in the future. Where assessments of works or costs necessary to achieve compliance have been made, these are based upon measures which, in SC's experience, could normally be negotiated with the relevant authorities under present legislation and enforcement practice, assuming a proactive and reasonable approach by site management.

Forecast cost estimates do not include such costs associated with any negotiations, appeals or other non-technical actions associated with the agreement on measures to meet the requirements of the authorities, nor are potential business loss and interruption costs considered that may be incurred as part of any technical measures.

Copyright

© This Report is the copyright of SC. Any unauthorised reproduction or usage by any person other than the addressee is strictly prohibited

1. Executive Summary

The design of the proposed development in 'The Lion, 2 Britannia Street, London, WC1X 9JE' located in an urban residential area in London, has incorporated building fabric enhancement (above current building regs requirements) to increase the energy efficiency of the building. This includes that the development uses less energy, by adopting sustainable design and construction measures and by supplying energy efficiently.

Given the complexity of calculating and assessing CO₂ emissions, the **Camden Council** requires all proposed developments to incorporate sustainable design and construction measures. Schemes must: demonstrate how sustainable development principles have been incorporated into the design and proposed implementation. **According to the Camden Planning Guidance, it is requested for refurbishments, conversions and changes of use (5 dwellings or more/ 500sq m of floorspace or more) to meet Eco-Homes 'Excellent' (now being replaced by the BREEAM Domestic Refurbishment) as a minimum requirement, by achieving the minimum standards for specific categories (% of un-weighted credits) of 60% of the credits achieved under the Energy and Water sections and 40% under the Materials sections** in accordance with the Development Policy DP22: Promoting sustainable design and construction & the CPG3: Sustainability Assessment Tools (9.8). **Also, according to the CS13 policy, developments need to achieve a reduction in CO₂ emissions of 20% from on site renewable energy generation**

The recommendation for the proposed development at **The Lion, 2 Britannia Street, London, WC1X 9JE**, that will entail "The Change of Use from an existing A4 (Drinking Establishment) to 8 No. Residential Units (Class C3) and addition of mansard roof, side extension and lowering of the existing basement floor" is that **Efficient Condensing Gas Combi boilers + 7.85kWp (which equals to 24PV panels and 6.52 m² total required roof space) should be progressed**. This is based on the following reasons:

1. The strategy would provide an average of **43.4% CO₂ reduction from the Existing Building to the proposed extended and converted dwellings. Therefore, the strategy meets BRUK-L1B requirements for the development.**
2. The strategy would provide an average of **20.3% reduction of CO₂ emissions the energy demand via onsite renewable technology (PV)**
3. **Eco-Homes has now been replaced by BREEAM Domestic Refurbishment.** Therefore a **BREEAM Domestic Refurbishment pre-assessment** has also been undertaken on the development to demonstrate the minimum intent to achieve an 'Excellent' rating, as detailed in the local authority planning policy requirements.

Meeting the Policy requirements:

- **The overall score is 71.10%, thus achieving an ‘Excellent’ rating.**
- Under the **Energy category**, the development achieves **21 credits out of 29 credits** available (more than 60% of the planning policy required credits) **and meeting the minimum standards of ‘Excellent’ in the ENE02 section by targeting 3.5 credits.**
- Under the **Water category**, the development achieves **4 credits out of 5 credits** available (more than 60% of the planning policy required credits).
- Under the **Materials category**, the development achieves **26 credits out of 45 credits** available (more than 40% of the planning policy required credits).



2. Introduction

Syntegra Consulting Ltd has been appointed as energy consultants to produce an energy strategy for the scheme at **'The Lion, 2 Britannia Street, London, WC1X 9JE'** – to support the scheme design process, demonstrate Building regulations Part L1B compliance, along with intent to deliver a minimum BREEAM Domestic Refurbishment – 'Excellent' rated dwelling (in accordance with the local authority planning policy targets).

This report will assess the proposed development site's estimated energy demand & CO2 emissions. It will look into the feasibility of Low Zero Carbon technologies, examining the following aspects relative to LZC/renewable technologies:

- Energy generated by Renewable/Low Zero Carbon Technologies (LZC)
 - Feasibility assessment for each Renewable/Low Zero Carbon Technologies (LZC)
 - Local Planning Requirements
 - Life cycle Costs & payback period for the technology investment
 - Available Grants
1. The proposed building fabric and Low Zero Carbon (LZC) design strategy and analysis calculations, with respect to the Standard Assessment energy assessment Procedure (SAP).
 2. The comparison of the development's energy consumption against the existing building model in order to show a minimum target for the overall development **against current 2010 Part L1B building regulations in order to achieve energy targets for BREEAM Domestic Refurbishment 'Excellent' rated dwelling.**
 3. The **BREEAM Domestic refurbishment pre-assessment** strategy in terms of the intent in achieving the **overall minimum 'Excellent' rating.** – In accordance with the local planning policy targets.



2.1 Site Description

The proposed development comprises of 'The Change of Use from an existing A4 (Drinking Establishment) to 8 No. Residential Units (Class C3) and addition of mansard roof, side extension and lowering of the existing basement floor'. The development is located in the area of St. Pancras in London. The development is in close proximity to King's Cross St Pancras Underground station (approx 0.3 miles). The site is within the London Borough of Camden.

2.2 Policy documents

The development proposals have been developed with regard to the relevant national, regional and local policy guidance which is reviewed within this section. The energy strategy proposal has been produced with due regard to the following key policy guidance:

London Borough of Camden, DP22 "Promoting sustainable Design & Construction"

DP22 – *Promoting sustainable design and construction* contributes towards delivering the strategy in policy CS13 by providing detail of the sustainability standards we will expect development to meet.



The London Plan Renewable Energy Policy 2011 (Policy 5.2, 5.6 & 5.7)

The Mayor will and boroughs should in their DPDs adopt a presumption that developments will achieve a reduction in carbon dioxide emissions of 20% from onsite renewable energy generation according to 5.42 section of Policy 5.7 Renewable Energy (which can include sources of decentralised renewable energy). According to Policy 5.2 Minimising CO2 Emissions a 25% CO2 emission reduction BER/TER based on 2010 Building Regulations should be achieved, unless it can be demonstrated that such provision is not feasible. Furthermore, intent must be shown for connecting to a Decentralised energy Network according to Policy 5.6 and utilizing a Combined Heat & Power.


2.3 The Energy Hierarchy:

The report has used the Mayor's Energy Strategy to assess the development. This strategy adopts a set of principles to guide design development and decisions regarding energy, balanced with the need to optimise environmental and economic benefits. These guiding principles have been reordered since the publication of the Mayor's Energy Strategy in Feb 2004 and the recently adopted replacement London Plan 2011 states that 'The following hierarchy should be used to assess applications:

- *Using less energy, in particular by adopting sustainable design and construction measures;*
- *Supplying energy efficiently, in particular by prioritising decentralised energy generation; and*
- *Using renewable energy.*

The development Energy strategy has adopted the following design ethos:

1. **BE LEAN** – By using less energy and taking into account the further energy efficiency measure in comparison to the baseline building.
2. **BE CLEAN** – By supplying energy efficiently. The clean building looks at further carbon dioxide emission savings over the lean building by taking into consideration the use of decentralise energy via CHP.
3. **BE GREEN** – By integrating renewable energy into the scheme which can further reduce the carbon dioxide emission rate.



3. The Development configuration scheme

The proposed development scheme consists of the following characteristics:

3.1 The Unit configuration

The following table presents the type, area and number of units to be assessed within this report:

Proposed units to be assessed for the development

No. of Flats	Flat Name	No. of bedrooms	Individual Flat Area m ²
1	Apartment 1	2	140.0
2	Apartment 2	2	145.7
3	Apartment 3	2	97.1
4	Apartment 4	1	52.1
5	Apartment 5	1	60.3
6	Apartment 6	2	89.65
7	Apartment 7	1	62.0
8	Apartment 8	2	110.0
Total	8	12	756.85

Table 1

3.2 Specification of Building Materials

The table presented below demonstrates the material properties of the building fabric that have been proposed in comparison to the existing:

Envelope Specification

Building Element	Existing Specification (Drinking Establishment)	Proposed Specification (Residential Units)
External Floor U-value	0.56	0.2
External Walls U-value	1.6	0.2
External Walls (Extension) U-value	-	0.25
Window units (whole window) U-value	4.8 single glazing	1.4 double glazing
Roof U-value	0.16	0.16
Air Permeability m ³ /(h.m ²) at 50 Pa	15.0	15.0
Low Energy Lighting	0%	100%

Table 2

3.3 Fuel

The assessment has assumed the following fuel carbon emissions factors - The fuel carbon emissions factors used are in accordance with **SAP 2009 (for Building Regs Part L1B)**.

Carbon Emissions Factor	SAP 2009 kgCO ₂ /kW
Grid Electricity	0.422
Grid displaced Electricity	0.568
Manufactured smokeless fuel	0.402
Coal (traditional British Coal)	0.301
Heating Oil	0.28
LPG	0.25
Natural Gas	0.198
Wood Pellets	0.028
Bio Diesel	0.098
Bio Gas	0.019

Table 3



4. Baseline CO₂ Emissions

The feasibility studies for the Standard Case Models have been produced using the **SAP2009 to produce the existing building model and CIBSE standard case model for Part L1B building regulations compliance purposes**. The standard case includes the minimum space and water heating services as set out in the domestic building services compliance guides (where applicable):

Table Cat 1.2: Standard CO ₂ Emissions Calculation - Specification Assumptions		
Element or System		Value
[1]	Main heating fuel (space and water)	Mains gas
[2]	Main heating system (and second main heating system where specified)	Boiler and radiators Fully pumped circulation Water pump in heated space
[2a]	Boiler	SEDBUK (2009) 88% Room-sealed Fanned Flue On/off burner control
[2b]	Heating system controls	Programmer Room thermostats TRVs Boiler interlock
[3]	Secondary heating fuel (<i>where secondary heating is specified</i>)	Electricity
[3a]	Secondary heating system (<i>where secondary heating is specified</i>)	Panel, convector or radiant heaters
[4]	Hot water system	Stored hot water, heated by boiler only Separate time control for space and water heating
[4a]	Hot water storage	150 litre cylinder insulated with 35mm of factory applied foam
[4b]	Primary water heating losses	Primary pipework insulated Cylinder temperature controlled by thermostat
[4c]	Technologies covered by Appendix H of SAP	None specified
[5]	Technologies covered by Appendix M of SAP	None specified

The baseline annual energy use and CO₂ emissions for the existing part of the development are presented in the table below.

Building Services	Existing Building Energy Use (kWh/m ² /yr)	Existing Building CO ₂ Emissions (kg of CO ₂ /m ² /yr)
Heating	150.27	29.75
Auxiliary	0.23	0.12
Lighting	2.87	1.48
Hot Water	6.47	1.28
Total (regulated)	159.84	32.63



5. BE LEAN – Energy Efficient Design

This section outlines the design energy efficient measures taken in order to minimise the building's energy demand and therefore reduce energy use and CO₂ emissions further than the baseline. The energy efficient measures include:

- i) Inclusion of better U-values than the minimum U-values set in the ADL1B 2010 document.
- ii) Designing for a buildings air permeability exceeding ADL1B target values.

	ADL1B 2010 minimum required values	Proposed building values Residential
Air Permeability m ³ /(h.m ²) at 50 Pa	10	15
Wall U value W/m ² C ⁰	0.3	0.2
Roof U value W/m ² C ⁰	0.18	0.16
Floor U value W/m ² C ⁰	0.25	0.2
Window U value W/m ² C ⁰	2	1.4

The following tables demonstrate the reduction in CO₂ emissions caused by the energy efficiency measures mentioned above:

Building Services	Existing Building Energy Use (kWh/m ² /yr)	BE LEAN Building Energy Use (kWh/m ² /yr)	Existing Building CO ₂ Emissions (kg of CO ₂ /m ² /yr)	BE LEAN Building CO ₂ Emissions (kg of CO ₂ /m ² /yr)
Heating	150.27	85.29	29.75	16.89
Auxiliary	0.23	1.85	0.12	0.96
Lighting	2.87	7.04	1.48	3.64
Hot Water	6.47	46.74	1.28	9.25
Total (regulated)	159.84	140.92	32.63	30.74

CO₂ Reductions after BE LEAN stage

	BASELINE CO ₂ Emissions (kgr of CO ₂ /m ² /yr)	BE LEAN Building CO ₂ Emissions (kgr of CO ₂ /m ² /yr)	% reduction in CO ₂ Emissions
Regulated Emissions	32.63	30.74	5.8%

From the above table it can be seen that the overall CO₂ reduction due to energy efficiency is **5.8%** for the total emissions.

.



6. BE CLEAN – CHP & DECENTRALISED ENERGY NETWORKS

The energy hierarchy encourages the use of a CHP system and the connection to District Heating system to reduce CO₂ emissions further.

CHP

The Energy Hierarchy identifies combined heat and power (CHP) as a method of producing heat and electricity with much lower emissions than separate heat and power. Also, it encourages the creation of district heating systems supplied by CHP.

The implementation of a CHP strategy should be decided according to good practice design. Key factors for the efficient implementation of the CHP system are:

- Development with high heating load for the majority of the year.
- CHP operation based on maximum heat load for minimum 10 hours per day.
- CHP operation at maximum capacity of 90% of its operating period.

A CHP system will not be considered for this development due to the following reasons:

- The heating load of the building is not enough for the CHP system to run efficiently.
- Economic viability is heavily dependent on the demand for heat and power, as well as the price of electricity and gas. The heat and power demand of the proposed development is not sufficient for a CHP system to run efficiently

Hence, the implementation of a CHP strategy is not recommended for this development.

Micro - CHP

Micro CHP has not been considered further for this project for the following reasons:

Micro-CHP is a relatively new concept (Baxi Ecogen was made available in 2009) and issues are raised in relation to unproven technology, inefficiency for shorter run cycles and lack of technical knowledge that can limit the practical application of micro CHP at present. In addition other issues surrounding the fact that around 50% of electricity generated in domestic properties is surplus, high installation costs and estimated low life expectancy has also been taken into consideration as to its commercial un-viability for this development scheme. Micro-CHP also has lower FIT tariff rate and period duration and is only applicable for systems under 2kW.

Decentralised Energy Network

The feasibility of connecting into an existing heating network or providing the building with its own combined heat and power plant has been assessed alongside the **London Heat Map Study For London Borough of Camden** as part of this assessment. The study does not identify the area in 2 Britannia Street as a high potential area for a District Heating network. The development is not in close proximity to an existing nor a potential District Heating transmission line. At the moment there is no decentralized energy network available and in particular a district heating network in the proximity

of the proposed development site that would allow the development to connect to such a network. This is demonstrated clearly from the London Heat Map (<http://www.londonheatmap.org.uk>) snapshot below.

Site Location



The clean strategy includes:

- i) Utilising low energy efficient lighting such as LED lighting.
- ii) Utilising the highly efficient heating and hot water systems.

Heating Demand & Hot Water

The heating energy demand will be reduced by providing good insulation of the building envelope in order to minimise heat losses.

The option presented for the heating & HWS for the residential units is **Condensing Combi gas boilers with 89.2% efficiency.**

Lighting

The light fittings installed will be low energy efficient fittings. These can be T5 fluorescent fittings with high frequency ballasts, or LED fittings.

Ventilation

A natural supply ventilation strategy will be adopted in the dwelling with extract fans in bathroom and kitchen. Therefore, higher energy consumption and CO₂ emissions due to mechanical ventilation is avoided.

• Individual Condensing gas boilers BE CLEAN stage

Building Services	BE LEAN Energy Use (kWh/m ² /yr)	BE CLEAN Building Energy Use (kWh/m ² /yr)	BE LEAN CO ₂ Emissions (kg of CO ₂ /m ² /yr)	BE CLEAN Building CO ₂ Emissions (kg of CO ₂ /m ² /yr)
Heating	85.29	76.64	16.89	15.20
Auxiliary	1.85	1.85	0.96	0.96
Lighting	7.04	4.14	3.64	2.14
Hot Water	46.74	24.86	9.25	4.92
Total (regulated)	140.92	107.49	30.74	23.22

CO₂ Reductions after BE CLEAN stage

	BE LEAN CO ₂ Emissions (kgr of CO ₂ /m ² /yr)	BE CLEAN Building CO ₂ Emissions (kgr of CO ₂ /m ² /yr)	% reduction in CO ₂ Emissions
Regulated Emissions	30.74	23.22	24.5%

From the above table it can be seen that the overall CO₂ reduction due to energy efficiency is **24.5%** for the total emissions.

7. BE GREEN – RENEWABLE ENERGY

In this section the viable renewable energy technologies that will reduce the development's CO₂ emissions are examined. Incorporating lean design measures will significantly reduce the onsite energy consumption and the CO₂ emissions of the building. Below is a review of possible renewable technologies for incorporation in the proposed development.

All of the LZC technologies are assessed against a number of criteria. Hence, LZC technology feasibility will be assessed according to the following criteria:

- I. Renewable energy resource or fuel availability of the LZC technology on the site.
- II. Space limitations due to building design and urban location of the site.
- III. Capital, operating and maintenance cost.
- IV. Planning Permission
- V. Implementation with regards the overall M&E design strategy for building type

The renewable/LZC technologies which were found **non feasible** based on the above criteria are the following:

- Wind Turbines [See Appendix Section 10.1]
- Biomass Boilers [See Appendix Section 10.2]
- Hydrogen Fuel Cells [See Appendix Section 10.3]
- Small scale hydro power [See Appendix Section 10.4]
- Grd. Source Heat Pump (GSHP) [See Appendix Section 10.5]
- CHP & Micro CHP [See Appendix Section 10.6]
- Solar Thermal

7.1 PHOTOVOLTAIC (PV) – PROPOSED TECHNOLOGY

PV is the proposed renewable technology for this development. The PV system will provide self-generating electricity which can be sold back to the grid. The CO₂ reduction via renewables target is achieved with the implementation of PV. For the calculation of the payback period, the Feed-In-Tariffs' (FITs) has been taken into account. The PV load falls within the bracket associated with a FIT tariff applied of 14.9p per kWh for electricity generated and 4.64p per kWh for electricity exported back to the grid (over 20 years).

PV System specification

- Individual Combi Gas Boilers + 7.85kWp PV**

The tables below illustrate the site and the PV panels details:

Orientation	South
Panel Tilt	30°
Overshading	Less than 20 percent
Proportion Exported	50%
Build Type	New
Energy Efficiency	EPC valid and at least Band D or higher
Installation Type	Not a multi-installation

Number of Panels	24
Manufacturer	Sunpower
Model	SPR 327NE WHT D
Type	Monocrystalline
Area	1.631 m ²
Power Output	327 Wp

System Specification :	7.85kWp
Total Roof Area Required :	39.14 m²
Annual Electricity Output :	6738 kWh

This table above shows that the proposed PV specification for the residential units. It will generate 6738kWh per year. For the 7.85kWp system, 24 high efficiency 327W monocrystalline PV panels need to be installed. The roof area required for the PV panels is approximately 39.14 m².

7.85kWp Solar PV for ROI model below**Note: PV panels are based on high output, high efficiency at 327 Watts/panel.****Investment in 7.82kWp System: *** £ 11,673.90**First Year:** Income from Feed-In Generation Tariff @ 13.50p/kWh: £ 884.15

Income from exporting energy @ 4.64p/kWh: £ 197.53

Electricity Saving: £ 330.08

Total Benefit: £ 1,411.75

Payback Time: 7y 2m**Total Profit Over 20 years:****£ 36,737.59****15.73 % per year (7.11% AER)****Assumptions:**

- Illustrative solar PV performance figures only. Figures are given in good faith but do not constitute "Financial Advice".
- Exact PV subsidy figures may depend on grants available at particular locations and other factors.
- Your property has an Energy Performance Certificate (EPC) rating of level D or better.
- Yearly PV output uses a factored degradation over time based on industry estimates.
- Tariffs shown presume installation after at the new FiT rates
- VAT is included (at 5% where appropriate) unless a new build is specified.
- Photovoltaic Panels will not be shaded (e.g. by Trees or Buildings) as shading affects PV output.
- Exact equipment costs are estimated based on retail prices in 2012 and will vary by installer/supplier.
- Installation costs are based on industry averages for installation type/size. Every install is different and you should obtain 3 quotes.
- Assuming that you pay 14.4p per unit and that around 35% of the solar electricity that you generate will be used in your home, having an export meter (you can change such assumptions above).

In order to qualify both the installer and the equipment must be certified under the Microgeneration Certification Scheme (MCS).

PV plant location(s) – To be located on the flat roof.

CO₂ Emissions Reduction by PV

The table below demonstrate the results of the CO₂ emissions and energy use after the implementation of the PV technology. The target according to the London Plan 2011 and the Local Council is to meet a 20% reduction in CO₂ emissions from renewable technology. The following tables demonstrate the reductions achieved by the renewable technology:

Individual Combi gas boilers + 7.85 kWp PV BE GREEN stage

Building Services	BE CLEAN Energy Use (kWh/m ² /yr)	BE GREEN Building Energy Use (kWh/m ² /yr)	BE CLEAN CO ₂ Emissions (kg of CO ₂ /m ² /yr)	BE GREEN Building CO ₂ Emissions (kg of CO ₂ /m ² /yr)
Heating	76.64	76.64	15.20	15.20
Auxiliary	1.85	1.85	0.96	0.96
Lighting	4.14	4.14	2.14	2.14
Hot Water	24.86	24.86	4.92	4.92
Energy generated by renewable (kWh/m ² /yr)	-	-8.90	-	-4.71
Total (regulated)	107.49	98.59	23.22	18.51

CO₂ Reductions after BE GREEN stage

	BE CLEAN CO ₂ Emissions (kgr of CO ₂ /m ² /yr)	BE GREEN Building CO ₂ Emissions (kgr of CO ₂ /m ² /yr)	% reduction in CO ₂ Emissions
Regulated Emissions	23.22	18.51	20.3%

From the above table it can be seen that the overall CO₂ reduction due to energy efficiency is **20.3%** for the total emissions.

8. Conclusion

Due to the site spatial limitations, location and the other issues identified previously in the report technologies such as Ground Source Heat Pump, Biomass, Solar Thermal, Hydroelectricity and Wind turbines are immediately unfeasible. The design has incorporated building fabric enhancement (above current building regs requirements) to increase the energy efficiency of the building.

The recommendation for the proposed development at **The Lion, 2 Britannia Street, London, WC1X 9JE**, that will entail **“The Change of Use from an existing A4 (Drinking Establishment) to 8 No. Residential Units (Class C3) and addition of mansard roof, side extension and lowering of the existing basement floor”** is that **Efficient Condensing Gas Combi boilers + 7.85kWp (which equals to 24PV panels and 6.52 m² total required roof space) should be progressed**. This is based on the following reasons:

1. Plant location(s) – The plant would be located on the flat roof. The PV panels are based PV on high output, high efficiency Sunpower 327 watts. PV layouts and allocation of roof areas are yet to be finalised.
2. The strategy would provide an average of **43.4% CO₂ reduction from the Existing Building to the proposed extended and converted dwellings**. Therefore, the strategy meets **BRUK-L1B requirements for the development**.
3. The strategy would provide an average of **20.3% reduction of CO₂ emissions the energy demand via onsite renewable technology (PV)**
4. **Eco-Homes has now been replaced by BREEAM Domestic Refurbishment**. Therefore a separate BREEAM Domestic Refurbishment pre-assessment has been undertaken for the development. **The BREEAM pre-assessment demonstrates that an “Excellent” rating can be achieved as detailed in the local authority planning policy requirements**. [See the Appendix for the BREEAM pre-assessment report]



9. Appendix

- Low Zero Carbon Energy Systems
- BREEAM Domestic Refurbishment pre-assessment
- BRUKL Part L1B compliance summary report

Syntegra Consulting Ltd, The Braccans Business Centre, 2 The Braccans, Bracknell, RG12 2XH
Registered Company No. 06408056

T: 08450091625 E: mail@syntegra-epc.co.uk

VAT Registration No. 980016044



10. Low & Zero Carbon Energy Systems

The following section is an overview of the LZC energy systems that are available and can be implemented to the building environment. Firstly, a brief description of the types of renewable energy (zero carbon energy) that can be harnessed with technology will be presented. In addition, the renewable energy system technologies that harness the renewable energy and convert it to electricity, heating and hot water etc, to be consumed in buildings will be presented as well.

The second part of this section will provide an indication of the available low carbon technologies that can be installed on a building to minimise carbon emissions and reduce energy costs.


10.1. Zero Carbon (Renewable) Energy Overview.

Renewable energy is the energy that is grasped by the earth's abundant natural sources. Renewable energy can be harnessed with the appropriate use of technology to satisfy the human energy needs. Solar, wind, wave, tide and bio energy are termed as renewable. These renewable energy sources can be classified as 'active' or 'passive'. Active RES are the renewable sources which with the use of renewable energy systems technology (REST) can generate power and heat to satisfy the energy and heating demands of buildings. Passive RES are the renewable sources which with the use of static building elements can enhance the natural ventilation and the heating of a building.

Solar Energy

Solar energy is the energy of sun light. The temperature of the Sun's surface reaches to a value of approximately 5,762K. The Earth's perimeter of 40,000 km results in an intersected sun power of 174,000TW. Attenuation by the atmosphere results in peak intensity at sea level of around 1kW/m², giving a 24 hour annual average of 0.2kW/m² and a 24 hour annual average power of 102,000 TW.

This commands the environment and maintains the life support system of Earth's ecosystem and all forms of renewable energy with the exception of geothermal energy. The solar energy reaching the earth's surface surpasses 10,000 times the current global energy demand.



To be more specific in terms of harnessing solar energy we are interested with the irradiance. Irradiance is the energy of light incident on a solar collector. Irradiance is measured in energy per area, (W/m²). The solar irradiance received on the Earth's surface consists of three components, the beam irradiance, diffuse and ground reflected irradiance. The beam component is the irradiance that reaches the solar collector directly. The diffuse irradiance is formulated due to scattering and absorption in the earth's atmosphere. Finally, the ground reflected irradiance is formed due to the sunlight reflected by the earth's ground.

Wind Energy

Wind energy is the energy found in the wind that is grasped by REST in order to generate power for human benefit. Wind turbines are the REST used to collect the wind resource and generate power. Today, wind turbines are used to generate electricity from the wind. There are two types of wind turbines, the horizontal axis turbine which is the most common one and the vertical axis turbine. The HAWT is the most efficient and cost effective. Most of the wind turbines used for electricity generation is of this type. Wind turbines can be found in many sizes and outputs, from small battery charging turbines (say a rotor diameter of 1 or 2 metres with an output of a few hundred Watts) to the largest machines used to supply electricity to the grid (Rotor diameters in excess of 70m and output powers of over two MW).



Bio-energy

Bio-energy is the energy produced from biomass. Biomass is available from materials derived from biological sources. Biomass is any organic material which has stored sunlight in the form of chemical energy. As a fuel it may include wood, wood waste, straw, manure, sugar cane, and many other by products from a variety of agricultural processes. Energy from biomass is produced by burning organic matter.




Biomass is the solid form of 'bioenergy', but liquid fuels can also be generated from plant matter and this is referred to as 'biofuel'. Biomass is carbon-based so when used as fuel it also generates carbon emissions.

However, the carbon that is released during combustion is equivalent to the amount that was absorbed during growth, and so the technology is carbon-neutral.

Geothermal Energy

Geothermal energy is the heat from the Earth. It's clean and sustainable. Resources of geothermal energy range from the shallow ground to hot water and hot rock found a few miles beneath the Earth's surface, and down even deeper to the extremely high temperatures of molten rock called magma. Almost everywhere, the shallow ground or upper 10 feet of the Earth's surface maintains a nearly constant temperature between 10° and 16°C. Geothermal heat pumps can tap into this resource to heat and cool buildings. A geothermal heat pump system consists of a heat pump, an air delivery system (ductwork), and a heat exchanger-a system of pipes buried in the shallow ground near the building. In



the winter, the heat pump removes heat from the heat exchanger and pumps it into the indoor air delivery system. In the summer, the process is reversed, and the heat pump moves heat from the indoor air into the heat exchanger. The heat removed from the indoor air during the summer can also be used to provide a free source of hot water.

10.2 Zero Carbon Technologies

In this section the zero carbon technologies also known as Renewable Energy System Technologies (REST) are described.

- Photovoltaics (PV)
- Solar Water Heating
- Wind Turbines
- Small scale Hydro Power
- Biomass Heating

10.2.1 Photovoltaic Systems

Description of PV Systems

Photovoltaic systems convert energy from the sun directly into electricity. They are composed of photovoltaic cells, usually a thin wafer or strip of semiconductor material that generates a small current when sunlight strikes them. Multiple cells can be assembled into modules that can be wired in an array of any size. These flat-plate PV arrays can be mounted at a fixed angle facing south, or they can be mounted on a tracking device that follows the sun, allowing them to capture the most sunlight over the course of a day, or even in the form of a solar PV facade. Several connected PV arrays can provide enough power for a household/building.



Thin film solar cells use layers of semiconductor materials only a few micrometers thick. Thin film technology has made it possible for solar cells to now double as rooftop shingles, roof tiles, building facades, or the glazing for skylights or atria. The solar cell version of items such as shingles offer the same protection and durability as ordinary asphalt shingles.



Advantages

The PV systems are relatively simple, modular, and highly reliable due to the lack of moving parts. Moreover, PV systems do not produce any greenhouse gases, on the contrary they save approximately 325kg of CO₂ per year kWp they generate.


Best Practice Design

PV installations performance is proportional to the active area (area covered by PVs). The desirable location for PV panels is on a south facing roof or façade, as long as no other building or tall trees overshadows it, resulting in reduced PV efficiency. PV panels are require strong structurally roofs due to their heavy weight, especially if the panels are placed on top of existing tiles. The area of PV panels required to generate 1 kWp varies but generally 6-8m² for mono-crystalline and 10m² for polycrystalline panels will generate 1kWp(kWp-energy generated at full sunlight) of electricity.



Cost & Maintenance

Prices for PV systems vary, depending on the size of the system to be installed, type of PV cell used and the nature of the actual building on which the PV is mounted. The size of a PV system depends on the buildings electricity demand. For an average domestic system, costs of a PV system can be around £4000 - £9000 per kWp installed, with most domestic systems usually between 1.5 and 2 kWp. Solar tiles cost more than conventional panels, and panels that are integrated into a roof are more expensive than those that sit on top. Grid connected systems require very little maintenance, generally limited to ensuring that the panels are kept relatively clean and that shade from trees does not obstruct the sunlight path. However, the wiring and system components should be checked regularly by a qualified technician.



Available Grants

The Feed - In - Tariffs have been introduced in order to give an incentive for PV generated electricity.

The Feed-In-Tariffs scheme is based on the principle that the

energy supplier pays generation tariff for every kWh the PV system generates

and an export tariff for every kWh of electricity supplied back to the national grid.

Tariff level for new Solar PV installations after 1st August 2012 (pence/kWh). For non PV technologies there will be new rates as of October 2012

Technology	Scale	Standard generation tariff	Multi-installation tariff	Lower tariff if energy efficiency requirement not met
PV	≤4 kW (new build)	16.0	14.4	7.1
PV	≤4 kW (retrofit)	16.0	14.4	7.1
PV	>4-10 kW	14.5	13.05	7.1
PV	Stand alone system	7.1	N/A	N/A

10.2.2 Solar Water Heating

Description of Solar Water Heating System

Solar water heating systems use solar energy to heat water. Depending on the type of solar collector used, the weather conditions, and the hot water demand, the temperature of the water heated can vary from tepid to nearly boiling. Most solar systems are meant to furnish 20 to 85% of the annual demand for hot water, the remainder being met by conventional heating sources, which either raise the temperature of the water further or provide hot water when the solar water heating system cannot meet demand.



Solar systems can be used wherever moderately hot water is required. Off-the-shelf packages provide hot water to the bathroom and kitchen of a house; custom systems are designed for bigger loads, such as multi-unit apartments.

The most common collector is called a flat-plate collector. Mounted on the roof, it consists of a thin, flat, rectangular box with a transparent cover that faces the sun. Small tubes run through the box and carry the fluid – either water or other fluid, such as an antifreeze solution – to be heated. The tubes are attached to an absorber plate, which is painted black to absorb the heat. As heat builds up in the collector, it heats the fluid passing through the tubes.

Advantages

Solar water heating can provide about a third of a typical dwellings/business hot water needs. The average domestic system reduces CO₂ by 325 kg per year approximately and around £50 a year of hot water bills, when installed in a gas heated home.

Fuel Displaced	£ Saving per year	CO ₂ saving per year kg
Gas	50	325
Electricity	80	635

Table 4

The savings presented on the previous table are approximate and are based on the hot water heating demand of a 3 bed semi detached house.

Best Design Practice

For domestic systems a 3-4 m² of southeast to southwest facing roof receiving direct sunlight for the main part of the day is required. Also, more space will be needed if a water cylinder is required.

Planning Issues

In England, changes to permitted development rights for micro generation technologies introduced on 6th April 2008 have lifted the requirements for planning permission for most solar water heating installations. Roof mounted and stand alone systems can now be installed in most dwellings, as long as they follow certain size criteria. Listed, English Heritage and buildings in conservation areas are exempted.


Cost & Maintenance

A typical installation cost for a domestic SHW system is £3000-£5000. Evacuated tube systems are more expensive due to their higher manufacturing cost.

SWH systems in general have a 5-10 years warranty and require little maintenance. A yearly check by the owner of the system and a more detailed maintenance check by a qualified installer every 3-5 years should be adequate.

Available Grants

In March 2011, the UK Government announced the details of their Renewable Heat Incentive (RHI). RHI is designed to provide financial support that encourages individuals, communities and businesses to switch from using fossil fuel for heating, to renewables such as wood fuel.



There will be two phases for domestic customers:

Phase 1 (available from July 2011) - “RHI Premium Payment”

This is called the “RHI Premium Payment” and will be worth around £15m and available to 25,000 householders in Great Britain who install from July 2011.

The exact amounts available to consumers are confirmed:

- * Solar Thermal - £300/unit

These are one off payments; so not annual. DECC plan to publish details of the “Phase 2 RHI Payment” and how this will apply next year. Recipients of this payment will need to ensure that:

- * They have a well-insulated property based on its energy performance certificate;
- * They agree to give feedback on how the equipment performs.

Phase 2 (available from October 2012) – RHI tariffs

People in receipt of the Renewable Heat Premium Payments will be able to receive long term RHI tariff support once these tariffs are introduced, as will anybody who has installed an eligible technology since 15th July 2009.

These tariff payments will start alongside the Green Deal from October 2012 to allow a more whole-house approach to heat production and energy saving.

10.2.3 Wind Turbines

Description of Wind Turbine

Wind energy systems convert the kinetic energy of moving air into electricity or mechanical power. They can be used to provide power to central grids or isolated grids, or to serve as a remote power supply or for water pumping. Wind turbines are commercially available in a vast range of sizes. The turbines used to charge batteries and pump water off-grid tend to be small, ranging from as small as 50 W up to 10 kW. For isolated grid applications, the turbines are typically larger, ranging from about 10 to 200 kW. Wind turbines are mounted on a tower to harness the most energy. At 30 meters or more aboveground, they can capture the faster and less turbulent wind in an urban environment. Turbines harness the wind's energy with their propeller-like blades. In most of the cases, two or three blades are mounted on a shaft to form a rotor.



There are two types of wind turbines that can be used for buildings:

- Mast mounted – which are free standing and located near the building that will be consuming the generated electricity.
- Roof Mounted – which can be installed on house roofs and other buildings.

Planning Issues

Planning issues such as visual impact, noise and conservation issues also have to be considered. System installation normally requires permission from the local authority.

Cost & Maintenance

- Roof mounted turbines cost from £3000. The amount of energy and carbon that roof top micro wind turbines save depends on size, location, wind speed, nearby buildings and the local landscape. At the moment there is not enough data from existing wind turbine installations to provide a figure of how much energy and CO₂ could typically be saved. The Energy saving

trust is monitoring up to 100 installations nationwide which will give ball park figures of carbon savings.

- Mast Mounted turbines in the region of 2.5kW to 6kW would cost approximately £11000-£19000. These costs are inclusive of the turbine, mast, inverters, battery storage and installation cost. It should be noted that these costs vary depending on location, size and type of system to be installed.
- Turbines have an operational lifetime of up to 22.5 years but require service checks every few years to ensure efficient operation. For battery storage systems, typical battery life is around 6-10 years, depending on the type, so batteries may have to be replaced at some point in the system's life.

Available Grants

The Feed - In – Tariffs have been introduced in order to give an incentive for wind generated electricity. The Feed-In-Tariffs scheme is based on the principle that the energy supplier pays generation tariff for every kWh the wind system generates and an export tariff for every kWh of electricity supplied back to the national grid.

- Generation Tariff: 28.0 – 36.20 pence/kWh depending on installed rated output (up to 15KW)
- Export Tariff: 3.10pence/kWh
- Tariff period duration is 20 yea

10.2.4 Small Scale Hydro Description of Small scale Hydro System

Small hydro systems convert the potential and kinetic energy of moving water into electricity, by using a turbine that drives a generator. As water moves from a higher to lower elevation, such as in rivers and waterfalls, it carries energy with it; this energy can be harnessed by small hydro systems. Used for over one hundred years, small hydro systems are a reliable and well-understood technology that can be used to provide power to a central grid, an isolated grid or an off-grid load, and may be either run-of-river systems or include a water storage reservoir.



In a residential small scale hydro system the constant flow of water is critical to the success of the project. The energy available from a hydro turbine is proportional to the flow rate of the water and the head height. Since the majority of the cost of a small hydro project stems from up front expenses in construction and equipment purchase, a hydro project can generate large quantities of electricity with very low operating costs and modest maintenance expenditures for 50 years or longer.

Advantages

For houses with no mains connection but with access to a micro hydro site, a good hydro system can generate a steady, more reliable electricity supply than other renewable technologies at lower cost. Total system costs can be high but often less than the cost of a grid connection and with no electricity bills to follow.

Cost & Maintenance

Small hydro schemes are very site specific and are related to energy output. For low heat systems, costs may lie in the region of £4,000 per kW installed up to about 10kW and would drop per kW for larger schemes.

For medium heads, there is a fixed cost of about £10,000 and about £2,500 per kW up to around 10kW – so a typical 5kW domestic scheme might cost £20-£25,000.

Unit costs drop for larger schemes. Maintenance costs vary but small scale hydro systems are very reliable.

Available Grants

The Feed - In – Tariffs have been introduced in order to give an incentive for hydroelectric generated electricity. The Feed-In-Tariffs scheme is based on the principle that the energy supplier pays generation tariff for every kWh the hydroelectric system generates and an export tariff for every kWh of electricity supplied back to the national grid.

- Generation Tariff: 20.90 pence/kWh depending on installed rated output (up to 15KW)
- Export Tariff: 3.10pence/kWh
- Tariff period duration is 20 years

10.2.5 Biomass Heating

Description of Biomass Heating System

Biomass heating systems also known as biomass boilers burn organic matter—such as wood chips, agricultural residues or municipal waste—to generate heat for buildings. They are highly efficient heating systems, achieving near complete combustion of the biomass fuel through control of the fuel and air supply, and often incorporating automatic fuel handling transport systems. Biomass boilers consist of a boiler, a heat distribution system, and a fuel transportation system. The biomass heating system typically makes use of multiple heat sources, including a waste heat recovery system, a biomass combustion system, a peak load boiler, and a back-up boiler. The heat distribution system conveys hot water or steam from the heating plant to the loads that may be located



within the same building as the heating plant, as in a system for a single institutional or industrial building, or, in the case of a “district heating” system, clusters of buildings located in the vicinity of the heating plant.

Biomass heating systems have higher capital costs than conventional boilers and need diligent operators. Balancing this, they can supply large quantities of heat on demand with very low fuel costs, depending on the origin of the fuel.

Best Design Practice

It's important to have storage space for the fuel and appropriate access to the boiler for loading the fuel. A local fuel supplier should be present in order to make the scheme viable.

The vent material must be specifically designed for wood appliances and there must be sufficient air movement for proper operation of the stove. Chimneys can be fitted with a lined flue.

A Biomass heating system installation should comply with all safety and building regulations. Wood can only be burned in exempted appliances, under the Clean Air Act.

Advantages

Producing energy from Biomass has both environmental and economic advantages. Although Biomass produces CO₂ it only releases the same amount that is absorbed whilst growing, which is why it is considered to be carbon neutral. Furthermore, Biomass can contribute to waste management by harnessing energy from products that are often disposed at landfill sites.

It is most cost effective and sustainable when a local fuel source is used, which results in local investment and employment, which in addition minimizes transport emissions.

Planning Issues

If the building is listed or is in an area of outstanding natural beauty, then it is required that the Local Authority Planning department is notified before a flue is fitted.

Cost & Maintenance

Stand alone room heaters cost £2,000 to £4,000. Savings will depend on how much they are used and which fuel you are replacing. A Biomass stove which provides a detached home with 10% of annual space heating requirements could save around 840kg of CO₂ when installed in an electrically heated home. Due to the higher cost of Biomass pellets compared with other heating fuels, and the relatively low efficiency of the stove compared to a central heating system it will cost more to run.

The cost of Biomass boilers varies depending on the system choice; a typical 15kW pellet boiler would cost about £5,000-£14,000 installed, including the cost of the flue and commissioning process. A manual log feed system of the same size would be slightly cheaper. A wood pellet boiler could save around £750 a year in energy bills and around 6 tons of CO₂ per year when installed in an electrically heated home.

In terms of biomass fuel costs, they generally depend on the distance between the dwelling and the supplier and whether large quantities can be bought.

Available Grants

In March 2011, the UK Government announced the details of their Renewable Heat Incentive (RHI). RHI is designed to provide financial support that encourages individuals, communities and businesses to switch from using fossil fuel for heating, to renewables such as wood fuel.

The RHI is in two phases:

Phase 1 (available from July 2011) - “RHI Premium Payment”

This is called the “RHI Premium Payment” and will be worth around £15m and available to 25,000 householders in Great Britain who install from July 2011.

The exact amounts available to consumers have yet to be confirmed. However the Department of Energy and Climate Change (DECC) have announced that the following amounts may be available:

- * Biomass boilers - £950/unit (available only to off-gas installations)

These are one off payments; so not annual. DECC plan to publish details of the “Phase 2 RHI Payment” and how this will apply next year. Recipients of this payment will need to ensure that:

- * They have a well-insulated property based on its energy performance certificate;
- * They agree to give feedback on how the equipment performs.

Phase 2 (available from October 2012) – RHI tariffs

People in receipt of the Renewable Heat Premium Payments will be able to receive long term RHI tariff support once these tariffs are introduced, as will anybody who has installed an eligible technology since 15th July 2009.

These tariff payments will start alongside the Green Deal from October 2012 to allow a more whole-house approach to heat production and energy saving.

10.3 Low Carbon Technologies

In this section the low carbon technologies are described.

- Air Source Heat Pumps
- Ground Source Heat Pumps (GSHP)

- Combined Heat and Power (CHP)
- Micro CHP
- Fuel Cells

10.3.1. Air Source Heat Pumps (ASHP)


Description of Air Source Heat Pumps

Air source heat pumps work in a very similar way to fridges and air conditioners and absorb heat from the air. They are ideally suited to work with under floor heating systems because of the lower design temperatures of under floor systems. The lower the water temperature, the higher the COP. Air source heat pumps use air. They are fitted outside a house; generally perform better at slightly warmer air temperatures. The seasonal efficiencies of air source heat pumps are between 200% - 400%. Heat pumps can operate at outside temperatures down to -15°C , although there is a drop in COP.



Advantages

- A reduction in carbon emission.
- No boiler flues and danger of carbon monoxide leakage.
- Maintenance is carried outside the premises.
- No annual boiler servicing and safety checks.
- Heat pump life expectancy about 25 years compared to a boiler of 15 years



Costs & Savings

Operating Cost Savings around 15% in comparison with a typical gas fired condensing boiler installation with HWS cylinder and an electrically driven Community air to water heat pump.

Available Grants

In March 2011, the UK Government announced the details of their Renewable Heat Incentive (RHI).

RHI is designed to provide financial support that encourages individuals, communities and businesses to switch from using fossil fuel for heating, to renewables such as wood fuel.

The RHI is in two phases:

Phase 1 (available from July 2011) - “RHI Premium Payment”

This is called the “RHI Premium Payment” and will be worth around £15m and available to 25,000 householders in Great Britain who install from July 2011.

The exact amounts available to consumers are confirmed:

- * Air Source Heat Pumps - £850/unit (available only for off-gas installations)

These are one off payments; so not annual. DECC plan to publish details of the “Phase 2 RHI Payment” and how this will apply next year. Recipients of this payment will need to ensure that:

- * They have a well-insulated property based on its energy performance certificate;
- * They agree to give feedback on how the equipment performs.



Phase 2 (available from October 2012) – RHI tariffs

People in receipt of the Renewable Heat Premium Payments will be able to receive long term RHI tariff support once these tariffs are introduced, as will anybody who has installed an eligible technology since 15th July 2009.

Whilst Air source heat pumps will be eligible for the Renewable Premium Payment, a decision on whether or not they'll be included in the tariff payments will be based upon consumer feedback on the performance of the technologies. This should be clarified towards the end of 2011.

These tariff payments will start alongside the Green Deal from October 2012 to allow a more whole-house approach to heat production and energy saving.


10.3.2 Ground Source Heat Pumps (GSHP)

Description of Ground Source Heat Pumps

Ground-source heat pumps provide low temperature heat by extracting it from the ground or a body of water and provide cooling by reversing this process. Their principal application is space heating and cooling, though many also supply domestic hot water. They can even be used to maintain the integrity of building foundations in permafrost conditions, by keeping them frozen through the summer.

A ground-source heat pump (GSHP) system has three major components: the earth connection, a heat pump, and the heating or cooling distribution system. The earth connection is where heat transfer occurs. One common type of earth connection comprises tubing buried in horizontal trenches or vertical boreholes, or alternatively, submerged in a lake or pond. An antifreeze mixture, water or another heat-transfer fluid is circulated from the heat pump, through the tubing, and back to the heat pump in a “closed loop.” “Open loop” earth connections draw water from a well or a body of water, transfer heat to or from the water, and then return it to the ground or the body of water.

Since the energy extracted from the ground exceeds the energy used to run the heat pump, GSHP “efficiencies” can exceed 100%, and routinely average 200 to 500% over a season. Due to the stable, moderate temperature of the ground, GSHP systems are more efficient than air-source heat pumps, which exchange heat with the outside air. GSHP systems are also more efficient than conventional heating and Air-conditioning technologies, and typically have lower maintenance costs. They require less space, especially when a liquid building loop replaces voluminous air ducts, and, since the tubing is located underground, are not prone to vandalism like conventional rooftop units. Peak electricity consumption during cooling season is lower than with conventional air-conditioning, so utility demand charges may be reduced. Heat pumps typically range in cooling capacity from 3.5 to 35 kW (1 to 20 tons of Cooling). A single unit in this range is sufficient for a house or small commercial Building. The heat pump usually generates hot or cold air to be distributed locally by conventional ducts.



Advantages

The efficiency of GSHP system is measured by the coefficient of performance (COP). This is the ratio of units of heat output for each unit of electricity used to drive the compressor and pump for the ground loop. Average COP known as seasonal efficiency, is around 3-4 although some systems may produce a greater rate of efficiency. This means that for every unit of electricity used to pump the heat, 3-4 units of heat are produced, making it an efficient way of heating a building. If grid electricity is used for the compressor and pump, then a range of energy suppliers should be consulted in order to benefit from the lower running costs.

Cost & Savings

A typical 8-12kW system costs £6,000-£12,000 (not including the price of distribution system). This can vary with property and location. When installed in an electrically heated home a GSHP could save as much as £900 a year on heating bills and almost 7 tonnes of CO₂ a year. Savings will vary depending on what fuel is being replaced.

Available Grants

In March 2011, the UK Government announced the details of their Renewable Heat Incentive (RHI). RHI is designed to provide financial support that encourages individuals, communities and businesses to switch from using fossil fuel for heating, to renewables such as wood fuel.

There will be two phases for domestic customers:

Phase 1 (available from July 2011) - “RHI Premium Payment”

This is called the “RHI Premium Payment” and will be worth around £15m and available to 25,000 householders in Great Britain who install from July 2011.

The exact amounts available to consumers are confirmed:

*Ground Source Heat Pumps - £1,250/unit (available for off-gas installations only)

These are one off payments; so not annual. DECC plan to publish details of the “Phase 2 RHI Payment” and how this will apply next year. Recipients of this payment will need to ensure that:

- * They have a well-insulated property based on its energy performance certificate;
- * They agree to give feedback on how the equipment performs.

Phase 2 (available from October 2012) – RHI tariffs

People in receipt of the Renewable Heat Premium Payments will be able to receive long term RHI tariff support once these tariffs are introduced, as will anybody who has installed an eligible technology since 15th July 2009.

These tariff payments will start alongside the Green Deal from October 2012 to allow a more whole-house approach to heat production and energy saving

10.3.3 Combined Heat and Power (CHP) & Micro CHP

Description of CHP

The principle behind combined heat and power (cogeneration) is to recover the waste heat generated by the combustion of a fuel in an electricity generation system. This heat is often rejected to the environment, thereby wasting a significant portion of the energy available in the fuel that can otherwise be used for space heating and cooling, water



Syntegra Consulting Ltd, The Braccans Business Centre, 2 The Braccans, Bracknell, RG12 2XH
Registered Company No. 06408056

VAT Registration No. 980016044

epc.co.uk



heating, and industrial process heat and cooling loads in the vicinity of the plant. This cogeneration of electricity and heat greatly increases the overall efficiency of the system, anywhere from 25-55% to 60-90% depending on the equipment used, and the application.

A CHP installation comprises four subsystems: the power plant, the heat recovery and distribution system, an optional system for satisfying heating and/or cooling loads and a control system. A wide range of equipment can be used in the power plant, with the sole restriction being that the power equipment rejects heat at a temperature high enough to be useful for the thermal loads at hand. In a CHP system, heat may be recovered and distributed as hot water, conveyed from the plant to low temperature thermal loads in pipes for domestic hot water, or for space heating.

Advantages

CHP can significantly reduce primary energy consumption, and can therefore have a major impact on CO₂ emissions associated with the combustion of fossil fuels in conventional boilers. Each 1 kW of electrical capacity provided by CHP plant using fossil fuels has the potential to reduce annual CO₂ emissions by around 0.6 tonnes compared to gas-fired boilers and fully grid-derived electricity. For plant which is fuelled by renewable energy sources the potential is much greater.

Costs & Savings

Capital costs for CHP installations are higher than for alternative systems, but this can be recovered over a relatively short period of time (typically 5–10 years) for installations where there is a demand for heat and power for 4500 hours or more each year. The cost effectiveness is very sensitive to the relative price of electricity and fossil fuel which have been subject to frequent variations since de-regulation of the energy supply industries.

Micro CHP

Micro CHP (Combined Heat & Power) is the simultaneous production of useful heat and power within the home. It works very much like the gas boiler in a central heating system and heats the home in just the same way. However, at the same time it generates electricity, some of which will be used in the dwelling and the remainder will be exported to the electricity grid. Effectively the micro CHP unit replaces the gas central heating boiler and provides heat and hot water as usual, but additionally provides the majority of the home's electricity needs. Although individual units produce, by definition, relatively small amounts of electricity, the significance of micro CHP lies in the potentially huge numbers of systems which may ultimately be installed in the millions of homes in the UK where natural gas is currently the dominant heating fuel.



Available grants

The Feed - In – Tariffs have been introduced in order to give an incentive for micro CHP generated electricity. The Feed-In-Tariffs scheme is based on the principle that the energy supplier pays

generation tariff for every kWh the micro CHP system generates and an export tariff for every kWh of electricity supplied back to the national grid.

- Generation Tariff: 10.50 pence/kWh depending on installed rated output (up to 2KW)
- Export Tariff: 3.10pence/kWh
- Tariff period duration is 10 years

10.3.4 Fuel Cells

Description of Fuel Cells

A fuel cell is a device that generates more electricity by a chemical reaction. Every fuel cell has two electrodes, one positive and one negative, called, respectively, the anode and cathode. The reactions that produce electricity take place at the electrodes.


Every fuel cell also has an electrolyte, which carries electrically charged particles from one electrode to the other, and a catalyst, which speeds the reactions at the electrodes. Hydrogen is the basic fuel, but fuel cells also require oxygen.

One great appeal of fuel cells is that they generate electricity with very little pollution—much of the hydrogen and oxygen used in generating electricity ultimately combine to form a harmless by product, namely water.

Fuel Cell Operation

The purpose of a fuel cell is to produce an electrical current that can be directed outside the cell to do work, such as powering an electric motor or illuminating a light bulb or a city. Because of the way electricity behaves, this current returns to the fuel cell, completing an electrical circuit. The chemical reactions that produce this current are the key to how a fuel cell works.

There are several kinds of fuel cells, and each operates a bit differently. But in general terms, hydrogen atoms enter a fuel cell at the anode where a chemical reaction strips them of their electrons. The hydrogen atoms are now “ionized,” and carry a positive electrical charge. The negatively charged electrons provide the current through wires to do work. If alternating current (AC) is needed, the DC output of the fuel cell must be routed through a conversion device called an inverter.



Advantages

Even better, since fuel cells create electricity chemically, rather than by combustion, they are not subject to the thermodynamic laws that limit a conventional power plant. Therefore, fuel cells are

more efficient in extracting energy from a fuel. Waste heat from some cells can also be harnessed, boosting system efficiency still further.

Fuel Cells with Hydrogen from Renewable Sources

Fuel cells can be used as CHP systems in buildings. There are currently several different systems under development using different chemical processes, which operate at different temperatures. They currently use natural gas as the fuel, which is reformed to produce hydrogen, the required fuel for the fuel cell. When and if hydrogen becomes available from renewable energy, fuel cell CHP from renewable sources may be possible in buildings.

11. BE GREEN – RENEWABLE ENERGY

In this section the viable renewable energy technologies that will reduce the development's CO₂ emissions further by 20% are examined. Incorporating green design measures will significantly reduce the onsite energy consumption and the CO₂ emissions of the building. The 'London Plan' states that a further CO₂ reduction of 20% must be achieved by the installation of renewable technologies. Below is a review of possible renewable technologies for incorporation in the proposed development.

All of the LZC technologies are assessed against a number of criteria. Hence, LZC technology feasibility will be assessed according to the following criteria:

- VI. Renewable energy resource or fuel availability of the LZC technology on the site.
- VII. Space limitations due to building design and urban location of the site.
- VIII. Capital, operating and maintenance cost.
- IX. Planning Permission
- X. Implementation with regards the overall M&E design strategy for building type

The **ADDITIONAL** renewable/LZC technologies which were found non feasible based on the above criteria are the following:

- Wind Turbines
- Biomass Boilers
- Micro CHP
- Hydrogen Fuel Cells
- Small scale hydro power
- Grd. Source Heat Pump (GSHP)

11.1 Wind Turbines

Wind turbines are not feasible for the development since it does not meet the criteria mentioned above. Since the development is located in a dense residential and commercial area; the wind

resource may be restricted due to the adjacent large trees and air turbulence generated between them. The yearly average wind speed is quite low at 10 meters above ground.

Wind speed at 10m above ground level (m/s)

4.9	5.3	5.6
4.8	4.8	5
4.9	4.8	4.9

Wind speed at 25m above ground level (m/s)

5.7	6	6.3
5.6	5.6	5.8
5.7	5.6	5.7

Wind speed at 45m above ground level (m/s)

6.2	6.5	6.7
6.1	6.2	6.3
6.1	6.1	6.2

Squares surrounding the central square correspond to wind speeds for surrounding grid squares.

What does this mean?

Power generated is related to wind-speed by a cubic ratio. That means if you halve the wind-speed, the power goes down by a factor of 8 (which is $2 \times 2 \times 2$). A quarter of the wind-speed gives you a $\frac{1}{64}^{\text{th}}$ of the power ($4 \times 4 \times 4$).

As a rough guide, if your turbine is rated at producing 1KW at 12m/s then it will produce 125W at 6m/s and 15W at 3m/s.

Please Note!

Bear in mind that the NOABL wind-speed dataset used here is a model of wind-speeds across the country, assuming **completely flat terrain**. It isn't a database of measured wind-speeds. Other factors such as hills, houses, trees and other obstructions in your vicinity need to be considered as well as they can have a significant effect.

An actual wind-speed measurement using an anemometer has not been used for the purpose of this energy strategy report.

The central square highlighted in yellow demonstrates the average wind speed in m/s for the site. Squares surrounding the central square correspond to wind speeds for surrounding grid squares.

From the above table it is shown that the average wind speed on the development according to **NOABL database was estimated at 4.8m/s at 10m high above ground and 5.6m/s at 25m above ground.**

Wind turbine(s) have been discounted for this development scheme for the following reasons:

- A large mast horizontal axis wind turbine will not be able to generate electricity at optimal operating range since it requires higher average wind speeds. Furthermore, the installation of small scale wind turbines won't be feasible due to low average wind speed at 10 meters height, 25m & 45metre heights.
- Due to the close proximity of neighboring commercial & residential properties and trees.
- In addition, the low frequency noise generated by wind turbines might cause inconvenience to the neighboring residents. However, the level a person can be affected by low frequency noise varies from individual to individual.
- Due to the size and the required height of a potential wind turbine scheme there is also an issue with the propellers' impacting bird traffic, obtrusiveness, shadow flicker which means that generally large wind turbines need to be located at least 300m from any residential properties, which would not be possible on this site.
- Roof mounted units are limited in size due to wind induced stresses which are transmitted to the building structure. Most roof mounted turbines currently on the market are approximately 2m diameter and capable of producing 1-1.5kW each. However, the output is dependent on the surrounding obstructions and local wind speed. Thus small scale wind turbines would not make any meaningful impact on a site such as this.
- There are likely to be planning issues associated with wind turbines of a size necessary to affect any significant CO2 savings or energy savings.
- Because of the above the investment case with regards this technology solution is not viable compared to other solutions with a more attractive ROI.

- Finally, the installation of wind turbines on the development requires planning permission (and is likely to instigate neighborhood committee interest regarding its aesthetics and acoustic issues).

11.2 Biomass Boilers

Biomass boilers should not be considered for this project due to the following reasons:

- Furthermore, in common with other types of combustion appliances, biomass boilers are potentially a source of air pollution. Pollutants associated with biomass combustion include particulate matter (PM₁₀/ PM_{2.5}) and nitrogen oxides (NO_x) EMISSIONS. These pollution emissions can have an impact on local air quality and affect human health. Biomass has recently been rejected by many London Boroughs as means of obtaining the on-site renewable contribution (and this will soon send ripples out to other regions). This is because of their associated flue emissions (which can be significantly higher than gas fired boilers) and the difficulty of ensuring the boiler will operate at its optimum efficiency, which is often quoted by designers at the initial design stages. Biomass flue emissions are often difficult to control because the quality of fuel can vary significantly between suppliers. Given this a bio fuel system may not be acceptable to the Council on planning grounds (e.g. concerns about associated flue emissions/impact on local 'Air Quality', increase in road traffic from pellet delivery lorries).
- Biomass fuel requires more onerous and frequent wood fuel silo (site storage issues) replenishing by delivery trucks- which in turn can cause site transportation issues that will need to be considered and addressed along with the impact on the other residents and neighborhood infrastructure.
- Restrictions on the type of fuel and appliance may apply to the development and according to studies commissioned by DEFRA the levels of particles emitted by the burning of wood chip or waste would be considered to outweigh the benefits of carbon reduction especially in an urban environment such as the proposed development site.
- Dependant on a fuel supply chain contract being confirmed.
- There is no suitable location for the plant and storage of the pellets on site at present.
- The whole of London Borough of Southwark is in a smoke control zone.

11.3 Hydrogen Fuel Cells

Not commercially viable yet - As a result this solution will not be assessed any further.

The BlueGen product is a ceramic fuel cell and has recently entered the UK market this year.

Using ceramic fuel cells, BlueGen® electrochemically converts natural gas into electricity at up to 60 per cent electrical efficiency. Electricity is consumed locally, with unused power being exported to the grid. When the integrated heat recovery system is connected, the waste heat from BlueGen can be used to produce hot water - which improves the total efficiency to approximately 85 per cent.

11.4 Small scale Hydro

Small scale hydro-electric will not be studied any further because of the location and the spatial limitations of the development. There is no river or lake within the development site boundaries. As a result this solution will not be assessed any further.

11.5 Ground Source Heat pump (GSHP)

GSHP will not be studied any further for the following reasons:

- If an open loop configuration was to be adopted, a test borehole would be needed to assess the available resource. The test resource process is expensive and of course does not guarantee an acceptable resource in the ground. Additionally, a closed loop borehole configuration could not be used due to spatial limitations of the site.
- There are likely to be planning issues associated with borehole excavation and drilling.
- Running costs and maintenance may be minimal. However, installation is a costly affair. A GSHP solution would represent a relatively expensive option in comparison to other renewable technologies available.
- Additional electric immersion and pumps would be required to heat the GSHP water up to suitable temperature to be used around the building and it's likely a centralised plant area will also be required to house the circulation pumps.
- This technology is not recommended due to the increased plant energy consumption requirements in turn impacting the DER/TER score for the required energy strategy objectives.
- Furthermore, boreholes also destabilize the ground surface and may be considered a minus for environmentally friendly endeavours.

11.6 CHP & Micro CHP

CHP has not been considered further for this project for the following reasons:

- The average maximum heating load of a new apartment (built to 2010 building regs) is approximately 3kW and therefore most individual heating systems with independent condensing gas boilers would be incapable of working at optimal efficiencies or achieving their stated SEDBUK rating due to boiler cycling.
- Traditional CHP should not be considered for this project due to the spatial constraints of the development plot and dwelling layouts. There is not suitable space in the development for CHP plant.
- Heat from the CHP plant could be utilized to drive an absorption chiller during the summer months (tri-generation), but due to the sustainable design of the building fabric, and the use of

natural ventilation wherever possible, we anticipate that the cooling load will be minimal, making this a non-viable proposition.

- Micro-CHP is a relatively new concept (Baxi Ecogen was made available in 2009) and issues are raised in relation to unproven technology, inefficiency for shorter run cycles and lack of technical knowledge that can limit the practical application of micro CHP at present. In addition other issues surrounding the fact that around 50% of electricity generated in domestic properties is surplus, high installation costs and estimated low life expectancy has also been taken into consideration as to its commercial un-viability for this development scheme. Micro-CHP also has a lower FIT tariff rate and period duration and is only applicable for systems under 2kW.



Change of Use and Extension at
The Lion, 2 Britannia Street, London, WC1X 9JE
Building Regulation Part L1B Compliance.

Summary

Part L Compliance requires calculations to show improvements in the CO₂ emissions between the Existing building A4 (Drinking Establishment), using SAP 2009 Appendix R reference values and the proposed converted and extended development (8 No. Residential Units - Class C3), using declared U values, with improvements made where necessary.

Software used – Govt approved FSAP 2009 Stroma.

BRUKL Calculations

1. The calculations for the ***Existing Building*** gave the following results:-

TER = 12.87 kgCO₂/m².annum

BER = **32.64** kgCO₂/m².annum

And

2. The calculations for the ***Proposed Converted & Extended Building*** gave the following results:-

TER = 17.47 kgCO₂/m².annum

BER = **18.49** kgCO₂/m².annum

Improvements.

The Improvements to the property includes the following to the Thermal elements and services: -

1. Floor U value to be 0.2 w/m²k or better everywhere.
2. Walls to be lined 0.2 w/m²k or better.
3. Roof U value to be 0.16 w/m²k or better everywhere.

Syntegra Consulting Ltd, The Braccans Business Centre, 2 The Braccans, Bracknell, RG12 2XH
Registered Company No. 06408056 VAT Registration No. 980016044

T: 08450091625 E: mail@syntegra-epc.co.uk

4. Windows U values to be 1.4 w/m²k or better as double glazed argon filled.
5. Individual Condensing Combi gas boilers @ 89% efficiency to the flats.
6. Target in improvement of air permeability
7. 100% Energy Efficient lighting

Conclusion

The above results show a **43.4% improvement (reduction)** in CO₂ emissions from the *Existing Building* to the *Proposed change of use and extension* and therefore meets Building Regulations Part L1B criteria.

A.M. Wing-King
MSc, CEng, MEI, NDEA, OCDEA

14.11. 2013



BREEAM Domestic Refurbishment 2012 Pre-Assessment Estimator v0.7

This assessment and indicative BREEAM rating is not a formal certified BREEAM assessment or rating and must not be communicated as such. The score presented is indicative of a dwelling's potential performance and is based on a simplified pre-formal BREEAM assessment and unverified commitments given at an early stage in the design process.

Building name				The Lion, 2 Britannia Street		
Indicative building score (%)				71.10%		
Indicative BREEAM rating				BREEAM Excellent		
Management	Health & Wellbeing	Energy	Water	Materials	Waste	Pollution

	Minimum Standards				
	Pass	Good	Very Good	Excellent	Outstanding
Ene 02	✓	✓	✓	✓	✓
Wat 01	✓	✓	✓	✓	✗
Hea 05	✓	✓	✓	✓	✓
Hea 06	✓	✓	✓	✓	✓
Pol 03	✓	✓	✓	✓	✓
Mat 02	✓	✓	✓	✓	✓

INNOVATION

Section Weighting: 10%

Indicative Section Score: 1.00%

Comments	
----------	--

MANAGEMENT

Section Weighting: 12%

Indicative Section Score: 8.73%

Man 01 Home Users Guide				
No. of BREEAM credits available	3	Available contribution to overall score	3.27%	
No. of BREEAM innovation credits	0	Minimum Standards applicable:	No	
Assessment Criteria				Indicative Credits
Where a Home Users Guide be provided to all dwellings, covering all issues set out in the 'Users Guide Contents list', three credits may be awarded				3
Comments				
3No credits will be achieved since a Home User Guide will be produced and will cover all listed items in the User Guide Contents List.				

Man 02 Responsible Construction Practices				
No. of BREEAM credits available	2	Available contribution to overall score:	2.18%	
No. of BREEAM innovation credits	1	Minimum Standards applicable:	No	
Assessment Criteria				Indicative Credits
Where a compliant considerate construction scheme will be used, credits are awarded depending the score achieved as outlined below:				1
Large Scale - project with more than 5 units				
	One Credit	Two Credits		
Considerate Constructors Scheme	Score of 25-34 with a score of 5 in each section	Score of 35-39 with a score of 7 in each section		
Alternative Compliant Scheme	Compliance	Beyond Compliance		
Small Scale - project with 5 units or fewer				
	One Credit	Two Credits		
Considerate Constructors Scheme	Score of 25-34 with a score of 5 in each section	Score of 35-39 with a score of 7 in each section		
Alternative Compliant Scheme	Compliance	Beyond Compliance		
Checklist A-3	50% of the optional items	80% of the optional items		
Exemplary Credit				Indicative Innovation Credits Achieved
Considerate Constructors Scheme	Score of 40 or more with a score of 7 in each section	* Small Scale Project Only		Please Select
Alternative Compliant Scheme	Exemplary Level Compliance			
Checklist A-3*	All Items (Optional & Mandatory)			

Comments	1No Credits will be awarded. It is assumed that the principal contractor will use the Considerate Constructors Scheme (CCS) with a score of 25-34 or address 50% of the items in Checklist A-4.
----------	---

Man 03 Construction Site Impacts				
No. of BREEAM credits available	1	Available contribution to overall score	1.09%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where evidence demonstrate that site impacts will be monitored, as detailed below:				1
One Credit				
Large Scale	Where there is evidence to demonstrate that 2 or more of the sections in Checklist A-4 are completed			
Small Scale	Where there is evidence to demonstrate that 2 or more of the sections in Checklist A-5 are completed			
Sections of Checklist				
Large Scale - Checklist A-4		Small Scale - Checklist A-5		
Monitor, report and set targets for CO2 production of energy use arising from site activities		Set objectives for reducing CO2 production from energy use arising from site activities		
Monitor, report and set targets for water consumption arising from site activities		Set objectives for reducing water use arising from site activities		
A main contractor with an environmental materials policy		Main contractor environmental materials statement		
A main contractor that operates an Environmental Management System		80% of site timber is reclaimed, re-used or responsibly sourced		
80% of site timber is reclaimed, re-used or responsibly sourced				
Same definition of small and large scale as in Man 02				
Comments				
1No Credit will be achieved since the main contractor will (i) set objectives for reducing CO2 production from energy use arising from site activities (ii) set objectives for reducing water use arising from site activities (iii) provide environmental materials statement.				

Man 04 Security				
No. of BREEAM credits available	2	Available contribution to overall score:	2.18%	
No. of BREEAM innovation credits	0	Minimum Standards applicable:	No	
Assessment Criteria				Indicative Credits
Where the following requirements will be met:				1
One Credit Secure windows and doors	External doors and accessible windows meet minimum standards and appropriately certified			
Two Credits Secured by design	Principles and guidance of Secured by Design Section 2 are complied with			
	A suitably qualified security consultant is consulted at the design stage and their recommendations are incorporated into the refurbishment			
Comments				
1No credit will be achieved since the external door and the accessible windows will meet the following criteria: (i) Doors will be certified to: PAS 24:2007 or LPS 1175 Issue 7 Security Rating 1 or equivalent, (ii) Windows will be certified to: BS 7950:1997 (36) and LPS 1175 Issue 7 Security Rating 1 or equivalent.				
Man 05 Protection and Enhancement of Ecological Features				
No. of BREEAM credits available	1	Available contribution to overall score:	1.09%	
No. of BREEAM innovation credits	1	Minimum Standards applicable:	No	
Assessment Criteria				Indicative Credits
Where the following requirements will be met:				0
One Credit Protecting Ecological Features	Site survey carried out to determine presence of ecological features			
	Statutory Nature Conservation Organisation notified of protected species			
	Features of ecological value protected during refurbishment works			
Exemplary Credit Ecological enhancement	A suitably qualified ecologist recommends features to enhance ecology of the site			Indicative Innovation Credits Achieved Please Select
	adopts all general ecological recommendations			
	adopts 30% of additional recommendations			
Comments				
This credit is not sought.				
Man 06 Project Management				
No. of BREEAM credits available	2	Available contribution to overall score	2.18%	
No. of BREEAM innovation credits	2	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where the following requirements will be met:				2
One Credit Project Roles and Responsibilities	Where all of the project team are involved in the project decision making			
	Small Scale - the project manager assigns individual and shared responsibilities amongst the project team including all trades on site			
	Large Scale - the project manager assigns individual and shared responsibilities across the following key design and refurbishment stages: i. Planning and Building control notification ii. Design iii. Refurbishment iv. Commissioning and handover v. Occupation			
Small Scale projects: five units or fewer and less than £100k		Large Scale projects: more than five units and more than £100k		
One Credit Handover and Aftercare	Handover meeting arranged			
	2 or more of the following committed to: - A site inspection within 3 months of occupation - Conduct post occupancy interviews with building occupants or a survey via phone or posted information within 3 months of occupation - Longer term after care e.g. a helpline, nominated individual or other appropriate system to support building users for at least the first 12 months of occupation			
Exemplary Credits				Indicative Innovation Credits Achieved 1
One Exemplary Credit Early Design Input	Where A BREEAM Accredited Professional has been appointed to oversee key stages within the project. OR Where a BREEAM Domestic Refurbishment Assessor has been appointed at an early stage of the project, prior to the production of a refurbishment specification			
One Exemplary Credit Thermographic Surveying and Airtightness Testing	Where Thermographic surveying and Airtightness testing have been carried out at both pre and post refurbishment stages			
	Where an improved air tightness target has been set at design stage and testing demonstrates that this has been achieved post refurbishment			
Comments				
For the 1st credit, (i) all of the project team will be involved in the project decision making (ii) the project manager will assign individual and shared responsibilities amongst the project team including all trades on site. For the 2nd credit, (i) a handover meeting will be arranged (ii) a site inspection within 3 months of occupation will be carried out. One exemplary credit has been assumed since a BREEAM Domestic Refurbishment Assessor has been appointed at an early stage of the project, prior to the production of a refurbishment specification.				

HEALTH & WELLBEING		Section Weighting: 17%		Indicative Section Score 9.92%	
Hea 01 Daylighting					
No. of BREEAM credits available	2	Available contribution to overall score	2.83%		
No. of BREEAM innovation credits	0	Minimum Standards applicable	No		
Assessment Criteria				Indicative Credits	
Where the refurbishment results in a neutral impact on daylighting or where minimum daylighting standards are met, up to two credits may be awarded as follows:				1	
For Existing Dwellings and Change of Use Projects					
First Credit Maintaining Good Daylighting		The refurbishment results in a neutral impact on the dwellings daylighting levels in the kitchen, living room, dining room and study			
Where the property is being extended					
First Credit Maintaining Good Daylighting		New spaces achieve minimum daylighting levels			
		The extension does not significantly reduce daylighting levels in the kitchen, living room, dining room or study of neighbouring properties			
For All Properties					
Second Credit Minimum Daylighting		The dwelling achieves minimum daylighting levels in the kitchen, living room, dining room and study			
Comments					
It is anticipated that the conversion and extension will meet the required minimum daylight factor levels. It is envisaged that daylight calculations will be undertaken during the detail design stage.					
Hea 02 Sound Insulation					
No. of BREEAM credits available	4	Available contribution to overall score	5.67%		
No. of BREEAM innovation credits	0	Minimum Standards applicable	No		
Assessment Criteria				Indicative Credits	
To ensure the provision of acceptable sound insulation standards and so minimise the likelihood of noise complaints.				2	
Properties where sound testing has been carried out:					
Up to Four Credits		Four credits awarded according to the improvement over building regulations. See table in additional information in Technical Manual			
Properties where sound testing is not feasible and not required by the appointed Building Control body					
Two Credits		Where existing separating walls and floors are designed to meet the requirements of Building Regulations with compliant construction details			
Up to Four Credits		Where a Suitably Qualified Acoustician (SQA) provides recommendations for the specification of all existing separating walls and floors			
		SQA confirms in their professional opinion that they have the potential to meet or exceed the sound insulation credit requirements			
		Where these recommendations are implemented			
		See table in additional information in Technical Manual			
Historic Buildings					
Up to Four Credits		Where the dwelling is a Historic Building and sound testing results demonstrate existing separating walls and floor meet the Historic Building credit requirements			
		See table in additional information in Technical Manual			
		Where sound testing is not feasible and not required by the appointed Building Control body meeting criteria 2 and 3 using Table 12			
		Properties where sound testing has been carried out, credits awarded according to the improvement over building regulations. See table in additional information in Technical Manual			
		Where the dwelling is a detached property			
Detached Properties					
Four Credits		By Default			
Properties with separating walls or floors only between non habitable rooms OR Testing not required by building control body					
Four Credits		By Default			
Comments					
2No credits will be achieved if an accoustics consultant is on board and produces a noise assessment confirming Part E compliance. In the detailed stages of the project an assessment will be made of the expected reduction in internal noise levels as a result of the refurbishment.					
Hea 03 Volatile Organic Compounds					
No. of BREEAM credits available	1	Available contribution to overall score	1.42%		
No. of BREEAM innovation credits	0	Minimum Standards applicable	No		
Assessment Criteria				Indicative Credits	
Where the refurbishment avoids the use of VOCs with new products meeting the following requirements:				1	
One Credit Avoiding the use of VOCs		Where all decorative paints and varnishes used in the refurbishment have met the requirement listed in table 5.4 in the Technical Manual			
		Where at least five of the eight remaining product categories listed in table 5.4 have met the testing requirements and emission levels for Volatile Organic Compound (VOC) emissions against the relevant standards identified within table 5.4 in the Technical Manual			
		Where five or less products are specified within the refurbishment, all must meet the requirements in order to achieve this credit.			
Comments					
It is assumed that all decorative paints and varnishes and at least five of the categories listed in table 5.4 of the BREEAM domestic Refurbishment manual will meet the testing requirements and emission levels for VOC emissions against the relevant standards identified in table 5.4 of the BREEAM Domestic Refurbishment Manual.					
Hea 04 Inclusive Design					
No. of BREEAM credits available	2	Available contribution to overall score	2.83%		
No. of BREEAM innovation credits	1	Minimum Standards applicable	No		
Assessment Criteria				Indicative Credits	
Where an access statement has been carried out using Checklist A-8 of the Technical Manual to optimise the accessibility of the home as follows:				1	

	Checklist A-8 of the Technical Manual		
	Section 1	Section 2	
One Credit Minimum Accessibility	Completed with Evidence		
Two Credits Advanced Accessibility	Completed with Evidence	Completed with Evidence	
Exemplary Performance			Indicative Innovation
One Credit	Where an access expert suitably qualified member of the design team has completed sections 1, 2 and 3 of Checklist A-8, access statement template with evidence provided of the measures implemented in the refurbishment		Credits Achieved
			Please Select
Comments			
An Access statement will be produced and checklist A-8 of the BREEAM technical manual will be completed by a member of the design team.			

Hea 05 Ventilation				
No. of BREEAM credits available	2	Available contribution to overall score	2.83%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	Yes	
Assessment Criteria				Indicative Credits
Where the dwelling meets the following ventilation requirements:				1
One Credit Minimum Ventilation Requirements	A minimum level of background ventilation is provided (with trickle ventilators or other means of ventilation) for all habitable rooms, kitchens, utility rooms and bathrooms compliant with section 7, Building Regulations Approved Document Part F, 2010			
	A minimum level of extract ventilation is provided in all wet rooms (e.g. kitchen, utility and bath-rooms), compliant with section 5, Building Regulations Approved Document Part F 2010.			
	A minimum level of purge ventilation is provided in all habitable rooms and wet rooms, compliant with section 7, Building Regulations Approved Document Part F, 2010.			
	It is an historic building and meets historic building requirements in CN4 of the technical manual			
Two Credits Advanced Requirements	Ventilation is provided for the dwelling that meets the requirements of Section 5 of Building Regulations Part F in full			
	Where the building is a historic building and meets the requirements for Historic Buildings in compliance note 4 of the technical manual			
Comments				
It is assumed that a minimum level of background ventilation will be provided (with trickle ventilators or other means of ventilation) for all habitable rooms, kitchens and bathrooms compliant with section 7, Building Regulations Approved Document Part F, 2010. Also, it is assumed that a minimum level of extract ventilation will be provided in all wet rooms (e.g. kitchen, utility and bath-rooms), compliant with section 5, Building Regulations Approved Document Part F 2010. It is assumed that a minimum level of purge ventilation is provided in all habitable rooms and wet rooms, compliant with section 7, Part F, 2010.				
Hea 06 Safety				
No. of BREEAM credits available	1	Available contribution to overall score	1.42%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	Yes	
Assessment Criteria				Indicative Credits
Where a fire and carbon monoxide (CO) detection and alarm system is specified as follows:				1
One Credit Fire and Carbon Monoxide (CO) Detection and Alarm Systems	Where a compliant fire detection and fire alarm system is provided			
	Carbon Monoxide detector installed if dwelling is supplied with mains gas or other fossil fuel			
	Mains supplied fire detection and alarm system if project involves re-wiring*			
	Battery operated fire detection and alarm system if no re-wiring* is to take place			
* see CN9 in Hea 06 for the definition of re-wiring				
Comments				
Fire detectors, alarm system and Carbon Monoxide Detectors will be installed. These will be mains supplied if the project involves rewiring. Battery operated if not.				
ENERGY				
Section Weighting: 43%		Indicative Section Score 31.14%		
Ene 01 Improvement in Energy Efficiency Rating				
No. of BREEAM credits available	6	Available contribution to overall score	8.90%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where the following targets are met for the improvement in Energy Efficiency Rating achieved as a result of refurbishment:				1.5
	Improvement in EER	Credits		
	≥ 5	0.5		
	≥ 9	1		
	≥ 13	1.5		
	≥ 17	2		
	≥ 21	2.5		
	≥ 26	3		
	≥ 31	3.5		
	≥ 36	4		
	≥ 42	4.5		
	≥ 48	5		
	≥ 54	5.5		
	≥ 60	6		
Comments				
Syntegra Consulting Ltd has undertaken the pre refurbishment SAP calculations as designed post refurbishment SAP calculations. The energy averaging is applied for multiple dwellings. The average EER improvement is 15, and therefore 1.5No credits can be achieved.				
Ene 02 Energy Efficiency Rating Post Refurbishment				
No. of BREEAM credits available	4	Available contribution to overall score	5.93%	
No. of BREEAM innovation credits	2	Minimum Standards applicable	Yes	
Assessment Criteria				Indicative Credits
Where the following Energy Efficiency Rating benchmarks will be met as a result of refurbishment:				3.5
	EER post refurbishment	Credits	Minimum requirements	
	≥50	0.5	'Pass' level EER of 50	
	≥55	1	'Good' level EER of 58	
	≥60	1.5		
	≥65	2	'Very Good level' EER of 65	
	≥70	2.5	'Excellent' level EER of 70	
	≥75	3		
	≥80	3.5	'Outstanding' level EER of 81	
	≥85	4		
	Exemplary	Credits		Indicative Innovation Credits Achieved
	≥90	1		Please Select
	≥100	2		
Comments				
The average EER for post refurbishment is 82. Therefore, 3.5No credits are achieved.				

Ene 03 Primary energy demand				
No. of BREEAM credits available	7	Available contribution to overall score	10.38%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where the following Primary Energy Demand benchmarks will be met as a result of refurbishment:				7
	Primary Energy Demand Post Refurbishment (kWh/m ² /year)	Credits		
	≤ 400	0.5		
	≤ 370	1		
	≤ 340	1.5		
	≤ 320	2		
	≤ 300	2.5		
	≤ 280	3		
	≤ 260	3.5		
	≤ 240	4		
	≤ 220	4.5		
	≤ 200	5		
	≤ 180	5.5		
	≤ 160	6		
	≤ 140	6.5		
	≤ 120	7		
Comments				
As a result of the refurbishment the average area weighted primary energy demand will be 107.49 kWh/m ² /year. Therefore, 7 No Credits will be achieved.				
Ene 04 Renewable Technologies				
No. of BREEAM credits available	2	Available contribution to overall score	2.97%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where the dwelling will meet the following % contribution from renewables and primary energy demand targets as a result of refurbishment				0
	Dwelling Type	Primary Energy Demand	Percentage from Renewables	
			1 Credit	2 Credits
	Detached	≤ 250 kWh/m ² /year	≥10%	≥20%
	Semi-Detached		≥10%	≥20%
	Bungalow		≥10%	≥20%
	End of Terrace		≥10%	≥20%
	Mid Terrace	≤ 220 kWh/m ² /year	≥10%	≥20%
	Low Rise Flat		≥10%	≥20%
	Mid Rise Flat		≥10%	≥15%
	High Rise Flat		≥10%	≥15%
Comments				
These credits are not sought.				
Ene 05 Energy Labelled White Goods				
No. of BREEAM credits available	2	Available contribution to overall score	2.97%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where Energy Efficiency White goods are to be provided as follows:				2
First Credit				
	Appliance	Appliance provided	Appliance not to be provided	
	Fridges, Freezers and Fridge-Freezers	Energy Saving Trust Recommended appliances specified	EU Energy Efficiency Labelling Scheme Information Leaflet provided to all dwellings	
Second Credit				
	Appliance	Appliance provided	Appliance not to be provided	
	Washing Machines and Dishwashers	Energy Saving Trust Recommended appliances specified	Second credit not achieved	
	Washer-Dryers and Tumble Dryers	Appliances specified with B Rating under EU Energy Efficiency Labelling Scheme	EU Energy Efficiency Labelling Scheme Information Leaflet provided to all dwellings	
Comments				
It is assumed that fridges and freezers will be recognised by the Energy Saving recommended labelling scheme, carrying the Energy Saving recommended label. Also washing machines will be recognised by the Energy Saving Trust Recommended labelling scheme, carrying the Energy Saving Trust Recommended Label AND washer dryers and tumble dryers will have a B rating under the EU Energy Efficiency Labelling Scheme. Hence, 2 credits can be awarded.				
Ene 06 Drying Space				
No. of BREEAM credits available	1	Available contribution to overall score	1.48%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where adequate, secure internal or external space with posts and footings or fixings is provided with the following:				1
	1 Credit			
	Number of bedrooms	Drying line required		
	1-2	4m+		
	3+	6m+		
Comments				
For the 1-2 bedroom flats it has been assumed that 4m+ of drying line will be installed for each unit (over bath fixed lines). Hence 1 credit can be awarded.				
Ene 07 Lighting				
No. of BREEAM credits available	2	Available contribution to overall score	2.97%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where energy efficient internal and external lighting is provided as follows:				2
	External Lighting - 1 Credit			
	Energy Efficient Space Lighting of more than 45 lumens per circuit watt and Energy Efficient Security Lighting OR Where Energy Efficient Space Lighting is provided ONLY			
	Internal Lighting - 1 Credit			
	Maximum average wattage across the total floor area of the dwelling of 9 watts/m ²			
Comments				
2No credits will be achieved since all communal areas will be fitted with energy efficient space lighting and internal lighting will have a maximum average wattage of 9 Watts/m ² .				

Ene 08 Display Energy Devices				
No. of BREEAM credits available	2	Available contribution to overall score	2.97%	
No. of BREEAM innovation credits	1	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where consumption data is displayed to occupants by a compliant energy display device				1
Electricity usage data displayed		Primary Heating Fuel		
Electricity usage data displayed		Electricity	Other	
		2 credits awarded	1 credit awarded	
Primary Heating Fuel usage data displayed		N/A	1 credit awarded	
Electricity & Primary Heating Fuel usage displayed		N/A	2 credits awarded	
Exemplary Credits				
One credit		Where the first two credits are achieved		
Recording consumption data		Where any compliant Energy Display Device is capable of recording consumption data		Indicative Innovation Credits Achieved
				Please Select
Comments				
An energy display device for each unit will be installed that shows electricity usage data and records consumption data.				
Ene 09 Cycle Storage				
No. of BREEAM credits available	2	Available contribution to overall score	2.97%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where individual or communal compliant cycle storage is provided as follows:				2
Dwelling Size		One Credit	Two Credits	
Studios/ 1 bedroom		1 per two dwellings	1 per dwelling	
2-3 bedrooms		1 per dwelling	2 per dwelling	
4 bedrooms		2 per dwelling	4 per dwelling	
Comments				
It has been assumed that 13 cycle spaces will be provided. 3 Cycle spaces for the 1 bedroom units and 10 for the 2 bedroom units. Hence 2 credits can be awarded.				
Ene 10 Home Office				
No. of BREEAM credits available	1	Available contribution to overall score	1.48%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where sufficient space and services will be provided to allow occupants to set up a home office in a suitable room with adequate ventilation				1
Comments				
1 No. credit has been awarded since it is assumed that home office facilities will be provided within the lounge area of each flat.				
WATER				
Section Weighting: 11%		Indicative Section Score 8.80%		
Wat 01 Internal Water Use				
No. of BREEAM credits available	3	Available contribution to overall score	6.60%	
No. of BREEAM innovation credits	1	Minimum Standards applicable	Yes	
Assessment Criteria				Indicative Credits
Where the dwellings water consumption meets the following consumption benchmarks, or where terminal fittings meet the following water consumption standards:				2
Calculated Water Consumption (litres/person/day)	Equivalent terminal fitting standards	Minimum Standard	Credits	
>150	Typical baseline performance	N/A	0	
from 140 to ≤ 150	All showers specified to 'Good' OR All taps and WC's to 'Good' OR Kitchen fittings specified to 'Excellent'	N/A	0.5	
from 129 to < 140	All showers specified to 'Excellent' OR All showers and bathroom taps to 'Good'	BREEAM Very Good	1	
from 118 to < 129	All bathroom and WC room fittings specified to 'Good' OR All bathroom fittings specified to 'Excellent'	N/A	1.5	
from 107 to < 118	All Bathroom and WC room fittings specified to 'Excellent' OR All Bathroom fittings Specified to 'Excellent' and WC room fitting specified to 'Good' OR All Bathroom fittings, kitchen and utility fittings specified to 'Good'	BREEAM Excellent	2	
from 96 to < 107	All kitchen, bathroom, utility room and WC room fittings specified to 'Good' OR All bathrooms, kitchens and utility rooms specified to 'Excellent'	N/A	2.5	
< 96	All bathroom fittings specified to 'Excellent' and WC room, kitchen and utility room fittings specified to 'Good'	BREEAM Outstanding	3	
NOTE: 'Good' fittings are equivalent to good practice fittings with 'Excellent' fittings equivalent to best practice fittings (see the technical manual for full details).				
		Exemplary Credit	If the water consumption is less than 80l/person/day	Indicative Innovation Credits Achieved
				Please Select
Comments				
It is assumed 2 credits will be achieved since internal fittings will comply with a water consumption rate of between 107 and 118 litres/person/day.				
Wat 02 External Water Use				
No. of BREEAM credits available	1	Available contribution to overall score	2.20%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where the following requirements will be met:				1
Requirements:				
One Credit	Where a compliant rainwater collection system for external/internal irrigation use has been provided to dwellings. OR Where dwellings have no individual or communal garden space.			
Comments				
It is assumed 1 credit will be achieved since dwellings do not have individual or communal garden space.				
Wat 03 Water Meter				
No. of BREEAM credits available	1	Available contribution to overall score	2.20%	
No. of BREEAM innovation credits	0	Minimum Standards applicable	No	
Assessment Criteria				Indicative Credits
Where an appropriate water meter for measuring usage of mains potable water meter has been provided to dwelling(s), one credit may be awarded				1
Comments				
A water meter will be installed to each one of the units.				

MATERIALS		Section Weighting: 8%		Indicative Section Score 4.62%	
Mat 01 Environmental Impact of Materials					
No. of BREEAM credits available	25	Available contribution to overall score	4.44%		
No. of BREEAM innovation credits	0	Minimum Standards applicable	No		
Assessment Criteria				Indicative Credits	
Up to 25 credits can be awarded, with credits calculated using the Mat 01 calculator tool. The table below shows the maximum number of credits available for each element:				15	
Elements		Green Guide Rating credits available	Thermal performance credits available*		
Roof		5	3		
External walls		5	3.8		
Internal walls (including separating walls)		5	-		
Upper and Ground Floor		5	1.2		
Windows		5	2		
The full 25 credits represents all of the elements containing refurbished or existing materials that meet the Green Guide Rating of A+(6)					
GG Rating	Points for existing / refurbished elements		Points for new elements		
A+ (6)	5				
A+ (5)	4.6				
A+ (4)	4.2				
A+ (3)	3.8				
A+ (2)	3.4				
A+	3		3		
A	2		2		
B	1		1		
C	0.5		0.5		
D	0.25		0.25		
E	0		0		
Where the full 25 credits cannot be achieved the score can be 'topped up' with thermal performance credits. The full number of thermal performance credits for each element can be achieved when achieving the minimum U-values shown below.					
Elements		Minimum U-Value (W/m2K)			
Roof		0.11			
External walls		0.15			
Internal walls (including separating walls)		-			
Upper and Ground Floor		0.15			
Windows		1.4			
Comments					
The internal walls and windows will each attain at least a Green Guide rating of A. Therefore, at least 15No credits will be achieved. Retained elements such as external walls, roof undergoing refurbishment can achieve a maximum of 5 credits where will attain at least a Refurbishment Green Guide Rating of A.					
Mat 02 Responsible Sourcing of Materials					
No. of BREEAM credits available	12	Available contribution to overall score	2.13%		
No. of BREEAM innovation credits	0	Minimum Standards applicable	Yes		
Assessment Criteria				Indicative Credits	
Where new materials are responsibly sourced, up to 12 credits may be awarded where 80% of new materials for an element are responsibly sourced. The credits achieved are dependent on % of point achieved which is based upon the responsible sourcing tier level of each material sourced as detailed below:				3	
Table 1		Tier level		Points	
		1		4	
		2		3.5	
		3		3	
		4		2.5	
		5		2	
		6		1.5	
		7		1	
		8		0	
Table 2		BREEAM credits		% of available points achieved	
		12		≥54%	
		10		≥45%	
		8		≥36%	
		6		≥ 27%	
		4		≥ 18%	
		2		≥ 9%	
Comments					
All new timber used in the project will be sourced in accordance with the UK Government's Timber Procurement Policy.					
Mat 03 Insulation					
No. of BREEAM credits available	8	Available contribution to overall score	1.42%		
No. of BREEAM innovation credits	0	Minimum Standards applicable	No		
Assessment Criteria				Indicative Credits	
Where any new insulation specified for use within external walls, ground floor, roof and buildings services meet the following requirements:				8	
Requirements					
4 Credits	Where the Insulation Index for new insulation used in the buildings is ≥2				
	Where Green Guide ratings are determined using the Green Guide to specification tool				
Requirements					
4 Credits	Where ≥ 80% of the new thermal insulation used in the building elements is responsibly sourced.				
Comments					
8No credits will be achieved since (i) the insulation index for new insulation used in the buildings is ≥2, and the ratings will be determined using the green guide to specification tool. Also, ≥80% of the new thermal insulation will be responsibly sourced.					

WASTE		Section Weighting: 3%		Indicative Section Score 2.40%																		
Was 01 Household Waste																						
No. of BREEAM credits available	2	Available contribution to overall score	1.20%																			
No. of BREEAM innovation credits	0	Minimum Standards applicable	No																			
Assessment Criteria				Indicative Credits																		
Where compliant recycling and composting facilities are provided, up to two credits may be awarded as follows				1																		
<table border="1"> <thead> <tr> <th colspan="2">First Credit - Recycling Facilities</th> </tr> <tr> <th>Scenario</th> <th>Internal recycling storage requirements</th> </tr> </thead> <tbody> <tr> <td rowspan="4">Compliant collection scheme in place</td> <td>3 internal recycling containers provided where recycling is not sorted post collection</td> </tr> <tr> <td>1 internal recycling container provided where recycling is sorted post collection</td> </tr> <tr> <td>Minimum 30 litre total capacity, no single container less than 7 litre capacity</td> </tr> <tr> <td>Dedicated position in accordance with compliance note 1</td> </tr> <tr> <td rowspan="3">No compliant collection scheme in place No adequate external storage</td> <td>3 internal recycling containers provided</td> </tr> <tr> <td>Minimum 60 litre total capacity</td> </tr> <tr> <td>Dedicated position in accordance with compliance note 1</td> </tr> <tr> <td rowspan="3">No compliant collection scheme in place Adequate external storage provided</td> <td>3 internal recycling containers provided</td> </tr> <tr> <td>Minimum 30 litre total capacity, no single container smaller than 7 litre capacity</td> </tr> <tr> <td>Dedicated position in accordance with compliance note 1</td> </tr> </tbody> </table>						First Credit - Recycling Facilities		Scenario	Internal recycling storage requirements	Compliant collection scheme in place	3 internal recycling containers provided where recycling is not sorted post collection	1 internal recycling container provided where recycling is sorted post collection	Minimum 30 litre total capacity, no single container less than 7 litre capacity	Dedicated position in accordance with compliance note 1	No compliant collection scheme in place No adequate external storage	3 internal recycling containers provided	Minimum 60 litre total capacity	Dedicated position in accordance with compliance note 1	No compliant collection scheme in place Adequate external storage provided	3 internal recycling containers provided	Minimum 30 litre total capacity, no single container smaller than 7 litre capacity	Dedicated position in accordance with compliance note 1
First Credit - Recycling Facilities																						
Scenario	Internal recycling storage requirements																					
Compliant collection scheme in place	3 internal recycling containers provided where recycling is not sorted post collection																					
	1 internal recycling container provided where recycling is sorted post collection																					
	Minimum 30 litre total capacity, no single container less than 7 litre capacity																					
	Dedicated position in accordance with compliance note 1																					
No compliant collection scheme in place No adequate external storage	3 internal recycling containers provided																					
	Minimum 60 litre total capacity																					
	Dedicated position in accordance with compliance note 1																					
No compliant collection scheme in place Adequate external storage provided	3 internal recycling containers provided																					
	Minimum 30 litre total capacity, no single container smaller than 7 litre capacity																					
	Dedicated position in accordance with compliance note 1																					
<table border="1"> <thead> <tr> <th colspan="2">Second credit - Composting facilities</th> </tr> <tr> <th>With external space</th> <th>Without external space</th> </tr> </thead> <tbody> <tr> <td>Where a composting service or facility is provided for green/garden waste</td> <td>Where a composting service or facility is provided for kitchen waste</td> </tr> <tr> <td>Where a composting service or facility is provided for kitchen waste</td> <td>Where an interior container is provided for kitchen composting waste of at least 7 litres</td> </tr> <tr> <td>Where an interior container is provided for kitchen composting waste of at least 7 litres</td> <td></td> </tr> </tbody> </table>						Second credit - Composting facilities		With external space	Without external space	Where a composting service or facility is provided for green/garden waste	Where a composting service or facility is provided for kitchen waste	Where a composting service or facility is provided for kitchen waste	Where an interior container is provided for kitchen composting waste of at least 7 litres	Where an interior container is provided for kitchen composting waste of at least 7 litres								
Second credit - Composting facilities																						
With external space	Without external space																					
Where a composting service or facility is provided for green/garden waste	Where a composting service or facility is provided for kitchen waste																					
Where a composting service or facility is provided for kitchen waste	Where an interior container is provided for kitchen composting waste of at least 7 litres																					
Where an interior container is provided for kitchen composting waste of at least 7 litres																						
Comments																						
1No credit will be achieved as each unit will be provided with 3 internal recycling containers. Overall capacity will be a minimum of 30 litres.																						
Was 02 Refurbishment Site Waste Management																						
No. of BREEAM credits available	3	Available contribution to overall score	1.80%																			
No. of BREEAM innovation credits	1	Minimum Standards applicable	No																			
Assessment Criteria				Indicative Credits																		
Up to three credits are available depending on the site waste management plan to be implemented as follows				3																		
<table border="1"> <thead> <tr> <th colspan="2">Projects up to £100k</th> </tr> </thead> <tbody> <tr> <td>Three Credits</td> <td>Where waste generated through the refurbishment process is managed in accordance with Checklist A-9</td> </tr> <tr> <td>Exemplary Credit</td> <td>Where a compliant Level 1; Site Waste Management Plan (SWMP) is in place</td> </tr> </tbody> </table>						Projects up to £100k		Three Credits	Where waste generated through the refurbishment process is managed in accordance with Checklist A-9	Exemplary Credit	Where a compliant Level 1; Site Waste Management Plan (SWMP) is in place											
Projects up to £100k																						
Three Credits	Where waste generated through the refurbishment process is managed in accordance with Checklist A-9																					
Exemplary Credit	Where a compliant Level 1; Site Waste Management Plan (SWMP) is in place																					
<table border="1"> <thead> <tr> <th colspan="2">Projects up to £300k</th> </tr> </thead> <tbody> <tr> <td>Three Credits</td> <td>Where a compliant Level 1; Site Waste Management Plan (SWMP) is in place</td> </tr> <tr> <td rowspan="4">Exemplary Credit</td> <td>Where a compliant Level 2; Site Waste Management Plan (SWMP) is in place</td> </tr> <tr> <td>Non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the resource efficiency benchmark</td> </tr> <tr> <td>The percentage of non-hazardous construction waste and demolition waste generated by the project has been diverted from landfill and meets or exceeds the refurbishment & demolition waste diversion benchmarks</td> </tr> <tr> <td></td> </tr> </tbody> </table>						Projects up to £300k		Three Credits	Where a compliant Level 1; Site Waste Management Plan (SWMP) is in place	Exemplary Credit	Where a compliant Level 2; Site Waste Management Plan (SWMP) is in place	Non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the resource efficiency benchmark	The percentage of non-hazardous construction waste and demolition waste generated by the project has been diverted from landfill and meets or exceeds the refurbishment & demolition waste diversion benchmarks									
Projects up to £300k																						
Three Credits	Where a compliant Level 1; Site Waste Management Plan (SWMP) is in place																					
Exemplary Credit	Where a compliant Level 2; Site Waste Management Plan (SWMP) is in place																					
	Non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the resource efficiency benchmark																					
	The percentage of non-hazardous construction waste and demolition waste generated by the project has been diverted from landfill and meets or exceeds the refurbishment & demolition waste diversion benchmarks																					
<table border="1"> <thead> <tr> <th colspan="2">Projects over £300k</th> </tr> </thead> <tbody> <tr> <td>First Credit Management Plan</td> <td>Where a compliant Level 2; Site Waste Management Plan (SWMP) is in place</td> </tr> <tr> <td rowspan="5">Second Credit Good Practice Waste Benchmarks</td> <td>First credit achieved</td> </tr> <tr> <td>Non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the resource efficiency benchmark</td> </tr> <tr> <td>Amount of waste generated against £100,000 of project value is recorded in the SWMP</td> </tr> <tr> <td>Pre-refurbishment audit of the existing building is completed</td> </tr> <tr> <td>If demolition is included as part of the refurbishment programme, then the audit should also cover demolition materials</td> </tr> <tr> <td>Third Credit Best Practice Waste Benchmarks</td> <td>Where the first two credits have been achieved achieved</td> </tr> <tr> <td rowspan="3">Exemplary Credit</td> <td>Where Non-hazardous demolition waste generated by the dwellings refurbishment meets or exceeds the refurbishment & demolition waste diversion benchmarks</td> </tr> <tr> <td>Where non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the <i>exemplary level resource efficiency benchmark</i></td> </tr> <tr> <td>Where Non-hazardous demolition waste generated by the dwellings refurbishment meets or exceeds the exemplary level diversion benchmarks</td> </tr> </tbody> </table>						Projects over £300k		First Credit Management Plan	Where a compliant Level 2; Site Waste Management Plan (SWMP) is in place	Second Credit Good Practice Waste Benchmarks	First credit achieved	Non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the resource efficiency benchmark	Amount of waste generated against £100,000 of project value is recorded in the SWMP	Pre-refurbishment audit of the existing building is completed	If demolition is included as part of the refurbishment programme, then the audit should also cover demolition materials	Third Credit Best Practice Waste Benchmarks	Where the first two credits have been achieved achieved	Exemplary Credit	Where Non-hazardous demolition waste generated by the dwellings refurbishment meets or exceeds the refurbishment & demolition waste diversion benchmarks	Where non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the <i>exemplary level resource efficiency benchmark</i>	Where Non-hazardous demolition waste generated by the dwellings refurbishment meets or exceeds the exemplary level diversion benchmarks	
Projects over £300k																						
First Credit Management Plan	Where a compliant Level 2; Site Waste Management Plan (SWMP) is in place																					
Second Credit Good Practice Waste Benchmarks	First credit achieved																					
	Non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the resource efficiency benchmark																					
	Amount of waste generated against £100,000 of project value is recorded in the SWMP																					
	Pre-refurbishment audit of the existing building is completed																					
	If demolition is included as part of the refurbishment programme, then the audit should also cover demolition materials																					
Third Credit Best Practice Waste Benchmarks	Where the first two credits have been achieved achieved																					
Exemplary Credit	Where Non-hazardous demolition waste generated by the dwellings refurbishment meets or exceeds the refurbishment & demolition waste diversion benchmarks																					
	Where non-hazardous construction waste generated by the dwellings refurbishment meets or exceeds the <i>exemplary level resource efficiency benchmark</i>																					
	Where Non-hazardous demolition waste generated by the dwellings refurbishment meets or exceeds the exemplary level diversion benchmarks																					
Comments																						
The principal contractor will ensure that a BREEAM compliant SWMP will be in place. Syntegra Consulting would be able to provide consultation to achieve the required credits.																						
POLLUTION		Section Weighting: 6%		Indicative Section Score 4.50%																		
Pol 01 NOx Emissions																						
No. of BREEAM credits available	3	Available contribution to overall score	2.25%																			
No. of BREEAM innovation credits	0	Minimum Standards applicable	No																			
Assessment Criteria				Indicative Credits																		
Credits are awarded on the basis of NOx emissions arising from the operation of space heating and hot water systems for each refurbished dwelling as follows:				3																		
<table border="1"> <thead> <tr> <th colspan="2">Dry NOx Emissions</th> </tr> </thead> <tbody> <tr> <td>One Credit</td> <td>≤100 mg/kWh (NOx class 4 boiler)</td> </tr> <tr> <td>Two Credits</td> <td>≤70 mg/kWh (NOx class 5 boiler)</td> </tr> <tr> <td>Three Credits</td> <td>≤40 mg/kWh</td> </tr> </tbody> </table>						Dry NOx Emissions		One Credit	≤100 mg/kWh (NOx class 4 boiler)	Two Credits	≤70 mg/kWh (NOx class 5 boiler)	Three Credits	≤40 mg/kWh									
Dry NOx Emissions																						
One Credit	≤100 mg/kWh (NOx class 4 boiler)																					
Two Credits	≤70 mg/kWh (NOx class 5 boiler)																					
Three Credits	≤40 mg/kWh																					
Comments																						
The proposed Gas combi boilers for each flat will emit less than 40 mg/kWh. Hence, 3 credits can be awarded.																						

Pol 02 Surface Water Runoff																																		
No. of BREEAM credits available	3	Available contribution to overall score	2.25%																															
No. of BREEAM innovation credits	1	Minimum Standards applicable	No																															
Assessment Criteria			Indicative Credits																															
Where impacts of the refurbishment on surface water runoff are neutralised or where runoff is reduced as a result of refurbishment, up to three credits can be awarded as follows:			1																															
<table border="1"> <thead> <tr> <th colspan="2">Requirements</th> </tr> </thead> <tbody> <tr> <td rowspan="3">One Credit Neutral Impact on Surface Water</td> <td>New hard standing areas must be permeable</td> </tr> <tr> <td>If building on to previously permeable area additional run-off must be managed on site</td> </tr> <tr> <td>Calculations should be carried out by an appropriately qualified professional</td> </tr> <tr> <td colspan="2">Requirements</td> </tr> <tr> <td rowspan="4">OR Second Credits Reducing Run-Off From Site: Basic</td> <td>Where the criteria needed for One Credit has been achieved</td> </tr> <tr> <td>Where all run-off from the roof for rainfall depths up to 5 mm, have been managed on site using source control methods</td> </tr> <tr> <td>Include runoff from all existing and new parts of the roof.</td> </tr> <tr> <td>An appropriately qualified professional should be used to design an appropriate drainage strategy for the site</td> </tr> <tr> <td colspan="2">Requirements</td> </tr> <tr> <td rowspan="6">OR Three Credits Reducing Run-Off From Site: Advanced</td> <td>Where run-off as a result of the refurbishment is managed on site using source control</td> </tr> <tr> <td>An appropriately qualified professional should be used to design an appropriate drainage strategy for the site.</td> </tr> <tr> <td>The peak rate of run-off as a result of the refurbishment for the 1 in 100 year event has been reduced by 75% from the existing site.</td> </tr> <tr> <td>The total volume of run-off discharged into the watercourses and sewers as a result of the refurbishment, for a 1 in 100 year event of 6 hour duration has been reduced by 75%.</td> </tr> <tr> <td>An allowance for climate change must be included for all of the above calculations, in accordance with current best practice (PPS25, 2010).</td> </tr> <tr> <td></td> </tr> <tr> <td colspan="2">Requirements</td> </tr> <tr> <td rowspan="5">Exemplary Credit</td> <td>Where all run-off from the developed site is managed on site using source control</td> </tr> <tr> <td>The peak rate of run-off as a result of the refurbishment for the 1 in 1 year event is reduced to zero.</td> </tr> <tr> <td>The peak rate of run-off as a result of the refurbishment for the 1 in 100 year event is reduced to zero.</td> </tr> <tr> <td>There is no volume of run-off discharged into the watercourses and sewers as a result of the refurbishment, for a 1 in 100 year event of 6 hour duration.</td> </tr> <tr> <td>An allowance for climate change must be included for all of the above calculations, in accordance with current best practice (PPS25, 2010).</td> </tr> </tbody> </table>				Requirements		One Credit Neutral Impact on Surface Water	New hard standing areas must be permeable	If building on to previously permeable area additional run-off must be managed on site	Calculations should be carried out by an appropriately qualified professional	Requirements		OR Second Credits Reducing Run-Off From Site: Basic	Where the criteria needed for One Credit has been achieved	Where all run-off from the roof for rainfall depths up to 5 mm, have been managed on site using source control methods	Include runoff from all existing and new parts of the roof.	An appropriately qualified professional should be used to design an appropriate drainage strategy for the site	Requirements		OR Three Credits Reducing Run-Off From Site: Advanced	Where run-off as a result of the refurbishment is managed on site using source control	An appropriately qualified professional should be used to design an appropriate drainage strategy for the site.	The peak rate of run-off as a result of the refurbishment for the 1 in 100 year event has been reduced by 75% from the existing site.	The total volume of run-off discharged into the watercourses and sewers as a result of the refurbishment, for a 1 in 100 year event of 6 hour duration has been reduced by 75%.	An allowance for climate change must be included for all of the above calculations, in accordance with current best practice (PPS25, 2010).		Requirements		Exemplary Credit	Where all run-off from the developed site is managed on site using source control	The peak rate of run-off as a result of the refurbishment for the 1 in 1 year event is reduced to zero.	The peak rate of run-off as a result of the refurbishment for the 1 in 100 year event is reduced to zero.	There is no volume of run-off discharged into the watercourses and sewers as a result of the refurbishment, for a 1 in 100 year event of 6 hour duration.	An allowance for climate change must be included for all of the above calculations, in accordance with current best practice (PPS25, 2010).	Indicative Innovation Credits Achieved Please Select
Requirements																																		
One Credit Neutral Impact on Surface Water	New hard standing areas must be permeable																																	
	If building on to previously permeable area additional run-off must be managed on site																																	
	Calculations should be carried out by an appropriately qualified professional																																	
Requirements																																		
OR Second Credits Reducing Run-Off From Site: Basic	Where the criteria needed for One Credit has been achieved																																	
	Where all run-off from the roof for rainfall depths up to 5 mm, have been managed on site using source control methods																																	
	Include runoff from all existing and new parts of the roof.																																	
	An appropriately qualified professional should be used to design an appropriate drainage strategy for the site																																	
Requirements																																		
OR Three Credits Reducing Run-Off From Site: Advanced	Where run-off as a result of the refurbishment is managed on site using source control																																	
	An appropriately qualified professional should be used to design an appropriate drainage strategy for the site.																																	
	The peak rate of run-off as a result of the refurbishment for the 1 in 100 year event has been reduced by 75% from the existing site.																																	
	The total volume of run-off discharged into the watercourses and sewers as a result of the refurbishment, for a 1 in 100 year event of 6 hour duration has been reduced by 75%.																																	
	An allowance for climate change must be included for all of the above calculations, in accordance with current best practice (PPS25, 2010).																																	
Requirements																																		
Exemplary Credit	Where all run-off from the developed site is managed on site using source control																																	
	The peak rate of run-off as a result of the refurbishment for the 1 in 1 year event is reduced to zero.																																	
	The peak rate of run-off as a result of the refurbishment for the 1 in 100 year event is reduced to zero.																																	
	There is no volume of run-off discharged into the watercourses and sewers as a result of the refurbishment, for a 1 in 100 year event of 6 hour duration.																																	
	An allowance for climate change must be included for all of the above calculations, in accordance with current best practice (PPS25, 2010).																																	
Comments 1 No. credit has been assumed since the development will have SUDS strategy implemented. It is also assumed that calculations by a qualified Hydrologist will be provided at design stage.																																		
Pol 03 Flooding																																		
No. of BREEAM credits available	2	Available contribution to overall score	1.50%																															
No. of BREEAM innovation credits	0	Minimum Standards applicable	Yes																															
Assessment Criteria			Indicative Credits																															
Where the dwelling is located in a low flood risk zone, or where in a medium to high flood risk zone and a flood resilience/resistance strategy has been implemented, up to two credits can be awarded as follows:			2																															
<table border="1"> <tbody> <tr> <td>Minimum Standards</td> <td>A minimum of two credits must be achieved for this issue at the Excellent and Outstanding levels</td> </tr> <tr> <td colspan="2">Option 1 - Low Flood Risk</td> </tr> <tr> <td>Two Credits</td> <td>Where a Flood Risk Assessment (FRA) has been carried out and the assessed dwellings are defined as having a low annual probability of flooding.</td> </tr> <tr> <td colspan="2">Option 2 - Medium / High Flood Risk</td> </tr> <tr> <td rowspan="3">Two Credits</td> <td>Where a Flood Risk Assessment (FRA) has been carried out and the assessed dwellings are defined as having a medium or high annual probability of flooding.</td> </tr> <tr> <td>Two credits are awarded where as a result of the dwellings floor level or measures to keep water away the dwelling is defined as achieving avoidance from flooding by following Checklist A-10; Decision Strategy Flow Chart</td> </tr> <tr> <td>Where avoidance is not possible, two credits are achieved where a full flood resilience/resistance strategy is implemented for the dwellings in accordance with recommendations made by a Suitably Qualified Building Professional</td> </tr> </tbody> </table>				Minimum Standards	A minimum of two credits must be achieved for this issue at the Excellent and Outstanding levels	Option 1 - Low Flood Risk		Two Credits	Where a Flood Risk Assessment (FRA) has been carried out and the assessed dwellings are defined as having a low annual probability of flooding.	Option 2 - Medium / High Flood Risk		Two Credits	Where a Flood Risk Assessment (FRA) has been carried out and the assessed dwellings are defined as having a medium or high annual probability of flooding.	Two credits are awarded where as a result of the dwellings floor level or measures to keep water away the dwelling is defined as achieving avoidance from flooding by following Checklist A-10; Decision Strategy Flow Chart	Where avoidance is not possible, two credits are achieved where a full flood resilience/resistance strategy is implemented for the dwellings in accordance with recommendations made by a Suitably Qualified Building Professional																			
Minimum Standards	A minimum of two credits must be achieved for this issue at the Excellent and Outstanding levels																																	
Option 1 - Low Flood Risk																																		
Two Credits	Where a Flood Risk Assessment (FRA) has been carried out and the assessed dwellings are defined as having a low annual probability of flooding.																																	
Option 2 - Medium / High Flood Risk																																		
Two Credits	Where a Flood Risk Assessment (FRA) has been carried out and the assessed dwellings are defined as having a medium or high annual probability of flooding.																																	
	Two credits are awarded where as a result of the dwellings floor level or measures to keep water away the dwelling is defined as achieving avoidance from flooding by following Checklist A-10; Decision Strategy Flow Chart																																	
	Where avoidance is not possible, two credits are achieved where a full flood resilience/resistance strategy is implemented for the dwellings in accordance with recommendations made by a Suitably Qualified Building Professional																																	
Comments A Flood Risk Assessment will be undertaken for the 'The Lion, 2 Britannia Street' development by a qualified Hydrologist. According to the Environment agency the site is expected to be of low flooding risk. Hence, two credits can be awarded if the dwellings will be defined as having a low annual probability of flooding.																																		

BREEAM Domestic Refurbishment 2012 Pre-Assessment Estimator v0.6: Results Summary



Building name	The Lion, 2 Britannia Street
Indicative Building Score	71.10%
Indicative Building Rating	BREEAM Excellent

This assessment and indicative BREEAM rating is not a formal certified BREEAM assessment or rating and must not be communicated as such. The score presented is indicative of a dwelling's potential performance and is based on a simplified pre-formal BREEAM assessment and unverified commitments given at an early stage in the design process.

	Issue	Credits Available	Indicative Credits Achieved	Weighting	Section Score
Management	Man 01	3	3	12%	8.73%
	Man 02	2	1		
	Man 03	1	1		
	Man 04	2	1		
	Man 05	1	0		
	Man 06	2	2		

Health and Wellbeing	Hea 01	2	1	17%	9.92%
	Hea 02	4	2		
	Hea 03	1	1		
	Hea 04	2	1		
	Hea 05	2	1		
	Hea 06	1	1		

Energy	Ene 01	6	1.5	43%	31.14%
	Ene 02	4	3.5		
	Ene 03	7	7		
	Ene 04	2	0		
	Ene 05	2	2		
	Ene 06	1	1		
	Ene 07	2	2		
	Ene 08	2	1		
	Ene 09	2	2		
	Ene 10	1	1		

Water	Wat 01	3	2	11%	8.80%
	Wat 02	1	1		
	Wat 03	1	1		

Materials	Mat 01	25	15	8%	4.62%
	Mat 02	12	3		
	Mat 03	8	8		

Waste	Was 01	2	1	3%	2.40%
	Was 02	3	3		

Pollution	Pol 01	3	3	6%	4.50%
	Pol 02	3	1		
	Pol 02	2	2		

Innovation	10	1	N/A		1.00%
------------	----	---	-----	--	-------

	Minimum Standards				
	Pass	Good	Very Good	Excellent	Outstanding
Ene 02	✓	✓	✓	✓	✓
Wat 01	✓	✓	✓	✓	✗
Hea 05	✓	✓	✓	✓	✓
Hea 06	✓	✓	✓	✓	✓
Pol 03	✓	✓	✓	✓	✓
Mat 02	✓	✓	✓	✓	✓

