DRAWING N°.
RG-80-307
SHEET 1 OF 2

IF IN DOUBT ASK DO NOT SCALE





GLAZING SPECIFICATION:

OUTER SKIN: 25.5mm CLEAR TOUGHENED LAMINATED GLASS

OPTIONAL CERAMIC SLIP RESISTANT COATING TO FACE 1

WITH 75mm BLACK PAINTED BORDER TO FACE 1

CAVITY: 18mm ARGON FILLED

INNER SKIN: 6mm CLEAR TOUGHENED GLASS

WITH SOFT COAT LOW-E COATING TO FACE 3 OVER 1.7m<sup>2</sup> 14mm CAVITY 8mm INNER SKIN PLAN VIEW

MAXIMUM KERB SIZE

SQUARE ROOFLIGHTS 1700mm x 1700mm

RECTANGULAR ROOFLIGHTS 3m<sup>2</sup>

MAXIMUM KERB LENGTH = SPAN x 3

THIS DRAWING MUST NOT BE COPIED OR PASSED TO A THIRD PARTY WITHOUT  CHECKED  CHECKED  DATE	TOLERANCE UNLESS OTHERWISE STATED ±5  DIMENSIONS IN	THERWISE STATED ±5  ALUMINIUM  FINISH  POLYESTER POWDER  COATING, RAL				Roofglaze Limited, 30-32 Little End Road, Eaton Socon, St Neots, Cambs, PE19 8JH Telephone 01480 474797. Fax 01480 474774. E-mail technical@roofglaze.co.uk	ROO	FGLAZE
WRITTEN CONSENT FROM ROOFGLAZE LIMITED.  DRAWN  D. PUGH  DATE  28-2-2012	SCALE		REV AMENDMENTS	SIGNED	CHECKED	TITLE: FLAT GLAZE ROOFLIGHT WALK ON SPECIFICATION	A1 QUOTE N°.	RG-80-307 SHEET 1 OF 2