

## Schedule No 10

Ref		Description	Manufacturer	Type / Cat No	Lamp / Colour	Notes
A	+	Recessed ceiling grid Linear fluorescent	Luxonic Lighting	Luxonic Broad lighter	1 x 28w att T5	DSI Dimming
Α	-	Office Area	Whitecroft	Whitecroft Duo 2 range	fluorescent	High Frequency
AE		Office Area		•	White	nigri Frequency
AE		D: 4075 000	Concord	LuxLite		
	-	Dims: 1275 x 300mm			C.Temp : 4000° K	Micro prism optic
	-	AE = 3hr emergency version			Opal Diffuser Tpa rated	
В		Circular recessed downlighter version	DAL	DAL BE dow nlight	1 x18 w att compact	Low height version
		Offfice area r/Staircase Lobby areas /Toilet area			fluorescent	148 mm
BE		Dims : 190 Ø mm		BWE = w allw asher emergency	Fine trim	
		Cut -out :175 Ø			C.Temp : 4000° K	
BWW	MINITRIM TEMPO 125	BE = 3hr emergency version				
С		Compact Fluorescent recessed downlight with-	Concord	Concord Led 150 TE	1 x 18 w att TC-TEL	High Frequency
	CE SUP	Facited bezel	Whitecroft		White	
CE		Back of house			C.Temp : 4000° K	Low height version
	The contract of the contract o	Dims: 165 Ø, Recessed depth: 156				142mm
		CE= 3 hr emergency version				
D2		linear fluorescent	Concord	Concord Continium	1 x 28w T5	High Frequency
	200	Staircase lighting 1 x 28 w att version	DAL	DAL Light line 88	White	3hr Emergency
D2E		Toilet lobby areas			C.Temp : 4000° K	
		Dims: 1200 x 88mm 1500 x 88mm				
		DE= 3hr emergency version			Opal diffuser	Tpa rated
F		Wall Mounted Light fitting Toilet	Whitecroft	Lunar LUNh128EM	1 x 28w att 2D	High Frequency
· ·	†	10th floor	Concord	Opaline	20 4 20	3hr Emergency
		Tournoor	Coricord	Ориште	C.Temp : 4000° K	on Energency
					O. 1611p . 7000 K	
	-	Dims: 360 x 55mm			01-4:66	IP Rated
G	╀	Wall mounted 200w flood light	0	O Bi-bii NO(4)N/	Opal diffuser	
G	-	ū	Cooper	Cooper lighting MX1W	2 x 100w halogen	Tungsten
		Future Tenants Area ( Temporary)				Halogen
					White	
Ref		Description	Manufacturer	Type / Cat No	Lamp / Colour	Notes
J		Tray Downlighter surface mounted	Wila	Wila recessed trough Lighting	100w QR-LP111	High frequency
		Ground floor reception area		BESPOKE	1 x 18w TC-TEL	Metal Halide
					1 x 35w HIT	
						3hr Em led inbuilt
						OPTION 1
K			Luxonic	Luxonic HA1036TCL/HF/SG	1 x 26 w att TCL x 3	Metal halide
	3	Surface Mounted /External/ internal/Reception Area	Concord		1 x 36 w att HIT x 3	
	(E)		Wila	Wila recessed trough lighting		IP rated for external lights
	0-4					
	Mr. a.	Dims upto 4500 x 230		BESPOKE		-
	(3)	Dims upto 4500 x 230		BESPOKE		3hr Em led inbuilt
L			Thorn		1 x 28 w att T5	3hr Em led inbuilt
L		Surface mounted Linear fluorescent	Thorn	BESPOKE Arrow slim	1 x 28 w att T5	-
			Thorn		White	3hr Em led inbuilt High Frequency
L LE		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles	Thorn			3hr Em led inbuilt
		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles Dims: 1200 x 90	Thorn		White C.Temp : 4000° K	3hr Em led inbuilt High Frequency 3hr Emergency
LE		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles Dims: 1200 x 90 LE= 3hr emergency version		Arrow slim	White C.Temp : 4000° K Opal diffuser	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated
		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles Dims: 1200 x 90 LE=3hr emergency version Twin linear fluorescent ( Corrosion resistant )	Thorn		White C.Temp : 4000° K Opal diffuser 2 x 35w T5	3hr Em led inbuilt High Frequency 3hr Emergency
LE		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles Dims: 1200 x 90 LE= 3hr emergency version		Arrow slim	White C.Temp: 4000° K  Opal diffuser 2 x 35w T5  White	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated
LE		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles Dims: 1200 x 90 LE=3hr emergency version Twin linear fluorescent ( Corrosion resistant )		Arrow slim	White C.Temp : 4000° K Opal diffuser 2 x 35w T5	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated
LE		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles Dims: 1200 x 90 LE=3hr emergency version Twin linear fluorescent ( Corrosion resistant )		Arrow slim	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated
LE M		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90  LE= 3hr emergency version  Tw in linear fluorescent ( Corrosion resistant )  Plant rooms	Luxonic	Arrow slim  Luxonic corrosion resistant	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency
LE		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign	Luxonic  Cooper lighting	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated High Frequency 3hr Non-Maintained
LE M		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90  LE= 3hr emergency version  Tw in linear fluorescent ( Corrosion resistant )  Plant rooms	Luxonic  Cooper lighting Channel	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest )	White C.Temp: 4000° K  Opal diffuser 2 x 35w T5  White C.Temp: 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency
LE M		Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Twin linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors	Luxonic  Cooper lighting	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated High Frequency 3hr Non-Maintained
LE M	**	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign	Luxonic  Cooper lighting Channel	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest )	White C.Temp: 4000° K  Opal diffuser 2 x 35w T5  White C.Temp: 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated High Frequency 3hr Non-Maintained
LE M	<b>★</b> →	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Twin linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors	Luxonic  Cooper lighting Channel	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest )	White C.Temp: 4000° K  Opal diffuser 2 x 35w T5  White C.Temp: 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated High Frequency 3hr Non-Maintained
LE M	<b>★</b> → <b>I</b>	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Twin linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors	Luxonic  Cooper lighting Channel	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest )	White C.Temp: 4000° K  Opal diffuser 2 x 35w T5  White C.Temp: 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated High Frequency 3hr Non-Maintained
M P1	<b>★</b> →	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm	Luxonic  Cooper lighting Channel White croft	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest ) Pathfinder	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 1 x 9w att LED	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency  3hr Non-Maintained Emergency
M P1	<b>₹</b> → <b>1</b>	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm  Tw in spot emergency w all mounted fitting	Luxonic  Cooper lighting Channel White croft	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest ) Pathfinder	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 1 x 9w att LED	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency  3hr Non-Maintained Emergency  Halogen Lamps
M P1	**	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE=3hr emergency version Twin linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm  Twin spot emergency w all mounted fitting Futre Tenants Area	Luxonic  Cooper lighting Channel White croft	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest ) Pathfinder	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 1 x 9w att LED	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency  3hr Non-Maintained Emergency  Halogen Lamps
LE M	<b>★→</b>	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm  Tw in spot emergency w all mounted fitting	Luxonic  Cooper lighting Channel White croft	Arrow slim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest ) Pathfinder	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 1 x 9w att LED	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency  3hr Non-Maintained Emergency  Halogen Lamps
LE M	<b>★→</b>	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm  Tw in spot emergency w all mounted fitting Futre Tenants Area  Dims: 365 x 210mm	Luxonic  Cooper lighting Channel White croft  Channel	Arrowslim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting (Forest) Pathfinder  Channel Lighting (Maxi Flood)	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5 White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 1 x 9w att LED 2 x 20w att	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated High Frequency  3hr Non-Maintained Emergency  Halogen Lamps 3hr Emergency
LE M	<b>★</b> → <b>I</b>	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm  Tw in spot emergency w all mounted fitting Futre Tenants Area  Dims: 365 x 210mm  Recessed IP rated downlight	Luxonic  Cooper lighting Channel White croft	Arrowslim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest ) Pathfinder  Channel Lighting ( Maxi Flood )  Whitecroft lighting	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 1 x 9w att LED 2 x 20w att	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency  3hr Non-Maintained Emergency  Halogen Lamps 3hr Emergency
LE M P1 QE S	**-	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm  Tw in spot emergency w all mounted fitting Futre Tenants Area  Dims: 365 x 210mm  Recessed IP rated dow nlight Show ers /Toilet areas basement	Luxonic  Cooper lighting Channel White croft  Channel	Arrowslim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting (Forest) Pathfinder  Channel Lighting (Maxi Flood)	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 2 x 20w att  1 x 26w Downlighter White	3hr Em led inbuilt High Frequency 3hr Emergency Tpa rated High Frequency  3hr Non-Maintained Emergency  Halogen Lamps 3hr Emergency
LE M	<b>★→</b>	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Twin linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm  Twin spot emergency w all mounted fitting Futre Tenants Area  Dims: 365 x 210mm  Recessed IP rated downlight Showers /Toilet areas basement Dims: 165 Ø , Recessed depth: 156	Luxonic  Cooper lighting Channel White croft  Channel	Arrowslim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest ) Pathfinder  Channel Lighting ( Maxi Flood )  Whitecroft lighting	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 1 x 9w att LED 2 x 20w att	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency  3hr Non-Maintained Emergency  Halogen Lamps 3hr Emergency
LE M P1 QE S	<b>★→</b>	Surface mounted Linear fluorescent Staircase Lighting/Toilet cubicles  Dims: 1200 x 90 LE= 3hr emergency version Tw in linear fluorescent ( Corrosion resistant ) Plant rooms  Emergency exit sign Exit doors  Dims: 200 x 100 mm  Tw in spot emergency w all mounted fitting Futre Tenants Area  Dims: 365 x 210mm  Recessed IP rated dow nlight Show ers /Toilet areas basement	Luxonic  Cooper lighting Channel White croft  Channel	Arrowslim  Luxonic corrosion resistant  Cooper Lighting Evolved Channel Lighting ( Forest ) Pathfinder  Channel Lighting ( Maxi Flood )  Whitecroft lighting	White C.Temp : 4000° K  Opal diffuser 2 x 35w T5  White C.Temp : 4000° K  Opal diffuser 15 x longlife1w att LED 1 x 1w att LED 2 x 20w att  1 x 26w Downlighter White	3hr Em led inbuilt  High Frequency  3hr Emergency  Tpa rated High Frequency  3hr Non-Maintained Emergency  Halogen Lamps 3hr Emergency