

Riser Installation Method Statement:

Existing masonry to chased out to create required riser size.

Where riser passes behind skirtings and cornices the masonry behind is to be carefully removed leaving the skirtings and cornices in place and undisturbed.

This should be kept to a minimum as much of the existing fabric in place as possible.

NOTE:

- Riser sizes and content & manifold cabinets to mechanical and electrical engineer's specification.

			NO DIPPRISONS ARE TO BE SCALED FRONT HIS DRAWNIS, THE CONTRACTIOR/MARKACHER IS REPONSIBLE FOR CHEGING ALL DIPPRISONS AND QUERRIG ANY DISCIPRACES. THIS DRAWNIS IS THE PROPERTY OF BIOLARCHITECTS LTD. COPPRIGHT'S RESERVED BY THEN AND THE DRAWNIS IS SEED ON CONDITION THAT IT IS NOT COPIED REPRODUCED, RETAINED OR DISCIPRED ANY LAWLIN-DRIVED PRECIN, EITHER WHICLEY OR NIVATE WITHOUT WRITTEN CONDIST.		Project N° 479			Revision P1	e info@burwellarchitects.com w www.burwellarchitects.com a unit 0.01 california building deals gateway london SE13 7SF	
						I:5 @ AI, I:10 @ A3 JAN 2013		TENDER GN	t 020 8305 6010 f 020 8305 6020	
					Drawing	Drawing Typical Riser and Manifold Cabinet Section & Elevation			burwell deakins : architects	
P1	08.03.13	Issued for Planning			Project	31 Tavistock Squ		EZ		
Revision	Date	Amendment	Notes		Client	University Colleg	e London			