



KEY:

- ① 20mm DEFLECTION HEAD SEALED WITH INTUMESCENT MASTIC
- ② 100mm KINGSPAN K15 -OR SIMILAR APPROVED INSULATION BOARD
- ③ 100mm CAVITY
- ④ VAPOR BARRIER
- ⑤ 13mm CEMENT BOARD
- ⑥ METSEC FRAMING INFILLED WITH 100mm MINERAL WOOL INSULATION-
-ROCKWOOL OR SIMILAR APPROVED
- ⑦ 2X15mm SOUND BLOCK BOARDS
- ⑧ UPVC AND EXPANDED POLYSTYRENE CAVITY
CLOSER BY
- ⑨ STEEL ANGLE SPANNING BETWEEN OPENINGS
BEARING 150mm OVER SIDE WALLS- COLOR
FINISHED TO MATCH WINDOW FRAMES
- ⑩ COMPOSIT POLYESTER POWDER COATED
ALUMINIUM/TIMBER FRAMES TO DOUBLE
GLAZED PANELS

NOTE:**

SOME FRAMES MAY REQUIRE TRIPLE GLAZING TO SOUND ENG. SPEC.
THIS DRAWING TO BE READ IN CONJUNCTION WITH DRW . 12387_40_03

25_03

GLAZED SCREEN SET FORWARD HEAD DETAIL

SCALE 1:5 @ A3

REV BY DATE CHK DESCRIPTION

STATUS

FOR CONSTRUCTION

CONTRACTOR

WILMOT DIXON

PROJECT

TWYMAN HOUSE

CLIENT

TAYLOR WIMPEY
CENTRAL LONDON

DRAWING TITLE

TYPICAL WINDOW HEAD DETAIL
GLAZED SCREEN SET FORWARD

DATE CREATED 22.02.13	DATE AMENDED 22.02.13	SCALE 1:5@A3
DRAWN BY NA	AMENDED BY MBRZEZINSKA	CHECKED MB

DRAWING NO & REVISION
12387_40_04-D1

The Quadrangle,
180 Wardour Street,
London W1F 8FY
T +44 (0)20 7287 1153
F +44 (0)20 7287 3675
www.sprunt.net

sprunt.

ver 2.2