

KEY:

- 1) 2X15mm SOUNDBLOCK PLASTERBOARD FINISHED WITH 2mm SKIM COAT
- 2 VAPOR CHECK LAYER
- (3) REINFORCED CONCRETE COLUMN
- (4) 50mm KINGSPAN K15 THERMAL INSULATION BOARD
- 5 BRICK TIES
- (6) BREATHER MEMBRANE-ROBEROID PRO OR SIMILAR APPROVED
- (7) METSEC FRAME WITH MINERAL WOOL INSULATION INFILL
- (8) 100mm KINGSPAN K15 THERMAL INSULATION
- CAVITY CLOSER WITH PROPIETORY BRACKET FIXING INTO BRICK CORSING
- (10) POLYESTER POWDER COATED ALUMINIUM AND TIMBER COMPOSITE FRAME
- (11) POLYESTER POWDER COATED ALUMINIUM CILL
- (12) MDF WINDOW BORAD WHITE SATIN PAINT FINISH
- 13) 12mm CEMENT PARTICLE BOARD

NOTE:\*\*

SOME FRAMES MAY REQUIRE TRIPLE GLAZING TO SOUND ENG. SPEC. THIS DRAWING TO BE READ IN CONJUNCTION WITH DRW.12387\_40\_04

NOTE: DETAILS ALSO REFERENCED ON 10 SERIES DRAWINGS 01 TO 13

> C1 NA 10.12.12 MB FOR CONSTRUCTION REV BY DATE CHK DESCRIPTION

FOR CONSTRUCTION

CONTRACTOR

WILMOT DIXON

TWYMAN HOUSE

TAYLOR WIMPEY CENTRAL LONDON

TYPICAL WINDOW JAMB DETAIL GLAZED SCREEN SET FORWARD

DATE CREATED DATE AMENOED SCALE
22.02.13 22.02.13 1:5@A3
DRAWN BY AMENOED BY CHECKED
NA MBRZEZINSKA MB

12387\_40\_17-D1

The Quadrangle, 180 Wardour Street, London W1F 8FY T +44 (0)20 7287 1153 F +44 (0)20 7287 3675

