



- Existing soffit level to be accepted as 0.000 for the purposes of laying out the roof structure;
- All steel elements to be aligned at their bottoms;
- Timber joists to be inserted between them South-North at 400 mm intervals, their bottoms always 20 mm lower than that of the steel elements;
- This diagram should be used in conjunction with Architectural details see drawings 601-603.

00	Issued for tender	29/11/2012
REV.	DESCRIPTION	DATE

DRAWING STATUS:

**For Tender**



**COMMERCIAL ARCHITECTURE**  
**DOMESTIC PROJECTS**  
**CONSULTANCY**

4-43 Belsize Avenue, London NW3 4BN, UK  
 T: +44 7946 526210; E: info@ar-arch.co.uk; www.ar-arch.co.uk

GENERAL NOTES:

- Do not scale the drawing - use figured dimensions only.
- This drawing is to be read in conjunction with all relevant specifications and drawings.
- All dimensions to be checked on site.
- In the event of any discrepancies between drawings the contractor is to inform the Architect immediately.
- AR Architecture assumes no responsibility whatsoever for the interpretation of the drawing, nor for any errors or omissions resulting from the use of this information.
- Users shall be responsible for verifying suitability of this data for their application.

CLIENT: **Mr Yury Poluneev**

PROJECT: **House Refurbishment & Extension**  
**43 Quickswood London NW3 3SA**

DRAWING TITLE: **Extension structure**

DATE:	Nov 2012	STAGE:	F
SCALE:	1:50@A2	DRAWN BY:	MR
		CHECKED BY:	AR
PROJECT NO.	12004	DRAWING NO.	701
		REVISION:	00