

Marshalls 🤃

## Heritage® Paving

Cast from genuine split sandstone flags with mason fettled edges reminiscent of newly quarried yorkstone



## Heritage Paving

- The manufacturing process means that Heritage Paving should be bedded on mortar
- Paving joints should be 8-15mm wide and fully pointed with mortar
- Paving should not be butt jointed
- Do not use de-icing salts or chlorine-based products on, or adjoining, the finished paving
- If used indoors, paving should be sealed with a proprietary water-based acrylic sealant
- If required you can purchase less than full packs minimum quantity, single units (see 'Order Select', p.169)
- Only Heritage Weathered Yorkstone has Marshalls **Active Shield Protection**
- For information on Marshalls innovative Active Shield Protection, please see page 41

Paving	Sizes mm (nominal)	No. /m² *	Weight (kg/each)	Weight (kg/pack)	No. /pack	Colours	Order Select	kg CO <sub>2</sub> per m²
	600 x 600 x 38	2.7	31	682	22	1	1	22
	600 x 450 x 38	3.6	24	528	22	Υ.	1	22
	600 x 300 x 38	5.3	15	660	44	OY.	1	22
	450 x 450 x 38	4.7	18	779	44	CB.	1	22
	450 x 300 x 38	7.0	12	528	44	WYS	1	22
	300 x 300 x 38	10.4	8	352	44		1	22

\*Assumes 10mm nominal joint widths

## Marshalls @ Active Shield withTEFLON® surface protector



Yorkstone (Y)



Weathered Yorkstone (WYS) with Active Shield



Calder Brown (CB)



Old Yorkstone (OY)

## Stepping Stones

Stepping Stones	Sizes mm (nominal)	Weight (kg/each)	Weight (kg/pack)	No. /pack	Colours	Order Select	kg CO <sub>2</sub> Each
Circular	380 dia x 38	9.7	224	24	Y, OY, CB	1	2.6
Circular	600 dia x 38	25	250	10		1	5.5
Asymmetrical	560 x 420 x 38	16	352	22	Y, CB	1	4

