

CABLE EXIT ON INSIDE, 25 DIA. HOLE

G
G
G
G
F/S

ENTRY
PANEL

S
S

ELEVATION OF TYPICAL SINGLE DOORSET HLOD
NB. DOOR DRAWN OPENING OUT TOWARDS VIEWER

NB, DUUR DKAWN UPENING OOT TOWARDS VIEWER

INO SINGLE DOORSET REQUIRED HLOO AS DRAWN FOR 1-29 ST. ANTONY'S REAR MANUFACTURE NO

960 40 X 20 X 2 40 X 60 X 2 . DOOR STOP FΠR MAG-LOCK _FULL LENGTH HINGE COVER _ 3mm M.S. ZINTEC DOOR SKIN 100 X 50 X 2mm 100 X 20 X 40 X 60 X 2 M. S EXTERIOR SIDE 50 X 5mm M. STEEL. WIDTH SECTION THRO' SINGLE DOORSET CONTINUOUS GAP GUARD

IRONMONGERY SUPPLIED & PREPARED FOR BY DELTA SECURITY PER DOORSET.

1No 12mm S. STEEL CONTINUOUS FINGER FRIENDLY HINGE

1No LCN 4111 SURFACE DOOR CLOSER

2No ST. STEEL KICK PLATES

1No PULL HANDLE S/S 225 X 25

INO PUSH TO EXIT BUTTON ON INSIDE

INO FIREMAN SWITCH

INO ENTRY PANEL

2NO ELECTRO MAGNETIC LOCKS REF. M32 SERIES

INO ELECTRO MAGNETIC LOCKSREF. M32C SERIES

= 11.5mm CLEAR LAM. GLASS, 3mm GLAZING TAPE BOTH SIDES, 20 X 25 M. S. BEAD

S = 3mm M. S ZINTEC SOLID PANEL P. P. COATED 20 X 20 S. S. BEAD ALL BLACK SILICON POINTED

<u>FINISH</u>

ALL DOOR / FRAME TO BE SHOT BLASTED & ZINC SPRAYED AND PPC TEXTURED GLOSS COLOUR RAL. 8016 BROWN

| THIS DE AND MI TO A T | RAWING IS THE PROPE JIST NOT BE COPIED O HIRD PARTY WITHOUT SION OF DELTA SECUR | R DISCLOSED THE WRITTEN |) | URITY |
|-----------------------------|--|----------------------------|-------|--------|
| | | | | |
| 0 | ORIGINAL ISSUE | | | 6-2-12 |
| REV | DETAILS | | | DATE |
| PROJEC | THE ORIGIN & | 25 | | |
| DRAWN | BY DLP | DATE | 6-2-2 | 012 |
| SCALE | 1:20@A3 | APPROVED | | |
| JOB No | DELTA ORIGIN | DRG No | 01 | |
| | DELTA SEC | URITY | | |