

Capital Radio - London Architect - Morey Smith Associates Builder - Overbury Projects Ltd.



Mornington Court - London London Borough of Camden

Purpose Made Steel Windows and Doors

Monk Metal Windows are a well established manufacturer of purpose made W20 and W40 steel windows with over 50 years experience in the design, fabrication and installation of fenestrations for the construction industry.

The Company is registered with BSI as a firm of assesssed capability in accordance with the requirements of BS EN ISO 9002.

Monk are also on the Home Office list of approved suppliers for purpose made security windows to prisons and young offenders institutes.

Monk offer a complete window package of design, installation and glazing together with the additional service of removing existing windows before replacement.

Monk offers the flexibility and response of a small specialist firm able to provide single source responsibility using computer aided design and costing.






Heritage


W20 RANGE


Purpose Made Steel Windows

Head - opening light

- Hot dipped galvanised to BS EN ISO 1461
- Polyester powder coated to BS 6497
- Weather stripped
- Single or double glazed up to 14mm thick
- · Optional thro the frame trickle ventilation







W40 RANGE Coupling Mullion



NEWAGE

W40 RANGE


Enhanced Performance **Purpose Made Steel Windows**


Head - opening light

- Hot dipped galvanised to BS EN ISO 1461
- Polyester powder coated to BS 6497
- · Double weather stripped
- Single or double glazed up to 24mm thick
- Optional thro the frame trickle ventilation

Cill - fixed light

Transome Coupling





Maximum Recommended Sizes

This table is for guidance only and size limits may vary depending on window construction and design criteria.

TYPE		W20	W40
Fixed Light	L	3000	3000
	Н	3000	3000
	Р	9200	9400
Side hung casement	L	900	1000
open in or out	Н	2400	2400
	P	6400	6600
Top hung casement	L	1800	2000
open out	Н	1800	2000
**	P	6400	6600
Bottom hung casement	L	1800	2000
open in	Н	1500	1600
	P	6400	6600
Horizontally pivoted	L	1800	1800
casement	. H	1800	1800
	Р	6400	6400
Vertically pivoted	L	1500	1500
casement	Н	2400	2400
	Р	6500	6500
Double side hung	L	1800	2000
casements open	Н	2400	2400
in or out	Р	8000	8400
Double doors	L	1800	2000
open in or out	Н	2500	2500
2000 A 124	Р	8400	8600
Single door	L	900	1000
open in or out	Н	2500	2500
	Р	6600	6600

W20 W40

Size limits and performance details


THERMAL PERFORMANCE

Indicative 'U' Values of combined frame and insulating glass units, with and without low emissivity coatings are: (W/m² / degK)

W20	20 4mm glass / 6mm air gap / 4mm glass	
W20	4mm glass / 6mm air gap / 4mm Low E glass	3.3
W40	4mm glass / 16mm air gap / 4mm glass	3.3
W40	4mm glass / 16mm air gap / 4mm Low E glass	2.8

TYPE	RANGE	TEST PRESSURE CLASS			EXPOSURE
		AIR	WATER	WIND	CATEGORY
Fixed light	W20	600	300	2400	2400SPL
	W40	600	300	2400	2400SPL
Top hung	W20	300	200	2000	2000
	W40	300	300	2400	2400
Side hung	W20	300	200	2000	2000
open out	W40	300	* 300	2400	2400
Side hung	W20	200	100	1600	1200
open in	W40	300	300	2400	2400
Bottom hung	W20	200	100	1600	1200
	W40	300	300	2400	2400
Horizontal	W20	200	100	1600	1200
pivot	W40	300	200	2400	2000
Vertical	W20	200	50	1600	1200X
pivot	W40	300	150	2400	1200

Test pressure class and exposure category in Pascals of typical types and sizes when tested to BS 5368 and classified as BS 6375: Part 1.







Other Products:

A cold rolled steel window system designed with Italian flair by Secco. Developed and tested by Monk for the UK market. Brochure available on request.



Monk Metal Windows Ltd

Designers and Manufacturers of Purpose-made Metal Windows

Registered Office: Hansons Bridge Road Erdington Birmingham B24 0QP Telephone (0121) 351 4411 Fax (0121) 351 3673

E-mail: sales@monkmetalwindows.co.uk Website: www.monkmetalwindows.co.uk

Company Reg. No. 2279468



FM 10955







Steel Window Association