










Ranulf Road Preliminary Structural Proposals:

- **Demolition** - The existing detached property will be demolished with care in a sequence manner to ground level. This would be followed with preparing the piling matt for formation of the proposed basement.
- **Sub-structure construction** - The formation of basement and the lower ground floor will be carried in such a way as not to compromise the foundation and structure of the neighbouring buildings. As the site level is sloping towards the garden the maximum ground retention is towards Ranulf Road. Contiguous piling using a Continuous Flight Augered (CFA) rig is currently considered the preferred construction method for the substructure. This method has the advantage of low noise / vibration against methods such as driven piles. Once the piles are in place the basement slab would be formed and a secondary wall is built to ensure the basement is suitably tanked for residential purpose. Reinforced concrete capping beams would be formed for the formation of the lower ground floor and the superstructure.
- **Super-structure construction** - The proposed buildings upper levels comprises of a number of cubical volumes mounted on top of each other with slight staggering of the footprint in order to achieve versatile internal / external spaces that are contemporary in design. However beyond ground floor the cubes have four locations in common where they are vertically aligned providing the opportunity to position the buildings columns. Therefore there is a need for a transfer slab at ground floor which can be achieved using reinforced concrete slab. The intention is to construct the superstructure using modularised construction methods such as precast concrete or solid cross laminated timber. These methods have the advantage of a better quality finish as well as a speedier erecting time on site that would Benefit the project in its entirety and minimise any disturbance to the neighbouring buildings.





The background is a solid red color with a complex network of thin, white, irregular lines. These lines intersect to form a variety of geometric shapes, including triangles, quadrilaterals, and polygons of different sizes. The lines are distributed across the entire page, creating a sense of depth and movement.

04

Architectural Design



The design takes into consideration the impact on the local environment and the need for the building to enhance its surroundings. The massing for this development has led to work within the heights of the existing context and to enrich the urban environment. The material choices are sympathetic to the native palette of Jersey and achieves cohesion with the urban fabric.

Advances in design have meant that Brick has gained much more freedom of expression. Previous used has a structural elements today in regards to structural efficiency it can be a lot more expressive. The simple material can be used in a veer more interesting ways.

Visualisation- North East



Visualisation- South West



Visualisation- North East



Visualisation- North West



The background of the entire page is a solid red color. Overlaid on this is a complex, abstract pattern of thin, white, straight lines. These lines intersect at various angles to form a network of irregular, multi-sided polygons of different sizes. The pattern is dense and covers the entire area, creating a textured, crystalline effect.

05

Sustainability



OUTLINE DESIGN REQUIREMENTS
FOR
MECHANICAL AND ELECTRICAL
ENGINEERING SERVICES CODE FOR SUSTAINABLE HOMES
AT
RANULF ROAD, LONDON, NW2

ITD Consultants (Engineering Services)
226A Havant Road
Drayton
Portsmouth
PO6 1PA
Telephone: 023 9243 5050
Facsimile: 023 9243 1096
e-mail: eng@itdconsultants.co.uk
www.itdconsultants.co.uk

Specification No: 1963-3
Issue No: 1
Date: 29th September 2011

1.0. INTRODUCTION

This outline specification defines the principles to be adopted for the provision of mechanical and electrical services to achieve the Code for Sustainable Homes Levels as indicated.

This is an initial assessment and further advanced / additional services may be required subject to a SAP / SBEM Calculation. The assumptions have been made from previous projects with similar requirements.

Other aspects of the building, its design and operation such as local amenities, transport, health and wellbeing, land use, ecology and pollution will need to be assessed with the entire design team to ensure the appropriate code is achieved


2.0. LEVEL CODE 3

2.1. General

Code for Sustainable Homes level 3 requires a minimum 25% improvement over the TER CO2 emissions calculated in a SAP / SBEM model to achieve this it is likely the following systems will need to be installed.

2.2. Mechanical Services

2.2.1 Heating – It is unlikely that a gas fired boiler with a tradition heating system will achieve a code 3, so therefore alternative options such as an air source heat pump providing LTHW at around 45°C will be required. This will also provide the primary heating for the domestic hot water system.



2.2.2 Hot & Cold Water – The home will need to be designed to use no more than 105 litres per person per day. This can be achieved by installing items such as

Outline Design Requirements
Mechanical and Electrical Engineering Services
Ranulf Rd, London NW2
Reference: 1963-3
Issue: 1
Date: 29th September 2011

2



- i. 6/4 dual flush WC
- ii. Flow reducing taps
- iii. 6-9 l/m shower heads
- iv. Smaller shaped bath
- v. 18 litre max volume dishwasher
- vi. 60 litre max volume washing machine

Solar panels may have to be introduced to provide an LTHW circuit to the hot water cylinder, ensuring that immersion heaters are for back up purposes only and not an primary / secondary heat source for the hot water system.



Outline Design Requirements
Mechanical and Electrical Engineering Services
Ranulf Rd, London NW2
Reference: 1963-3
Issue: 1
Date: 29th September 2011

3



2.2.3 Ventilation – the use of a supply and extract heat recovery 'whole house' ventilation unit will almost certainly be required to satisfy code 3.



2.3. Electrical Services

2.3.1 Mains and Small Power – additional sub metering may be required, with the possibility of warning devises to ensure 'out of range values' are not occurring on site.

2.3.2 Lighting – 40% of the fixed internal lighting will need to be low energy fittings



Outline Design Requirements
Mechanical and Electrical Engineering Services
Ranulf Rd, London NW2
Reference: 1963-3
Issue: 1
Date: 29th September 2011

4



2.4. Additional Requirements

- Provide dry space heating (to avoid the use of tumble driers)
- Provide a 'home office'
- Provide dedicated cycle storage
- Reducing the amount of water that runs off the site into storm drains
- Using environmental friendly materials
- Provide recycling capacity either inside or outside the home
- Enhancing the security of the home
- Small rain water harvesting systems may be required such as water butts etc.

3.0. LEVEL CODE 4

To Achieve Code 4, all of the criteria set out in section 2 will need to be met along with some of the items listed in section three. As a comparison:

Code 3 requires 25% improvement over the TER CO2 emissions calculated in a SAP / SBEM model and a further 46.7 points from the Code for Sustainable Homes document

Code 4 requires 44% improvement over the TER CO2 emissions calculated in a SAP / SBEM model and a further 54.1 points from the Code for Sustainable Homes document

Code 5 requires 100% improvement over the TER CO2 emissions calculated in a SAP / SBEM model and a further 60.1 points from the Code for Sustainable Homes document


4.0. LEVEL CODE 5

4.1. General

Code for Sustainable Homes level 5 requires a minimum 100% improvement over the TER CO2 emissions calculated in a SAP / SBEM model to achieve this it is likely the following systems will need to be installed.

4.2. Mechanical Services

2.2.1 Heating – either a high efficient air source heat pump (possibly gas fired) or failing that, ground source heat pump will be required to provide the space heating throughout the dwelling. This can be either by oversized radiators or underfloor heating.



2.2.2 Hot & Cold Water – The home will need to be designed to use no more than 80 litres per person per day. This can be achieved by installing items such as

- vii. 6/4 dual flush WC
- viii. Flow reducing taps
- ix. 6-9 l/m shower heads
- x. Smaller shaped bath
- xi. 18 litre max volume dishwasher
- xii. 60 litre max volume washing machine

Solar panels will have to be introduced to provide an LTHW circuit to the hot water cylinder, ensuring that immersion heaters are for back up purposes only and not an primary / secondary heat source for the hot water system.

2.2.3 Ventilation – the use of a supply and extract heat recovery 'whole house' ventilation unit will be required to satisfy code 5.

2.2.4 Rain Water Harvesting – a rain water harvesting system will need to be provided. This is usually stored and utilised for gardening and irrigation purposes.



2.2.5 Grey Water Harvesting – a grey water harvesting system with appropriate treatment plant and filters will need to be provided. This is usually stored and used for the non-potable sanitary ware items within the house.



4.3. Electrical Services

2.3.1 Mains and Small Power – additional sub metering may be required, with the possibility of warning devises to ensure 'out of range values' are not occurring on site.



2.3.2 Lighting – 75% of the fixed internal lighting will need to be low energy fittings.



External / security luminaires will need to have maximum combined output of 150W and fitted with movement detectors and daylight shut off devices.

2.3.3 Photo Voltaic System – a PV system will almost certainly be required to provide supplementary dedicated electrical supply and a feed in tariff meter if not all of the generated electricity is consumed.



4.4. Additional Requirements

- Provide dry space heating (to avoid the use of tumble driers)
- Provide a 'home office'
- Provide dedicated cycle storage
- Reducing the amount of water that runs off the site into storm drains
- Using highly environmental friendly materials
- Provide recycling capacity either inside or outside the home





The current property has extensive landscape and garden to its rear. This has over a number of year of neglect become overgrown to the extent where the garden is not usable in its current condition. Our intention is to improve the spatial qualities of this by creating usable space. The intention is to use the Arboriculture report and expertises to minimise the effect of our landscaping strategy and to maintain and sustain as much as possible from the original garden. The design leads to an inevitable loss of tree on the site but the loss is minimised by insuring that the tress will be replaces by similar species. The landscaping insure that when land needs to be excavated for structures that this soil is recycled and soil reduction is kept to a minimum insuring the survival of the current fauna in the garden.





KAMVARI ARCHITECTS

UK, London

59 Banner Street, London EC1Y 8PX, UK

t. 0044 207 253 4513

Iran, Tehran

Vanak Avenue, Shiraz Junction, Khajoye Kermani Street No 5, Unit 4

t. 0098 21 88048820-25

www.kamvariarchitects.com