



KEY

SD

Smoke detector to plasterboard ceilings

SD

Void Smoke detector, if required.

E

Flourescent Batten 2 x 1500mm E denotes maintained emergency fitting All to BS5266-1:1999

PC

People counter and data poin

S22

iGuzzini LED/EM/3W.01 (white finish) emergency light fitting to retail areas only. 3 Hour maintained emergecny fitting.

S22

Cooper Menvier Bright blade NM BBM White in Retail area
Cooper Menvier Vistral NM e-lite in BOH area
All to BS5266-1:1999 and Signs BS5499-4:2000

E

Cooper Menvier Vistral NM e-lite All to BS5266-1:1999

E

Wall mounted emergency light fitting

E

Ceiling mounted emergency light fitting

Supply grille ext. or relocated clean all.

Return air/extract grille ext. or relocated clean all.

Fire Alarm Sounder

High level spur

New Speakers

New grille to suit recessed ceiling slot
fin. RAL 9003 satin from ducted (not cassettes) system
all details by Specialists sub contractor to Landlords approval.
1500mm x 150mm with 25mm border.
Main contractor to check confirmed dimensions with
Leckenby Associates prior to cutting out ceiling

Light switch either single or two way as shown
MK Logic white

Disabled Fitting Room Assistance Alarm

Ceiling or wall mounted dome head camera

450mm x 450mm ceiling hatch/grille to access AC units

600mm x 600mm ceiling hatch to access smoke
detection in voids and connection boxes for lighting.
Hatches to be frameless, skimmed and decorated to match
ceiling RAL 9003

AC unit

Ceiling mounted footflow counter

Erco Optec Spot

Erco Optec Flood

Erco Optec Flood

Existing Erco Track
(retained)

New Erco Track

Existing recessed Erco
gimbals to underside of
ceiling rafts to be fitted
whit new freee issue
front cover glass

Recessed luminaires
relocated from first
floor

Existing AC grille to
underside of ceiling raft.
To be retained and
upgraded where
necessary

NOTE: AC layout and Access hatches to be confirmed

