


NOTE:
All New glazing to be energy efficient,
New Aluminium Framed Glazed Sliding
Door and Fixed Glass Pane to be glazed
to provide a min 'U' value of 2.0W/m2k,
utilising 28mm DGU: 6mm clear toughened safety
outer glass, in 14mm Black Silicone Space Bar
hermetically sealed double-glazed units with low 'E'
coating for improved thermal efficiency, 8mm laminated
soft coat Low e inner pane,
, in hermetically sealed double-glazed
units with low 'E' coating for improved
thermal efficiency.

NOTE:
All New glazing to be energy efficient,
New Fixed Glazed Rooflight to be glazed
to provide a min 'U' value of 2.0W/m2k,
utilising 28mm DGU: 6mm clear toughened safety
outer glass, in 14mm Black Silicone Space Bar
hermetically sealed double-glazed units with low 'E'
coating for improved thermal efficiency, 8mm
laminated soft coat Low e inner pane, , in
hermetically sealed double-glazed units
with low 'E' coating for improved thermal
efficiency.
Glazing to be edged in aluminium
channels on 3 sides

PROPOSED SIDE ELEVATION

SCALE 1 : 100

SCALE 1 : 1



KEY

- Existing walls retained
- New masonry walls
- New metal stud walls

GENERAL NOTES

- All buildingwork to comply with all relevant Construction Standards.
- No dimensions to be scaled or scanned from drawing.
- All dimensions to be checked on site prior to construction and/or installation.
- Figured dimensions to be used at all times.
- Contractor is responsible for correct setting out with particular reference to boundaries, building lines, etc.
- Contractor to verify all levels, heights and dimensions on site and to check the same against the drawings before putting any work in hand.
- Contractor is to locate and identify existing services on the site and to protect these from damage throughout the duration of the works.
- Any errors, omissions or omissions to be reported immediately.
- Contractor is to build in approved waterproofing whether or not these are shown on drawings, to all walls at each floor level or parapet level and to all windows, doors, grilles or other openings in external walls.
- Any queries arising from all the above must be reported and clarified before any works is put in hand.

COPYRIGHT

rodriguezgilmour is the proprietor of all rights including copyright in this material. No reproductions are permitted without written consent. The client accepts the responsibility of materials, content and statement.

The elements shown on this drawing are prototypical design only. They may not be utilized, altered, the specification changed, or implemented in part or in whole, in any structure without notification and written approval being issued by rodriguezgilmour.

REVISIONS:

No.	Date	Description	Int.
A	30.05.11	ISSUED FOR PLANNING	
B	21.09.11	AMENDED AS PER COUNCIL'S REQUEST + REISSUED FOR PLANNING	
C	31.10.11	AMENDED AS PER COUNCIL'S REQUEST + REISSUED FOR PLANNING.	

ISSUED FOR
PLANNING

rodriguezgilmour
architecture + interiors

5 - 66 gloucester gardens
london w2 6bn
t: +44 (0) 207 402 9042

e: mail@rodriguezgilmour.com
w: www.rodriguezgilmour.com

Client
Mr.Jonathan Smith

Project Title
170 Haverstock Hill
London NW3 2AT

Drawing Title
PROPOSED
SIDE ELEVATION

Scale	Date	Client approval
1:100	09/05/2011	
Designed DRD	Drawn DRD	Checked DRD
Job No. 0136	Drawing No. A(PL)017	Revision C