



VITRAL Inspiration brushed stainless steel framed and glazed panels to form one mono-pitched rooflight, External faces only to have dark grey 3M finish.

All panels double glazed with hermetically sealed units comprising 6mm HP Suncool 70/40 ACTIV toughened outer over 6.4mm clear laminated super low "E" inner (having a 1.1 W/m²K mid-pane value) with 18mm Argon filled cavity.

Opening panels : 1 no. having one silver TECO 24 40 24V 0-500 mm stroke single chain actuators Operated via return to centre switch through step down transformer. (all wiring, switching, sensors and control panels installed by others).

All perimeter flashings to be min. 1.2mm polyester powder-coated aluminium in RAL colour RAL 9043.

All necessary timber / steel supporting structure, roofing, leadworks and internal finishes etc. by others. left ready to receive glazing.

PRELIMINARY

SOLAR VISION LIMITED
 Tel. 01366 377010
 e-mail: dave@solarvisionlimited.co.uk

PROJECT:
 33 Fitzroy Square
 London
 W1T 6EU

TITLE:
 VITRAL Glazing : -
 Cill Structure
 Requirements

Project ref: UK -	Contract ref: 8004
Drawn by: DBS	Date: 26-08-08
Drawing No. 09 of	Rev. P1
SCALE 1:2 @	