




Product features




Small, bezel, silver grey, opal diffuser




Small, cross, anthracite, opal diffuser




Small, halo visor, silver grey, clear diffuser




Small, halo visor, silver grey, opal diffuser




Large, bezel, anthracite, opal diffuser



Large, cross, black, opal diffuser



Large, visor, anthracite, opal diffuser



Large, halo visor, black, opal diffuser

Lamps

Small

18W TC-DEL (FSQ) compact fluorescent. Cap: G24q-2

26W TC-TEL (FSM) compact fluorescent. Cap: GX24q-3

Large

28-55W TC-DDEL (FSS) compact fluorescent. Cap: GR10

42W TC-TEL (FSM) compact fluorescent. Cap: GX24q-4

Materials/Finish

Housing and decorative feature (cross, bezel and visor): die-cast aluminium
Diffusers: opal or clear polycarbonate
Reflector: aluminium
Gaskets: extruded silicone rubber sponge
Vandal proof screws, torx key supplied with every luminaire

Installation/Mounting

Wall or ceiling (except 38W and 42W E3 versions) mounting with central BESA provision and four fixing points (2 horizontal holes to aid adjustment, additional holes for security or uneven surfaces). Two cable entries to rear or side (not for conduit use) into 3-way terminal block (4-way for E3 versions). Looping possible. Separate gear tray secures with two screws.

Standards

Designed and manufactured to comply with EN 60598
Emergency versions with EN 60598 2. 22




Class I electrical
IK10

IP65

Specification

Surface mounted bulkhead with die-cast black/silver grey/anthracite aluminium body and opal/clear polycarbonate diffuser. IP65. IK10/double wall design that will conceal cable from view. Round large/small with plain/cross/visor/halo visor. For compact fluorescent/metal halide lamps. With emergency/and photocell/lighting. As Thorn EyeKon.

For more information visit the EyeKon microsite
www.thornlighting.com/eyeKon



REF : E2