

This Design submission has been carried out by an Authorised SAP Assessor. It has been prepared from plans and specifications and may not reflect the property as constructed.

**Assessor Name** MRS JOANNE CHURCHILL

**Assessor Number** 1591

**Client**

**Date Last Modified** 21/04/2010

**Address** Unit 3 Makepeace Mansions Unit 3 Holly Lodge Estate, Camden, Greater London, NW1

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

## 1. Overall dwelling dimensions

	Area (m <sup>2</sup> )	Average storey height (m)	Volume (m <sup>3</sup> )
Ground Floor	<input type="text" value="42.24"/> (1a)	<input type="text" value="2.63"/>	<input type="text" value="111.09"/> (1)
Total floor area (1a)+(2a)+(3a)+(4a)+(4b)+(4d)+(4f)+(4h) =	<input type="text" value="42.24"/> (5)		
Dwelling volume		(1)+(2)+(3)+(4)+(4c)+(4e)+(4g)+(4i) =	<input type="text" value="111.09"/> (6)

## 2. Ventilation rate

	m <sup>3</sup> per hour	Air changes per hour
Number of chimneys	<input type="text" value="0"/> × 40 = <input type="text" value="0"/> (7)	
Number of open flues	<input type="text" value="0"/> × 20 = <input type="text" value="0"/> (8)	
Number of intermittent fans or passive vents	<input type="text" value="0"/> × 10 = <input type="text" value="0"/> (9)	
Number of flueless gas fires	<input type="text" value="0"/> × 40 = <input type="text" value="0"/> (9a)	
Infiltration due to chimneys, flues and fans = (7)+(8)+(9)+(9a) =	<input type="text" value="0"/>	÷ box (6) = <input type="text" value="0.00"/> (10)
<i>If a pressurisation test has been carried out, proceed to box (19)</i>		
Number of storeys in the dwelling	<input type="text" value="1"/> (11)	
Additional infiltration		[(11) - 1] × 0.1 = <input type="text" value="N/A"/> (12)
Structural infiltration: 0.25 for steel or timber frame or 0.35 for masonry construction		<input type="text" value="N/A"/> (13)
If suspended wooden floor, enter 0.2 (unsealed) or 0.1 (sealed), else enter 0		<input type="text" value="N/A"/> (14)
If no draught lobby, enter 0.05, else enter 0		<input type="text" value="N/A"/> (15)
Percentage of windows and doors draught stripped	<input type="text" value="N/A"/> (16)	
<i>Enter 100 in box (16) for new dwellings which are to comply with Building Regulations</i>		
Window infiltration	0.25 - [0.2 × (16) ÷ 100] =	<input type="text" value="N/A"/> (17)
Infiltration rate	(10)+(12)+(13)+(14)+(15)+(17) =	<input type="text" value="N/A"/> (18)
If based on air permeability value, then [q <sub>50</sub> ÷ 20] + (10) in box (19), otherwise (19) = (18)		<input type="text" value="0.50"/> (19)
<i>Air permeability value applies if a pressurisation test has been done or the design air permeability is being used</i>		

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

Number of sides on which sheltered (Enter 2 in box (20) for new dwellings where location is not shown)		<input type="text" value="2"/>	(20)
Shelter factor	$1 - [0.075 \times (20)] =$	<input type="text" value="0.85"/>	(21)
Adjusted infiltration rate	$(19) \times (21) =$	<input type="text" value="0.38"/>	(22)
Calculate effective air change rate for the applicable case			
If balanced whole house mechanical ventilation system	air throughput (ach) =	<input type="text" value="0.30"/>	(22a)
If balanced with heat recovery	efficiency in % allowing for in-use factor =	<input type="text" value="79.05"/>	(22b)
a) If balanced whole house mechanical ventilation with heat recovery	$(22) + (22a) \times [1 - (22b) / 100] =$	<input type="text" value="0.45"/>	(23)
b) If balanced whole house mechanical ventilation without heat recovery	$(22) + (22a) =$	<input type="text" value="N/A"/>	(23a)
c) If whole house extract ventilation or positive input ventilation from outside if $(22) < 0.25$ , then $(23b) = 0.5$ ; otherwise $(23b) = 0.25 + (22)$		<input type="text" value="N/A"/>	(23b)
d) If natural ventilation or whole house positive input ventilation from loft if $(22) \geq 1$ , then $(24) = (22)$ ; otherwise $(24) = 0.5 + [(22)^2 \times 0.5]$		<input type="text" value="N/A"/>	(24)
Effective air change rate - enter (23) or (23a) or (23b) or (24) in box (25)		<input type="text" value="0.45"/>	(25)

### 3. Heat losses and heat loss parameter

ELEMENT	Area (m <sup>2</sup> )	U - value	AXU (W/K)
Windows *	<input type="text" value="10.16"/>	<input type="text" value="1.77"/>	<input type="text" value="17.94"/>
Ground Floor	<input type="text" value="42.24"/>	<input type="text" value="0.22"/>	<input type="text" value="9.12"/>
Walls	<input type="text" value="31.40"/>	<input type="text" value="0.31"/>	<input type="text" value="9.83"/>
Walls	<input type="text" value="20.77"/>	<input type="text" value="0.25"/>	<input type="text" value="5.19"/>
Total area of elements $\Sigma A$ , m <sup>2</sup>	<input type="text" value="104.57"/>		

\* for windows and rooflights use effective window U-value calculated as given in paragraph 3.2

Fabric heat loss, W/K	$(26) + (27) + (27a) + (27b) + (28) + (29) + (29a) + (30) + (30a) + (31) =$	<input type="text" value="42.09"/>	(33)
Thermal bridges - $\Sigma (l \times \Psi)$ calculated using Appendix K if details of thermal bridging are not known calculate $y \times (32)$ [see Appendix K] and enter in box (34)		<input type="text" value="15.69"/>	(34)
Total fabric heat loss	$(33) + (34) =$	<input type="text" value="57.77"/>	(35)
Ventilation heat loss	$(25) \times 0.33 \times (6) =$	<input type="text" value="16.33"/>	(36)
Heat loss coefficient, W/K	$(35) + (36) =$	<input type="text" value="74.10"/>	(37)
Heat loss parameter (HLP), W/m <sup>2</sup> K	$(37) \div (5) =$	<input type="text" value="1.75"/>	(38)

### 4. Water heating energy requirement

**kWh/year**

Energy content of hot water used from Table 1 column (b)	<input type="text" value="1325.73"/>	(39)
Distribution loss from Table 1 column (c) If instantaneous water heating at point of use, enter "0" in boxes (40) to (45) For community heating use Table 1 (c) whether or not hot water tank is present	<input type="text" value="233.95"/>	(40)
Water storage loss:		

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

a) If manufacturer's declared loss factor is known (kWh/day):

Temperature factor from Table 2b N/A (41)

Energy lost from water storage, kWh/year (41) × (41a) × 365 = N/A (42)

b) If manufacturer's declared cylinder loss factor is not known:

Cylinder volume (litres) including any solar storage within same cylinder 150.00 (43)  
*If community heating and no tank in dwelling, enter 110 litres in box (43)*  
*Otherwise, if no stored hot water (this includes instantaneous combi boilers), enter '0' in box (43)*

Hot water storage loss factor from Table 2 (kWh/litre/day) 0.01 (44)  
*If community heating and no tank in dwelling, use cylinder loss from Table 2 for 50 mm factory insulation in box (44)*

Volume factor from Table 2a 0.93 (44a)

Temperature factor from Table 2b 0.60 (44b)

Energy lost from water storage, kWh/year (43) × (44) × (44a) × (44b) × 365 = 261.39 (45)

Enter (42) or (45) in box (46) 261.39 (46)

If cylinder contains dedicated solar storage, box (47) = (46) × [(43) - (H11)] / (43), else (47) = (46) 261.39 (47)

Primary circuit loss from Table 3 360.00 (48)

Combi loss from Table 3a (enter "0" if no combi boiler) 0.00 (49)

Solar DHW input calculated using Appendix H (enter "0" if no solar collector) 0.00 (50)

Output from water heater, kWh/year (39) + (40) + (47) + (48) + (49) - (50) = 2181.08 (51)

Heat gains from water heating 0.25 × [(39) + (49)] + 0.8 × [(40) + (47) + (48)] = 1015.71 (52)  
*include (47) in calculation of (52) only if cylinder is in the dwelling or hot water is from community heating*

### 5. Internal gains

	Watts	
Lights, appliances, cooking and metabolic (Table 5)	388.80	(53)
Reduction of internal gains due to low energy lighting (calculated in Appendix L)	30.13	(53a)
Additional gains from Table 5a	0.00	(53b)
Water heating <span style="float: right;">(52) ÷ 8.76 =</span>	115.95	(54)
Total internal gains <span style="float: right;">(53) + (53b) + (54) - (53a) =</span>	474.62	(55)

### 6. Solar gains

	Access factor Table 6d	Area m <sup>2</sup>	Flux Table 6a	g Table 6b	FF Table 6c	Gains (W)	
East	0.77	1.58	48.48	0.72	0.70	26.69	(59)
South	0.77	8.58	72.72	0.72	0.70	218.03	(62)

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

Total solar gains: [(56) + ..... + (64)] = 244.72 (65)

*Note: for new dwellings where overshadowing is not known, the solar access factor is '0.77'*

Total gains, W (55) + (65) = 719.33 (66)

Gain/loss ratio (GLR) (66) ÷ (37) = 9.71 (67)

Utilisation factor (Table 7, using GLR in box (67)) 0.84 (68)

Useful gains, W (66) × (68) = 606.70 (69)

Gains Zone 1, G1 364.02 (NHER)

Gains Zone 2, G2 242.68 (NHER)

## 7. Mean internal temperature

° C

Living area fraction (0 to 1.0) living room area ÷ (5) = 0.54 (75)

Interzone heat coefficient 98.58 (NHER)

Mean external temperature 3.15 (NHER)

**Zone1 Zone2**

Specific loss 40.15 33.94 (NHER)

Demand temperature 21.00 19.12 (NHER)

Mean internal temperature 19.23 16.89 (NHER)

## 8. Degree days

**Zone1 Zone2**

Base temperature 10.90 2.95 (NHER)

Degree-days 874.32 46.51 (NHER)

## 9. Space heating requirements

**Zone1 Zone2**

Space heating requirement (useful), kWh/year 1372.40 9.71 (NHER)

Total space heating requirement (useful), kWh/year 1382.11 (81)

*For range cooker boilers where efficiency is obtained from the Boiler Efficiency Database or manufacturer's declared value, multiply the result in box (81) by (1 - Φ<sub>case</sub>/Φ<sub>water</sub>) where Φ<sub>case</sub> is the heat emission from the case of the range cooker at fullload (in kW); and Φ<sub>water</sub> is the heat transferred to water at full load (in kW). Φ<sub>case</sub> and Φ<sub>water</sub> are obtained from the database record for the range cooker boiler or manufacturer's declared value.*

## 9b. Energy requirements - Community heating scheme

*This page should be used when space and water heating is provided by community heating only, with or without CHP or heat recovered from power stations. If CHP, recovered heat, or second boiler type is not involved enter "0" in box (83\*), and "1.0" in box (84\*)*

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

Overall system efficiency of the heating plant or boilers (100% minus the amount shown in the 'efficiency adjustment' column of Table 4c(3) where appropriate)		100.00	(82*)
Fraction of heat from CHP unit or fraction of heat recovered from power station or boilers Type 2 (from operational records or the plant design specification)		N/A	(83*)
Fraction of heat from boilers Type 1	1 - (83*) =	1.00	(84*)
Distribution loss factor for boilers Type 1 (Table 12c)		1.05	(85a*)
<b>kWh/year</b>			
Space heating from CHP, recovered/geothermal heat or boilers Type 2	$[(81) \times (83*) \times 100] \div (82*) \times (85*) =$	N/A	(86*)
Space heating from boilers Type 1	$[(81) \times (84*) \times 100] \div (82*) \times (85*) =$	1451.22	(87*)
Water heated by CHP or recovered heat or boilers Type 2	$[(51) \times (83*) \times 100] \div (82*) \times (85*) =$	0.00	(87a*)
Water heated by boilers Type 1 (or other system)	$[(51) \times (84*) \times 100] \div (82*) \times (85*) =$	N/A	(87b*)
<b>Water heating from DHW only community heating</b>			
Overall system efficiency of the DHW only heating plant		100.00	(82*)
Fraction of water heating from CHP unit		0.00	(83*)
Fraction of heat from boilers or heat pump	1 - (83*) =	1.00	(84*)
Distribution loss factor for DHW only community heating (Table 12c)		1.05	(85*)
Water heated by CHP	$[(51) \times (83*) \times 100] \div (82*) \times (85*) =$	N/A	(87a*)
Water heated by boiler or heat pump	$[(51) \times (84*) \times 100] \div (82*) \times (85*) =$	2290.13	(87b*)
<b>Electricity for pumps, fans, lights and appliances:</b>		1846.70	(NHER)
<b>Cooking:</b>			
Cooking fuel requirement (Electricity), kWh/year		302.30	(NHER)
Cooking fuel requirement (Other fuel), kWh/year		531.08	(NHER)

## 10b. Fuel costs - Community heating scheme

	Fuel required kWh/year	×	Fuel price (Table 12)	=	Fuel cost £/year	
<b>Space heating</b>						
Space heating (CHP or from power stations or boilers Type 2) <i>For CHP price from Table 12 is irrespective of fuel used by CHP</i>	(86*)	×	0.00	×	0.00	(89*)
Space heating (community boilers Type 1)	(87*)	×	1.90	×	27.50	(90*)
<b>Water heating from DHW only community heating</b>						
			<b>Fuel price</b>			
Water heated by CHP	(87a*)	×	N/A	×	N/A	(91*)
Water heated by boilers or heat pump	(87b*)	×	1.90	×	43.40	(92*)
<b>Pump, fan, lights and appliances energy cost</b>						
On-peak fraction					1.00	

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

Off-peak fraction

0.00

**Fuel price**

On-peak cost  $\frac{1846.70}{1.00} \times 7.96 \times 0.01 = 147.07$  (NHER)

Off-peak cost  $\frac{1846.70}{0.00} \times -1.00 \times 0.01 = 0.00$  (NHER)

**Cooking**

Cooking cost (Electricity)  $\frac{302.30}{7.96} \times 0.01 = 24.08$  (NHER)

Cooking cost (Other fuel)  $\frac{531.08}{1.87} \times 0.01 = 9.92$  (NHER)

**Additional standing charges**

61.64 (94\*)

**Renewable and energy-saving technologies ( Appendix M)**
**PV**

Energy produced or saved, kWh/year

N/A (95\*)

Cost of energy produced or saved, £/year

(95\*)

×

N/A

× 0.01 =

N/A

(95a\*)

**Wind**

Energy produced or saved, kWh/year

N/A (95b1\*)

Cost of energy produced or saved, £/year

(95b1\*)

×

N/A

× 0.01 =

N/A

(95b\*)

**Special features (Appendix Q)**

Energy produced or saved, kWh/year

N/A (s1\*)

Cost of energy produced or saved, £/year

(s1\*)

×

N/A

× 0.01 =

N/A

(s1a\*)

Energy consumed by the technology, kWh/year

N/A (s2\*)

Cost of energy consumed, £/year

(s2\*)

×

N/A

× 0.01 =

N/A

(s2a\*)

**Total heating**  $(89^*) + (90^*) + (91^*) + (92^*) + (94^*) + (94a^*) + (94b^*) - (95a^*) - (95b^*) - (s1a^*) + (s2a^*) = 313.60$  (97\*)

**11b. NHER rating - Community heating scheme**
**NHER rating**

11.70

**12a. Total CO2 for individual heating systems (including micro-CHP) and community heating without CHP**
**Community scheme:**

Efficiency of community boilers % *use actual efficiency if known, or value in Table 4a* 75.00 (104)

Energy for space heating  $(87^*) \times 100 \div (104) = 1934.95 \times 0.194 = 375.38$  (105)

**DHW only community scheme:**

Efficiency of community boilers % *use actual efficiency if known, or value in Table 4a* 90.00 (104)

Energy for water heating  $[(87b^*) \times 100 \div (104)] = 2544.59 \times 0.194 = 493.65$  (106)

Space and water heating  $[(101) + (102) + (106)] = 869.03$  (107)

Electricity for pumps, fans, lights and appliances  $\frac{1846.70}{0.422} = 779.31$  (NHER)

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

**Cooking**

Energy for cooking (Electricity)	302.30	×	0.42	=	127.57	(NHER)
Energy for cooking (Other fuel)	531.08	×	0.19	=	103.03	(NHER)
Energy produced or saved in dwelling (Appendices M and N)						
PV energy produced or saved	(95) or (95*)	×	N/A	=	N/A	(110)
Wind energy produced or saved	(95b1) or (95b1*)	×	N/A	=	N/A	(110b)
Micro-CHP energy produced or saved	(95c1) or (95c1*)	×	N/A	=	N/A	(110c)
Micro-CHP energy consumed	(96) or (96*)	×	N/A	=	0.00	(111)
Energy produced or saved in dwelling (Appendix Q)	(s1) or (s1*)	×	N/A	=	0.00	(s1a)
Energy consumed by the technology (Appendix Q)	(s2) or (s2*)	×	N/A	=	0.00	(s2a)
Total CO <sub>2</sub> kg/year	(107) + (108) + (109) - (110) + (111) - (s1a) + (s2a)			=	1877.94	(112)
<b>Total CO<sub>2</sub> (kg/m<sup>2</sup>/year)</b>				(112) ÷ (5)	=	44.46 (113)

**DHW only community scheme (uses section 12a calculations):**

Efficiency of community boilers %	use actual efficiency if known, or value in Table 4a				90.00	(104)	
Energy for water heating	$[(87b*) \times 100 \div (104)] =$	2544.59	$\times$	0.194	=	493.65	(106)

**13a. Primary energy, for individual heating systems (including micro-CHP) and community heating without CHP**
**Community scheme:**

Efficiency of community boilers %	75.00	(104)				
use actual efficiency if known, or value in Table 4a						
Energy for space heating	$(87*) \times 100 \div (104) =$	1934.95	$\times$	1.150	$=$	2225.20

**DHW only community scheme:**

Efficiency of community boilers %	use actual efficiency if known, or value in Table 4a				90.00	
Energy for water heating	$[(87b*) \times 100 \div (104)] =$	2290.13	$\times$	N/A	=	N/A
Space and water heating				$[(101) + (102) + (106)] =$		5151.47
Primary energy for pumps,fans,lights and appliances		1846.70	$\times$	2.80	=	5170.76 (NHER)

**Cooking**

Primary energy for cooking (Electricity)	302.30	×	2.80	=	846.43	(NHER)
Primary energy for cooking (Other fuel)	531.08	×	1.15	=	610.74	(NHER)
Energy produced or saved in dwelling (Appendices M and N)						
PV energy produced or saved	(95) or (95*)	×	N/A	=	N/A	
Wind energy produced or saved	(95b1) or (95b1*)	×	N/A	=	N/A	
Micro-CHP energy produced or saved	(95c1) or (95c1*)	×	N/A	=	N/A	

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**

Micro-CHP energy consumed	(96) or (96*)	×	N/A	=	0.00
Energy produced or saved in dwelling (Appendix Q)	(s1) or (s1*)	×	N/A	=	0.00
Energy consumed by the above technology (Appendix Q)	(s2) or (s2*)	×	N/A	=	0.00
<b>Primary energy kWh/year</b>					11779.41
<b>Primary energy kWh/m<sup>2</sup>/year</b>					278.87

*draft*

**This draft NHER rating worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control**