


# Key for CMS types

- 2N° 100 dia Ridgicoll for LV Power and Comms cables between draw pits, buried a minimum of 450 below finished platform level c/w draw wire refer to Detail 'A' on dwg STD-ELE-P-110-5-03.
- 2N° 100 dia Ridgicoll for LV Power and Comms cables to CCTV Cabinet refer to Detail 'G2' on dwg STD-ELE-P-110-5-06.
- 2N° 50 dia Ridgicoll for LV Power and Comms cables from draw pit to lighting column, refer to Detail 'A' on dwg STD-ELE-P-110-5-04.
- 1N° 50 dia Ridgicoll, refer to Detail 'A' on dwg STD-ELE-P-110-5-04.
- 2N° 25 dia galvanised steel conduits for LV Power and Comms cables.
- 1N° 25 dia galvanised steel conduit.
- 225x50 wide heavy duty return flanged 2-compartment galvanised steel cable tray for LV Power and Comms cables c/w heavy duty lid.
- 100x50 wide heavy duty return flanged 2-compartment galvanised steel cable tray for LV Power and Comms cables c/w heavy duty lid.
- 75x50 1 compartment galvanised steel cable trunking.
- 2N° 32 dia galvanised steel conduits for LV Power and Comms cables.


## Note:

Where 90° bends are required in CMS types 'E', 'F' and 'K' a minimum bending radius of 100mm must be incorporated.


Where 90° bends are required in CMS types 'G' and 'H' a 'Flat Bend' is to be incorporated.



Section 1



Section 2



Key Plan  
N.T.S.

## General notes

- This drawing is the copyright of GCP Rail Ltd, and should not be reproduced without prior written approval.
- This drawing is to be read in conjunction with all relevant Drawings, Specifications, and Contract Documents.
- This drawing must only be reproduced in colour.
- All dimensions in millimetres (mm) and all levels are in metres (m). Do not scale from this drawing.
- For Standard Notes used on Civil/Architectural (Ambience Works) drawings, refer to Drawing No. STD-PAD-P-110-5-01. For Standard Notes used on the Electrical (Ambience Works) drawings, refer to Drawing No. STD-ELE-P-110-5-02.
- For Symbols and Abbreviations used on the Civil/Architectural (Ambience Works) drawings, refer to Drawing No. STD-PAD-P-110-5-02. For Symbols and Abbreviations used on the Electrical (Ambience Works) drawings, refer to Drawing No. STD-ELE-P-110-5-02.
- This drawing has been produced without topographical or geometrical survey data. The relative positions of existing structures, station furniture, fixtures, etc. which are not subject to Phase 3 ambience works, are shown indicatively. It is the responsibility of the User of this drawing to check and verify the accuracy of the information provided prior to its use. In the event that such verification is not undertaken no liability will be accepted for claims, additional cost or extension of time resulting from any inaccuracies contained within the information provided. All dimensions must be checked on site to ensure the proposed works can be installed correctly and in accordance with the design intent prior to commencing work.
- All materials and workmanship shall be in accordance with current and specified standards.
- The systems equipment design which includes Closed Circuit Television Cameras (CCTV), Public Address Speakers (PA), Customer Information Screens (CIS), Next Train Indicator (NTI), Thin Film Transistor Display Screens (TFT), Closed Circuit Television Camera Live Monitor Display Screens (CCTV DS), Public Help Points (PHP) and Induction Loops (IL) is by LOROL System Designer. New CCTV cameras & PA speakers are shown in the general location indicated on the System Designer's CCTV Desktop Survey drawings. The systems equipment locations, where shown, is indicative and are provided for coordination and information purposes only. Lighting columns that support existing operational systems equipment shall not be removed until the new systems equipment is installed and operational. No reliance should be placed upon the accuracy of the systems information provided. Final connections to Systems Equipment to be by LOROL System Designer. Structural assessment of new or existing structures supporting systems equipment is by the Systems Designer.
- Repair and reinstatement / replacement of any existing assets damaged by the User of these documents works is the responsibility of the User. The User shall replace the damaged area / materials with new to a standard no less than equal quality and to the satisfaction of the Engineer. Replacement materials shall be Network Rail compliant. Repair will only be acceptable with prior written approval of the Engineer. The User shall be responsible for all direct and indirect costs associated with such damage.
- The User of these documents shall be familiar with the Designer's Risk Assessment prior to commencement of any work on site, and shall take all appropriate measures necessary to minimise Health & Safety risks associated with the work.

project no.  
1036 - 029

THIS DRAWING DOES NOT TAKE ACCOUNT OF INFORMATION CONTAINED WITHIN THE SYSTEMS OPERATORS FINAL PROPOSAL AND WILL BE SUBJECT TO CHANGE ONCE THESE DETAILS HAVE BEEN RECEIVED.

02 Based for Pre-Construction Approval JP 23.08.10 MS

GCP Rail Ltd  
42 Tabard Street  
London SE1 4JU  
t: 020 7487 3067  
f: 020 7357 9949  
www.gcp-rail.co.uk


gcp partnership

drawing status  
PRE-CONSTRUCTION APPROVAL


project client  
LOROL  
London Overground  
Camden Road Station

drawing title  
Proposed Station Cabling & Cont'mt  
Platform Elevations  
Sheet 1 of 2  
scale (A1) date drawn checked  
1:100 11.01.10 JP EMO


reference  
drawing no. revision  
CMD-ELE-P-20-3-01 00



Elevation A - Area 'A'



Elevation A - Area 'B'



Elevation A - Area 'C'




# Key for CMS types

- 2N° 100 dia Ridgiducts for LV Power and Comms cables between draw pits, buried a minimum of 450 below finished platform level c/w draw wire refer to Detail 'A' on dwg STD-ELE-P-110-5-03.
- 2N° 100 dia Ridgiducts for LV Power and Comms cables to CCTV Cabinet refer to Detail 'G2' on dwg STD-ELE-P-110-5-06.
- 2N° 50 dia Ridgiducts for LV Power and Comms cables from draw pit to lighting column, refer to Detail 'A' on dwg STD-ELE-P-110-5-04.
- 1N° 50 dia Ridgiduct, refer to Detail 'A' on dwg STD-ELE-P-110-5-04.
- 2N° 25 dia galvanised steel conduits for LV Power and Comms cables.
- 1N° 25 dia galvanised steel conduit.
- 225x50 wide heavy duty return flanged 2-compartment galvanised steel cable tray for LV Power and Comms cables c/w heavy duty lid.
- 100x50 wide heavy duty return flanged 2-compartment galvanised steel cable tray for LV Power and Comms cables c/w heavy duty lid.
- 75x50 1 compartment galvanised steel cable trunking.
- 2N° 32 dia galvanised steel conduits for LV Power and Comms cables.


## Note:

Where 90° bends are required in CMS types 'E', 'F' and 'K' a minimum bending radius of 100mm must be incorporated.


Where 90° bends are required in CMS types 'G' and 'H' a 'Flat Bend' is to be incorporated.




Key Plan  
N.T.S.



Elevation B - Area 'A'



Elevation B - Area 'B'



Elevation B - Area 'C'

- This drawing is the copyright of GCP Rail Ltd. and should not be reproduced without prior written approval.
- This drawing is to be read in conjunction with all relevant Drawings, Specifications, and Contract Documents.
- This drawing must only be reproduced in colour.
- All dimensions in millimetres (mm) and all levels are in metres (m). Do not scale from this drawing.
- For Standard Notes used on Civil/Architectural (Ambience Works) drawings, refer to Drawing No. STD-PAD-P-110-5-01. For Standard Notes used on the Electrical (Ambience Works) drawings, refer to Drawing No. STD-ELE-P-110-5-02.
- For Symbols and Abbreviations used on the Civil/Architectural (Ambience Works) drawings, refer to Drawing No. STD-PAD-P-110-5-01. For Symbols and Abbreviations used on the Electrical (Ambience Works) drawings, refer to Drawing No. STD-ELE-P-110-5-02.
- This drawing has been produced without topographical or geotechnical survey data. The relative positions of existing structures, station furniture, fixtures, etc. which are not subject to Phase 3 Ambience Works, are shown inductively. It is the responsibility of the User of this drawing to check and verify the accuracy of the information provided prior to its use. In the event that such verification is not undertaken no liability will be accepted for claims, additional cost or extension of time resulting from any inaccuracies contained within the information provided. All dimensions must be checked on site to ensure the proposed works can be installed correctly and in accordance with the design intent prior to commencing work.
- All materials and workmanship shall be in accordance with current and specified standards.
- The systems equipment design which includes Closed Circuit Television Cameras (CCTV), Public Address Speakers (PA), Customer Information Screens (CIS), Next Train Indicators (NTI), Thin Film Transistor Display Screens (TFT), Closed Circuit Television Camera Live Monitor Display Screens (CCTV DS), Public Help Points (PHP) and Induction Loops (IL) is by LOROL's System Designer. New CCTV cameras & PA speakers are shown in the general location indicated on the System Designer's CCTV Desktop Survey drawings. The systems equipment locations, where shown, is indicative and are provided for coordination and information purposes only. Lighting columns that support existing operational systems equipment shall not be removed until the new systems equipment is installed and operational. No reference should be placed upon the accuracy of the systems information provided. Final connections to Systems Equipment to be by LOROL's System Designer. Structural assessment of new or existing structures supporting Systems equipment is by the Systems Designer.
- Repair and replacement / replacement of any existing assets damaged by the User of these documents works is the responsibility of the User. The User shall replace the damaged area / materials with new to a standard no less than equal quality and to the satisfaction of the Engineer. Replacement materials shall be Network Rail compliant. Repair will only be acceptable with prior written approval of the Engineer. The User shall be responsible for all direct and indirect costs associated with such damage.
- The User of these documents shall be familiar with the Designer's Risk Assessment prior to commencement of any work on site, and shall take all appropriate measures necessary to minimise health & safety risks associated with the works.

project no.  
1036 - 029

THIS DRAWING DOES NOT TAKE ACCOUNT OF INFORMATION CONTAINED WITHIN THE SYSTEMS OPERATORS FINAL PROPOSAL AND WILL BE SUBJECT TO CHANGE ONCE THESE DETAILS HAVE BEEN RECEIVED.

02 Based for Pre-Construction Approval JP 20.03.10 001

GCP Rail Ltd  
42 Tebboard Street  
London SE1 4JZ  
t: 020 7497 3067  
f: 020 7357 9949  
www.gcpairpartnership.co.uk  
partnership

drawing status  
PRE-CONSTRUCTION APPROVAL

project  
client  
project title  
London Overground  
Camden Road Station

drawing title  
Proposed Station Cabling & Cont'mt  
Platform Elevations  
Sheet 2 of 2  
scale (A1)  
1:100  
date  
11.01.10  
drawn  
JP  
checked  
EMO

reference  
drawing no.  
CMD-ELE-P-20-3-02  
revision  
00