WARM DECK: -- 3G FELT TO BS 747 - CELOTEX XR3110 INSULATION BOARD - 1000g POLYTHENE VCL VELUX ROOFLIGHT CFP S00C - 12mm PLYWOOD SCREWED TO JOISTS @ 150 C/C CODE 5 LEAD FLASHING - FIRRINGS TO FALL 1:60 - 150x50 C16 SW JOISTS @ 400 c/c - 12.5mm PLASTERBOARD 150 **CONCRETE COPING ON DPC-**CODE 5 LEAD GUTTER TO 1:200 FALL-WITH T-PREN EXPANSION JOINTS @ 2m ON BLDG PAPER ON TREATED TIMBER. 1000

SECTION A-A

NOTES:

- DO NOT SCALE FROM THIS DRAWING. THIS DRAWING IS PREPARED FOR PLANNING PURPOSES ONLY AND NOT INTENDED FOR ANY OTHER USE.
- ALL DIMENSIONS ARE IN MILLIMETERS UNLESS STATED OTHERWISE.
- DIMENSIONS TO BE CHECKED ON SITE AND ANY ERRORS OR DISCREPANCIES DISCOVERED SHALL BE REPORTED TO THE 'MG' BEFORE THE WORK IS PUT IN HAND.
- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DOCUMENTS.

