



4<sup>th</sup> June 2007

**Mr. R. Mallinson**  
**Taylor Young**  
Chadsworth House  
Wilmslow Road  
Handforth  
SK9 3HP

**Building Services Consultants**

Kings Head Yard  
London  
SE1 1NA

DDI: +44 (0)  
T +44 (0) 20 7089 8900  
F +44 (0) 20 7089 8910  
E london@foremanroberts.com

www.foremanroberts.com

Dear Richard

**Centre Point – 103 New Oxford Street**  
**External Lighting**

RECEIVED  
14 JUN 2007

In response to the letter from Camden Planning services we can confirm that we have spoken to the specified manufacturer of the luminaires and that they have advised that all fixings of luminaires are concealed and will not be visible. Specifically for each type of luminaire the fixings will be as follows:

**Type L1 – Replacement handrail:** The existing handrail is supported on circular steel posts mounted into the concrete upstand. The existing hand rail is to be removed leaving the upright posts in position. The new handrail support posts will be sized to act as a sleeve and will sit over the existing posts. The new support columns will then be clamped to the existing post with.....

**Type L2 - Submersible uplight:** These luminaire shall be cast into a concrete block that shall sit on the bottom of the pool. The weight of the block will keep it in position and deter it being moved or damaged by people in the pool. This method of installation will also avoid making structural changes to the pool and thus prevent any problems with possible leaks.

**Type L3 – Planter luminaires:** These luminaires shall be mounted in a stainless steel box that shall be screw fixed to the corner of the planter with concealed fixings. This is again to prevent the luminaires being moved inadvertently. The cable feed to the planters shall be installed in a stainless steel conduit run in an existing recess on the rear of the planter.

**Type L4 – Canopy luminaire:** This luminaire shall sit in a stainless steel trough mounted on the side of the existing canopy gutter box. All fixings shall be concealed and the luminaire shall not be visible from low level.

**Types L5, L6 & L7 – Downlighters:** These are all similar style downlighters of varying lamp sources. The luminaires are surface mounted with screw fixings through the back of the luminaires into the concrete soffit.

**Type L8 – not used**

**Type L9 – Wayfinder luminaire:** This is a free standing luminaire with screw fixing into the concrete slabs.

**Types L10 & L11 – Linear LED luminaires:** These luminaires have a linear polycarbonate housing which is held in position by a fixing clips at approximately 1m centres.