Arundel House Development EcoHomes Pre-Assessment Estimator

> UNITE 3rd August 2006

Prepared by:

Eleanor Hayes Graduate Engineer Approved by:

Kevin Couling Principal Engineer

Rev No	Comments	Date
1		

Bush House, Prince Street, Bristol, BS1 4QD

Telephone: 0117 901 7000 Fax: 0117 901 7099 Website: http://www.fabermaunsell.com

Job No

Reference

Date Created 3rd August 2006

This contains confidential and commercially sensitive information, which shall not be disclosed to third parties.

document2

Table of Contents

1	Intro	duction	4
	1.1	General	4
2	Pred	icted Performance	5
	2.1	Predicted Performance	5
3	Pre-	Assessment Estimator	6

1 Introduction

1.1 General

EcoHomes seeks to minimise the adverse effects of new buildings on the environment at global and local scales, whilst promoting healthy indoor conditions for the occupants. The environmental implications of a new building are assessed at the design stage, and compared with good practice by independent assessors. An overall rating of the building's performance is given using the terms Pass, Good, Very Good or Excellent. This is determined from the total number of EcoHome criteria met in the eight EcoHome categories and their respective environmental weightings.

It is possible to make a reasonable prediction of the likely performance of a particular scheme in a full assessment by using the pre-assessment estimator. The estimator process uses a series of questions based on the full assessment credits and awards scores according to the anticipated performance of the building. Evidence to prove compliance with the credit requirements does not have to be provided in a pre-assessment estimator.

It must be understood that the estimator is only a guide to the likely performance of the scheme and should not be taken as a guarantee of full assessment performance due to the significant number of assumptions which are made in completing the process.

This assessment has been based on plan and elevation drawings and information received from Unite.

2 Predicted Performance

2.1

Predicted Performance

The predicted performance of the building is summarised below. Whilst reviewing the output of the estimator, it should be borne in mind that developments which take place in a poor location in EcoHome terms (such as those in rural locations on greenfield sites) tend to fare worse than those in better locations (such as those within the limits of a major urban conurbation, on brownfield sites etc).

	Topic	Likely
1.0	ENERGY	8.24
2.0	TRANSPORT	7
3.0	POLLUTION	3.64
4.0	MATERIALS	7.65
5.0	WATER	6.66
6.0	LANDUSE & ECOLOGY	8
7.0	HEALTH & WELLBEING	7
8.0	MANAGEMENT	9
	Total Score	59.03 = VERY GOOD

The required score for VERY GOOD is 58.

Based on past experience, it is worth aiming for a score above 58 in order to allow flexibility during the design development phase which often results in a reduction in the overall score when undertaking the formal assessment.

3 Pre-Assessment Estimator

The following pages summarise the output of the pre-assessment estimator and any assumptions that have been made.



EcoHomes 2006 Pre Assessment Estimator

Issue		% of total score	% of total sc achieved	Location ore
Energ	y			
Ene 1	Dwelling Emission Rate			
Ene 1	Credits are awarded to achieve SAP 2005 CO ₂ emissions as follows: Less than or equal to 40 kg/m²/yr R Less than or equal to 35 kg/m²/yr OR Less than or equal to 32 kg/m²/yr OR Less than or equal to 30 kg/m²/yr OR Less than or equal to 28 kg/m²/yr OR Less than or equal to 26 kg/m²/yr OR Less than or equal to 24 kg/m²/yr OR Less than or equal to 22 kg/m²/yr OR Less than or equal to 20 kg/m²/yr OR Less than or equal to 18 kg/m²/yr OR Less than or equal to 15 kg/m²/yr OR Less than or equal to 15 kg/m²/yr OR Less than or equal to 10 kg/m²/yr OR Less than or equal to 10 kg/m²/yr OR Less than or equal to 10 kg/m²/yr OR Less than or equal to -10 kg/m²/yr	0.92 1.83 2.75 3.67 4.58 5.50 6.42 7.33 8.25 9.17 10.08 11.00 11.92 12.83 13.75	3.67 (max 13.75)	
	based on the Heat Loss Parameter (HLP) method meets the following requirements: For new build: where the HLP is less than or equal to 1.3 W/m²K OR where the HLP is less than or equal to 1.1 W/m²K	0.92		



	For refurbishment: • where the HLP is less than or equal to 2.2 W/m²K	0.92	0.92	
	OR where the HLP is less than or equal to 1.75 W/m²K	1.83	(max 1.83)	
Ene 3	Drying space		(max 1.00)	
	Provision of drying space	0.92	0	
			(max 0.92)	
ene 4	Eco Labelled white goods			
	Provision of eco labelled white goods with the following energy ratings: • All fridges, freezers, fridge-freezers with an A ⁺ rating	0.92	1.83	
	All washing machines, and dishwashers where supplied, with an A rating and washer dryers and tumble dryers with a rating of B or higher	0.92		
	No white goods provided but info on Eco labelling	0.92		
Ene 5	Internal Lighting		(max 1.83)	
_116 0	Where 40% dedicated low energy lights have been specified.	0.92		
	Where 75% dedicated low energy lights have been	1.83	1.83	
	Where 75% dedicated low energy lights have been specified.		(max 1.83)	
Ene 6	External Lighting		(max 1.00)	
	Space lighting all space lighting is specifically designed to accommodate only compact fluorescent lamps (CFL)	0.92		
	all intruder lighting to be 150 watts maximum and be fitted with PIR and day light sensor and all other type of security lighting to accommodate	0.92	18.3	
	CFLs or fluorescent strips only and be fitted with dawn to dusk sensors or timers			
			(max 1.83)	
Total N	umber of Energy Credits Achieved		8.2	4
			(max 2	2.00)
Trans	port			
Tra 1	Public Transport			
	Urban and suburban areas 80% of the development within:	4.00		
	1000m of a 30 min peak and an hourly off peak service	1.00		
	Soom of a 15 min peak and a half hourly off peak service	2.00		2.00

Bet



	Rural areas 80% of the development within: 1000m of an hourly service OR	1.00		
	500m of an hourly service OR a community bus service	2.00		(max 2.00)
Tra 2	Cycle storage			
	Provision of cycle storage for: • 50% of dwellings	1.00	1.00	
	OR 95% or dwellings	2.00	(max 2.00)	
Гга 3	Local Amenities			
	Proximity to local amenities: Within 500m of a food shop and post box Within 1000m of 5 of the following: food shop postal facility, bank/ cash machine, pharmacy, primary school, medical centre, leisure centre, community centre, public house, children's play area, place of	1.00		3
	worship, outdoor open access public area Safe pedestrian routes to the local amenities if not used for the 1st credit	1.00		(max 3.00
Tra 4	Home office			
	Provision of space, and services, for a home office	1.00	1.00 (max 1.00)	
Total N	lumber of Transport Credits Achieved			
			7.0 (max	00 8.00)
		•		
	Specifying insulating materials, that avoid the use of ozone depleting substances and have a global warming potential (GWP) of less than 5 or more (and an ODP of zero), in either manufacture or composition, for the following elements: Roof (incl. loft hatch) Wall – internal and external (incl. all doors, lintels and all acoustic insulation).	0.91	0.91	
	Floor (incl. foundations)			



Pol 2	NO _x emissions			
	95% of dwellings throughout the development must be served by heating and hot water systems with an average NO _x emission rate of less than or equal to the levels listed below.			
	Less than or equal to 100 NO _x mg/kWh OR	0.91	0.91	
	Less than or equal to 70 NO _x mg/kWh OR	1.82		
Pol 3	Less than or equal to 40 NO _x mg/kWh Reduction of surface runoff	2.73	(max 2.73)	
	Where rainwater holding facilities and/or sustainable drainage techniques are used to provide attenuation of water run-off to either natural watercourses and/or municipal drainage systems, by 50%* in areas of low probability of flooding, 75%* in areas of medium flood risk and 100%* in areas of high flood risk, at peak times from: • Hard surface runoff • Roof runoff	0.91		
	*Where a statutory body requires a greater attenuation then the higher requirement should be met in order to achieve these credits.		(max 1.82)	
Pol 4	Renewable and Low Emission Energy Source		(
	Where evidence provided demonstrates that a feasibility study considering renewable and low emission energy has been carried out and the results implemented AND	0.91		
	 Where evidence provided demonstrates that the first credit has been achieved and 10% of total energy demand for the development is supplied from local renewable, or low emission energy, sources* 	0.91		
	 Where evidence provided demonstrates that the first credit has been achieved and 15% of total energy demand for the development is supplied from local renewable, or low emission energy, sources*. 	1.82		
	* In line with the recommendations of the feasibility study.		(max 2.73)	
Pol 5	Flood Risk Mitigation			
	 Where evidence provided demonstrates that the assessed development is located in a zone defined as having a low annual probability of flooding. OR 	1.82	1.82	
	Where evidence provided demonstrates that the assessed development is located in a zone defined as having a medium annual probability of flooding and the ground level of the building, car parking and	0.91		



Mat 1 Environmental Impact of Materials The following elements obtaining an A rating from the Green Guide for Housing: Roof Roof 1.35 1.		access is above the design flood level for the site's location.		(max 1.82)	
The following elements obtaining an A rating from the Green Guide for Housing: Roof External walls Internal walls - party walls and internal partitions Floors Windows External surfacing Boundary protection Mat 2 Responsible sourcing of Materials: Basic Building Elements Where the majority of materials in the following basic building elements are responsibly sourced: Frame Ground Floor Upper floors (including any loft boarding) External walls (including external cladding) External walls (including internal partitions) Foundations/substructure Staircase (including the tread, rises and stringers) Mat 3 Responsible sourcing of Materials: Finishing Elements Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Staircase (including haterials: Finishing Elements Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) Window (including sub-frames, frames, boards, sills) External & internal door: (including sub-frames, frames, linings, door) Skirting (including any other trim) Fundations Finishing (including any other trim) Finishing (including any fitted; kitchen, bedroom, and bathroom) Facias (soffit boards, bargeboards, gutter boards, others)	Γotal Nu	umber of Pollution Credits Achieved			
The following elements obtaining an A rating from the Green Guide for Housing: Roof External walls Internal walls - party walls and internal partitions Windows External surfacing Boundary protection Mat 2 Responsible sourcing of Materials: Basic Building Elements Where the majority of materials in the following basic building elements are responsibly sourced: Frame Ground Floor Upper floors (including any loft boarding) External walls (including internal partitions) Foundations/substructure Staircase (including the tread, rises and stringers) Mat 3 Responsible sourcing of Materials: Finishing Elements Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Staircase (including the tread, rises and stringers) Mat 3 Responsible sourcing of Materials: Finishing Elements Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) Window (including sub-frames, frames, boards, sills) External & internal door. (including sub-frames, frames, linings, door) Skirting (including any other trim) Facias (soffit boards, bargeboards, gutter boards, others)	Materi	als			
Green Guide for Housing: Roof External walls Internal walls - party walls and internal partitions Floors Windows External surfacing Boundary protection Mat 2 Responsible sourcing of Materials: Basic Building Elements Where the majority of materials in the following basic building elements are responsibly sourced: Frame Ground Floor Upper floors (including any loft boarding) External walls (including external cladding) External walls (including arternal partitions) Foundations/substructure Staircase (including the tread, rises and stringers) Mat 3 Responsible sourcing of Materials: Finishing Elements Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Staircase (including hardrails, balustrades, banisters, other guarding/rails (excluding staircase)) Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Stair (including and finishing elements) Stair (including	Mat 1	Environmental Impact of Materials	STATE OF STREET		
External walls Internal walls - party walls and internal partitions Floors Windows External surfacing Boundary protection Mat 2 Responsible sourcing of Materials: Basic Building Elements Where the majority of materials in the following basic building elements are responsibly sourced: Frame General surfacing Unper floors (including any loft boarding) External walls (including external cladding) External walls (including internal partitions) Foundations/substructure Staircase (including the tread, rises and stringers) Mat 3 Responsible sourcing of Materials: Finishing Elements Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) Window (including sub-frames, frames, boards, sills) External & internal door: (including sub-frames, frames, linings, door) Skirting (including any other trim) Facias (soffit boards, bargeboards, gutter boards, others)		The state of the s			
External surfacing Boundary protection Mat 2 Responsible sourcing of Materials: Basic Building Elements Where the majority of materials in the following basic building elements are responsibly sourced: 1. Frame 2. Ground Floor 3. Upper floors (including any loft boarding) 4. Roof (structure and cladding) 5. External walls (including external cladding) 6. Internal walls (including internal partitions) 7. Foundations/substructure 8. Staircase (including the tread, rises and stringers) Mat 3 Responsible sourcing of Materials: Finishing Elements Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: 1. Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) 2. Window (including sub-frames, frames, boards, sills) 3. External & internal door: (including sub-frames, frames, linings, door) 4. Skirting (including arrhitrave, skirting board & rails) 5. Panelling (including arrhitrave, skirting board & rails) 6. Furniture (including fitted; kitchen, bedroom, and bathroom) 7. Facias (soffit boards, bargeboards, gutter boards, others) 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.45 0.90 0.90 1.35		 External walls Internal walls - party walls and internal partitions Floors 	1.35 1.35 1.35	1.35	
Mat 2 Responsible sourcing of Materials: Basic Building Elements Where the majority of materials in the following basic building elements are responsibly sourced: 1. Frame 2. Ground Floor 3. Upper floors (including any loft boarding) 4. Roof (structure and cladding) 5. External walls (including external cladding) 6. Internal walls (including enternal partitions) 7. Foundations/substructure 8. Staircase (including the tread, rises and stringers) Mat 3 Responsible sourcing of Materials: Finishing Elements Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: 1. Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) 2. Window (including sub-frames, frames, boards, sills) 3. External & internal door: (including sub-frames, frames, linings, door) 4. Skirting (including architrave, skirting board & rails) 5. Panelling (including any other trim) 6. Furniture (including fitted; kitchen, bedroom, and bathroom) 7. Facias (soffit boards, bargeboards, gutter boards, others)		External surfacing		0.45	
Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: 1. Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) 2. Window (including sub-frames, frames, boards, sills) 3. External & internal door: (including sub-frames, frames, linings, door) 4. Skirting (including architrave, skirting board & rails) 5. Panelling (including any other trim) 6. Furniture (including fitted; kitchen, bedroom, and bathroom) 7. Facias (soffit boards, bargeboards, gutter boards, others)		Where the majority of materials in the following basic building elements are responsibly sourced: 1. Frame 2. Ground Floor 3. Upper floors (including any loft boarding) 4. Roof (structure and cladding) 5. External walls (including external cladding) 6. Internal walls (including internal partitions) 7. Foundations/substructure 8. Staircase (including the tread, rises and stringers)		0.9	
o. Any other significant use (max 1.35)	Mat 3	Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: 1. Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase)) 2. Window (including sub-frames, frames, boards, sills) 3. External & internal door: (including sub-frames, frames, linings, door) 4. Skirting (including architrave, skirting board & rails) 5. Panelling (including any other trim) 6. Furniture (including fitted; kitchen, bedroom, and bathroom) 7. Facias (soffit boards, bargeboards, gutter boards,			



	Recyling Facilities			
	Recycling of Household waste			
	Provision of internal storage only	0.90		
	Provision of external storage (or LA collection) only OR	0.90	0.9	
	Provision of internal AND external storage (or LA collection)	2.71	(may 2.71)	
			(max 2.71)	
Total N	umber of Materials Credits Achieved		7.6 (max 1	
Water				
Wat 1	Internal Potable Water Use			
	Less than or 52 m³ per bedspace per year	1.67		
	Less than or equal to 47 m³ per bedspace per year	3.33		
	Less than or equal to 42 m³ per bedspace per year	5.00		
	 OR Less than or equal to 37 m³ per bedspace per year 	6.66	6.66	
	OR Less than or equal to 32 m³ per bedspace per year	8.33	(max 8.33)	
Wat 2	External Potable Water Use		(IIIax 0.00)	
		1		
	Rain water collection system for watering gardens and	1.67	0	
	Rain water collection system for watering gardens and landscaped areas	1.67	(max 1.67)	
Total N		1.67	(max 1.67)	6
Total N	landscaped areas	1.67		
	landscaped areas	1.67	(max 1.67) 6.6	
	landscaped areas umber of Water Credits Achieved	1.67	(max 1.67) 6.6	
Land	umber of Water Credits Achieved Use and Ecology	1.33	(max 1.67) 6.6	10.00)
Land	umber of Water Credits Achieved Use and Ecology Ecological value of site		(max 1.67) 6.6	
Land Eco1	umber of Water Credits Achieved Use and Ecology Ecological value of site Building on land which is inherently of low ecological value		(max 1.67) 6.6 (max 1	10.00)



Eco4	Change of ecological value of site			
	A change of between –9 and –3 species	1.33		
	A change of between –3 and +3 species	2.67		
	A change between +3 and +9 species	4.00		
	A change of greater than +9 species	5.33		(max 5.33)
Eco5	Building footprint			
	 Where the total combined Floor area: Footprint ratio for all houses on the site is greater than 2.5:1 AND Where the total combined Floor area: Footprint ratio for all flats on the site is greater than 3.5:1 	1.33		
	Where the total combined Floor area: Footprint ratio for all dwellings on the site is greater than 3.5:1	2.67	2.67 (max 2.67)	
	umber of Land Use and Ecology Credits Achieved and Well Being		(max	8 12.00)
	and Well Being Provision of adequate daylighting, according to BS		(max	8 12.00)
	and Well Being	1.75 1.75 1.75	(max 3.5) (max 5.25)	8 12.00)
	Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies	1.75	3.5	8 (12.00)
Health	Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies View of sky in all above rooms	1.75	3.5 (max 5.25)	8 (12.00)
Health	Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies View of sky in all above rooms Sound Insulation Up to 4 credits where pre-completion testing is carried out to comply or improve on performance standards in Approved Document E (2003 Edition, Building	1.75 1.75	3.5 (max 5.25)	8 12.00)
Health Hea 2	Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies View of sky in all above rooms Sound Insulation Up to 4 credits where pre-completion testing is carried out to comply or improve on performance standards in Approved Document E (2003 Edition, Building Regulations England and Wales).	1.75 1.75	3.5 (max 5.25)	8 (12.00)
Hea 2	Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies View of sky in all above rooms Sound Insulation Up to 4 credits where pre-completion testing is carried out to comply or improve on performance standards in Approved Document E (2003 Edition, Building Regulations England and Wales). Private space	1.75 1.75 7.00	3.5 (max 5.25) 3.5 (max 7.00)	12.00)



Manag	ement			
Man 1	Home User Guide			
	Where evidence can be provided to demonstrate that there is provision, in each home, of a simple guide that covers information to the 'non-technical' tenant/occupant on: The environmental performance of their home Information relating to the site and surroundings	2.00	2.00 (max 3.00)	
Man 2	Considerate Constructors			
	Demonstrate a commitment to comply with best practice site management principles. OR	1.00		2.00
	 Demonstrate a commitment to go significantly beyond best practice site management principles. 	2.00		(max 2.00)
Man 3	Construction Site Impacts			
	 Evidence that demonstrates a commitment and a strategy to monitor, sort and recycle construction waste on site. AND 	1.00		
	Evidence that demonstrates that 2 or more of a-f listed below are achieved.	1.00		
	Evidence that demonstrates that 4 or more of a-f are achieved:	2.00		
	a. monitor and report CO ₂ or energy arising from site activities			3.00
	 b. monitor and report on CO₂ or energy arising from transport to and from site 			
	c. monitor water consumption from site activities			
	d. adopt best practice policies in respect of air (dust) pollution arising from the site			
	e. adopt best practice policies in respect of water (ground and surface) pollution occurring on the site			
	 80% of site timber is reclaimed, reused or responsibly sourced. 			(max 3.00
Man 4	Security			
	Commitment to work with an Architectural Liaison Officer and achieve Secured by Design award.	1.00	1.00	
	 Security standards for external doors and windows, to achieve a minimum of either: LPS1175SR1 (All doors and windows) OR PAS24-1 (All external pedestrian door-sets 	1.00	1.00	



Total Number	of Management Credits Achieved	9.00 (max 10.00)
	falling within scope of PAS24-1) AND BS7950 (All windows falling into the scope of BS7950)	(max 2.00)

Using the Pre Assessment Estimator

This Pre Assessment Estimator should only be used to estimate the rating that might be achieved under a formal EcoHomes assessment, prior to the appointment of a licensed assessor.

Complete the estimator by going through the credits and marking those which have been achieved. The EcoHomes score is awarded on the basis of the total percentage of credits achieved as indicated in the table below.

Rating	Score (%)
Pass	36
Good	48
Very Good	58
Excellent	70

Note that the estimated score must only be used as guidance to the design team and can not be used to demonstrate compliance with BREEAM. BRE cannot accept responsibility for any inaccuracies or for consequential loss incurred as a result of such inaccuracies arising through the use of the estimator.



For further information about EcoHomes including a contact list of licensed assessors please contact:

The BREEAM Office

BRE

Garston Watford WD25 9XX Tel: 01923 664462 Fax: 01923 664103

e-mail: ecohomes@bre.co.uk web site: www.ecohomes.org