

11th September 2006

EcoHome Pre-development Report

16 Stukeley Street London WC2B 5LJ



EcoHomes 2006 – The environmental rating for homes

Pre Assessment Estimator – 2006 / 1.2

April 2006

This pre-assessment estimator allows an evaluation of the likely rating to be achieved under a formal EcoHomes assessment.

NOTE: The rating obtained by using this Pre Assessment Estimator is for guidance only. Predicted ratings may differ from those obtained through a formal assessment, which must be carried out by a licensed EcoHomes assessor. Individual credit scores are rounded to the nearest two decimal points. Full guidance on the credit requirements can be found at www.ecohomes.org. Advice should be sought from a licensed assessor at an early stage in a project to ensure that the estimated rating will be obtained. A list of licensed assessors can be found at the EcoHomes website or by contacting the BREEAM office.

bre

© Building Research Establishment Ltd, April 2006. The EcoHomes name and logo are registered trade marks of Building Research Establishment Ltd. Permission is given for this estimator to

be copied without infringement of copyright for use only on projects where an EcoHomes assessment is carried out. Whilst every care is taken in preparing this estimator, BRE cannot accept responsibility for any inaccuracies or for consequential loss incurred as a result of such inaccuracies arising through the use of the estimator.

BREEAM Office BRE Garston Watford WD25 9XX Tel: 01923 664462

E-mail: <u>ecohomes@bre.co.uk</u>

Web site: <u>www.ecohomes.org</u>



EcoHomes 2006 Pre Assessment Estimator

Issi	16		% of total score	% of total so achieved	Location
En	ergy				
Ene	1	Dwelling Emission Rate			
	I	Credits are awarded to achieve SAP 2005 CO ₂ emissions as follows:			
		 Less than or equal to 40 kg/m²/yr OR 	0.92		
		 Less than or equal to 35 kg/m²/yr OR 	1.83		
		 Less than or equal to 32 kg/m²/yr OR 	2.75		
		 Less than or equal to 30 kg/m²/yr OR 	3.67		
		 Less than or equal to 28 kg/m²/yr OR 	4.58		
		 Less than or equal to 26 kg/m²/yr OR 	5.50		
		 Less than or equal to 24 kg/m²/yr OR	6.42		
	ĺ	 Less than or equal to 22 kg/m²/yr OR	7.33	7.33	
		 Less than or equal to 20 kg/m²/yr OR 	8.25	7.00	
		 Less than or equal to 18 kg/m²/yr OR			
	Ì	 Less than or equal to 15 kg/m²/yr OR	9.17		
		Less than or equal to 10 kg/m²/yr OR	10.08		
		 Less than or equal to 5 kg/m²/yr 	11.00	_ 	
		OR Less than or equal to 0 kg/m²/yr	11.92		
	1	OR Less than or equal to -10 kg/m²/yr	12.83		
		Nata. 40ka 00²/m² - 11 - 11 - 12 - 13 - 14 - 15 - 15 - 16 - 17 - 17 - 17 - 17 - 17 - 17 - 17	13.75		
	,	Note: -10kg CO ² /m ² allows for recognition of 'true zero' carbon solutions.			
Ene	2 E	Building envelope performance		(max 13.75)	
	t	Jp to 2 credits awarded where thermal performance based on the Heat Loss Parameter (HLP) method meets the following requirements:			
	F	For new build:			
		where the HLP is less than or equal to 1.3 W/m²K OR	0.92		
	•	where the HLP is less than or equal to 1.1 W/m²K	1.83	· -	



		T -		
	For refurbishment: • where the HLP is less than or equal to 2.2 W/m²K	0.92	0.92	
	where the HLP is less than or equal to 1.75 W/m²K	1.83	 (max 1.83)	
Ene 3	Drying space		·	
	Provision of drying space	0.92	0.92	
		<u> </u>	(max 0.92)	
Ene 4	Eco Labelled white goods			
	Provision of eco labelled white goods with the following energy ratings: • All fridges, freezers, fridge-freezers with an A ⁺ rating • All washing machines, and dishwashers where	0.92 0.92	0.92 0.92	
	supplied, with an A rating and washer dryers and tumble dryers with a rating of B or higher OR	0.02	0.72	
	No white goods provided but info on Eco labelling	0.92	(max 1.83)	
Ene 5	Internal Lighting			
	Where 40% dedicated low energy lights have been specified.	0.92		
	Where 75% dedicated low energy lights have been	1.83	1.83	
•	specified.		(max 1.83)	
Ene 6	External Lighting		(IIIax 1.00)	1,000
	Space lighting • all space lighting is specifically designed to accommodate only compact fluorescent lamps (CFL) Security lighting	0.92	0.92	
	 all intruder lighting to be 150 watts maximum and be fitted with PIR and day light sensor and all other type of security lighting to accommodate CFLs or fluorescent strips only and be fitted with dawn to dusk sensors or timers 	0.92	0.92	
			(max 1.83)	
Total Nu	ımber of Energy Credits Achieved		14.68	
			(max 22	2.00)
Trans	port			
Tra 1	Public Transport		1919	
	Urban and suburban areas 80% of the development within:			
	1000m of a 30 min peak and an hourly off peak service OR	1.00		
	500m of a 15 min peak and a half hourly off peak service	2.00	2.0	



Tra 2 Cycle storage	
	1ax 2.00)
Provision of cycle storage for: • 50% of dwellings OR • 95% or dwellings 2.00	
• 95% or dwellings 2.00 (max 2.00)	
Tra 3 Local Amenities Proximity to local amenities:	1.00 1.00
if not used for the 1 st credit	1. <i>00</i>
Tra 4 Home office	
Provision of space, and services, for a home office 1.00 /.00 (max 1.00)	
Total Number of Transport Credits Achieved	
(max 8.00)
Pollution	
Pol 1 Insulation ODP and GWP Specifying insulating materials, that avoid the use of ozone depleting substances and have a global warming	
potential (GWP) of less than 5 or more (and an ODP of zero), in either manufacture or composition, for the following elements: Roof (incl. loft hatch) Wall – internal and external (incl. all doors, lintels and all acoustic insulation). Floor (incl. foundations) Hot water cylinder (incl. pipe insulation and other thermal store) (max 0.91)	



Pol 2	NO _x emissions			
	95% of dwellings throughout the development must be served by heating and hot water systems with an average NO _x emission rate of less than or equal to the levels listed below.	,		
	 Less than or equal to 100 NO_x mg/kWh OR 	0.91		
	Less than or equal to 70 NO _x mg/kWh OR	1.82	1.82	
	Less than or equal to 40 NO _x mg/kWh	2.73	(max 2.73)	
Pol 3	Reduction of surface runoff			
	Where rainwater holding facilities and/or sustainable drainage techniques are used to provide attenuation of water run-off to either natural watercourses and/or municipal drainage systems, by 50%* in areas of low probability of flooding, 75%* in areas of medium flood risk and 100%* in areas of high flood risk, at peak times from: • Hard surface runoff • Roof runoff	0.91 0.91	N/A	
	* Where a statutory body requires a greater attenuation then the higher requirement should be met in order to achieve these credits.		(max 1.92)	
Pol 4	Renewable and Low Emission Energy Source		(max 1.82)	
	Where evidence provided demonstrates that a feasibility study considering renewable and low emission energy has been carried out and the results implemented	0.91	0.9/	
	Where evidence provided demonstrates that the first credit has been achieved and 10% of total energy demand for the development is supplied from local renewable, or low emission energy, sources*	0.91		
	 Where evidence provided demonstrates that the first credit has been achieved and 15% of total energy demand for the development is supplied from local renewable, or low emission energy, sources*. 	1.82	:	
	* In line with the recommendations of the feasibility study.		(max 2.73)	
Pol 5	Flood Risk Mitigation		(IIIGA 2.70)	
	Where evidence provided demonstrates that the assessed development is located in a zone defined as having a low annual probability of flooding.	1.82	1.82	
	 Where evidence provided demonstrates that the assessed development is located in a zone defined as having a medium annual probability of flooding and the ground level of the building, car parking and 	0.91		



	access is above the design flood level for the site's location.		(max 1.82)	
Total No	umber of Pollution Credits Achieved		5.46	10.00\
,			(max '	10.00)
Materi	als			
Mat 1	Environmental Impact of Materials			
	The following elements obtaining an A rating from the Green Guide for Housing:			
	 Roof External walls Internal walls - party walls and internal partitions 	1.35 1.35 1.35	1.35	
	 Floors Windows 	1.35 0.90	0.45	
<u> </u>	 External surfacing Boundary protection 	0.45 0.45		
Mat 2	Pasnansible sourcing of Materials: Basis Building		(max 7.23)	
Mat 2	Responsible sourcing of Materials: Basic Building Elements			
	Where the majority of materials in the following basic building elements are responsibly sourced: 1. Frame			
	 Ground Floor Upper floors (including any loft boarding) Roof (structure and cladding) 	0.90 - 2.71		
	 External walls (including external cladding) Internal walls (including internal partitions) 			
	 Foundations/substructure Staircase (including the tread, rises and stringers) 		(max 2.71)	
Mat 3	Responsible sourcing of Materials: Finishing Elements			
	Where the majority of materials in the following secondary building and finishing elements are responsibly sourced: 1. Stair (including handrails, balustrades, banisters, other guarding/rails (excluding staircase))			
	 Window (including sub-frames, frames, boards, sills) External & internal door: (including sub-frames, frames, linings, door) 	0.90 -	0.90	
	 4. Skirting (including architrave, skirting board & rails) 5. Panelling (including any other trim) 6. Furniture (including fitted; kitchen, bedroom, and bathroom) 	1.35		
	Facias (soffit boards, bargeboards, gutter boards, others)			
	8. Any other significant use		(max 1.35)	

Mat 4	Recyling Facilities		
	Recycling of Household waste		
	Provision of internal storage only	0.90	0.90
	Provision of external storage (or LA collection) only	0.90	
	OR Provision of internal AND external storage (or LA collection)	2.71	(max 2.71)
Total N	umber of Materials Credits Achieved		5.85
			(max 14.00)
Water			
Wat 1	Internal Potable Water Use		
	 Less than or 52 m³ per bedspace per year OR 	1.67	
	Less than or equal to 47 m ³ per bedspace per year OR	3.33	_
	Less than or equal to 42 m³ per bedspace per year OR	5.00	5.00
	Less than or equal to 37 m³ per bedspace per year OR	6.66	
	Less than or equal to 32 m³ per bedspace per year	8.33	(max 8.33)
Wat 2	External Potable Water Use		
	Rain water collection system for watering gardens and landscaped areas	1.67	
			(max 1.67)
Total No	umber of Water Credits Achieved		5.00
	······································		(max 10.00)
Land	Use and Ecology		
Eco1	Ecological value of site		
	Building on land which is inherently of low ecological value	1.33	/ 33 (max 1.33)
Eco2	Ecological enhancement		
	Enhancing the ecological value of the site through consultation with an accredited expert	1.33	/. 33 (max 1.33)
Eco3	Protection of ecological features		
	 Ensuring the protection of any existing ecological features on the site 	1.33	///A (max 1.33)



Eco4	Change of ecological value of site			
	A change of between –9 and –3 species	1.33	2//4	
	OR A change of between –3 and +3 species OR	2.67	11/1	
	A change between +3 and +9 species OR	4.00	MA	
	A change of greater than +9 species	5.33	N/A	(max 5.33)
Eco5	Building footprint			(INAX 0.00)
	 Where the total combined Floor area: Footprint ratio for all houses on the site is greater than 2.5:1 AND Where the total combined Floor area: Footprint ratio for all flats on the site is greater than 3.5:1 	1.33		
	Where the total combined Floor area: Footprint ratio for all dwellings on the site is greater than 3.5:1	2.67	2.67	
		<u> </u>	(max 2.67)	
••				
Total N	umber of Land Use and Ecology Credits Achieved		5.33	
Total N	umber of Land Use and Ecology Credits Achieved		5.33 (max -	(2.00)
	umber of Land Use and Ecology Credits Achieved and Well Being			(2.00)
				(2.00)
Health	Daylighting Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen	1.75 1.75	(max	(2.00)
Health	Daylighting Provision of adequate daylighting, according to BS 8206:pt2 in:	1.75 1.75 1.75		(2.00)
Health	Daylighting Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies	1.75		(2.00)
Hea1	Daylighting Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies View of sky in all above rooms	1.75		2.00)
Hea1	Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies View of sky in all above rooms Sound insulation Up to 4 credits where pre-completion testing is carried out to comply or improve on performance standards in Approved Document E (2003 Edition, Building	1.75 1.75 1.75-	(max *)	2.00)
Hea1	Daylighting Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies View of sky in all above rooms Sound Insulation Up to 4 credits where pre-completion testing is carried out to comply or improve on performance standards in Approved Document E (2003 Edition, Building Regulations England and Wales).	1.75 1.75 1.75-	(max ·	2.00)
Hea1	Daylighting Provision of adequate daylighting, according to BS 8206:pt2 in: In the kitchen In living rooms, dining rooms and studies View of sky in all above rooms Sound insulation Up to 4 credits where pre-completion testing is carried out to comply or improve on performance standards in Approved Document E (2003 Edition, Building Regulations England and Wales). Private space	1.75 1.75 7.00	(max - 1.75 (max 5.25) 4.00 (max 7.00)	(2.00)



	Manag	gement			
	Man 1	Home User Guide			
		Where evidence can be provided to demonstrate that there is provision, in each home, of a simple guide that covers information to the 'non-technical' tenant/occupant on: • The environmental performance of their home • Information relating to the site and surroundings	2.00 1.00	2.00	
\vdash	Man 2	Considerate Constructors		(max 3.00)	
		Demonstrate a commitment to comply with best practice site management principles. OR	1.00		
		 Demonstrate a commitment to go significantly beyond best practice site management principles. 	2.00	1.00	(max 2.00)
	Man 3	Construction Site Impacts			
		 Evidence that demonstrates a commitment and a strategy to monitor, sort and recycle construction waste on site. 	1.00	100	
		AND			
		 Evidence that demonstrates that 2 or more of a-f listed below are achieved. 	1.00	1.00	
		OR	0.00		
		 Evidence that demonstrates that 4 or more of a-f are achieved: 	2.00		
		 a. monitor and report CO₂ or energy arising from site activities 			
		 b. monitor and report on CO₂ or energy arising from transport to and from site 			
		c. monitor water consumption from site activities			
		d. adopt best practice policies in respect of air (dust) pollution arising from the site			
		e. adopt best practice policies in respect of water (ground and surface) pollution occurring on the site			
		f. 80% of site timber is reclaimed, reused or responsibly sourced.			(max 3.00)
	Man 4	Security			
		Commitment to work with an Architectural Liaison Officer and achieve Secured by Design award.	1.00	1.00	
		 Security standards for external doors and windows, to achieve a minimum of either: LPS1175SR1 (All doors and windows) OR PAS24-1 (All external pedestrian door-sets 	1.00	1.00	



	falling within scope of PAS24-1) AND BS7950 (All windows falling into the scope of BS7950)	(max 2.00)	
Total Nur	nber of Management Credits Achieved	9.00	
		(max 10.00)	
Total in all Sections		59.07	
		(max 100.00)	

Using the Pre Assessment Estimator

This Pre Assessment Estimator should only be used to estimate the rating that might be achieved under a formal EcoHomes assessment, prior to the appointment of a licensed assessor.

Complete the estimator by going through the credits and marking those which have been achieved. The EcoHomes score is awarded on the basis of the total percentage of credits achieved as indicated in the table below.

Rating	Score (%)
Pass	36
Good	48
Very Good	58
Excellent	70

Note that the estimated score must only be used as guidance to the design team and can not be used to demonstrate compliance with BREEAM. BRE cannot accept responsibility for any inaccuracies or for consequential loss incurred as a result of such inaccuracies arising through the use of the estimator.



For further information about EcoHomes including a contact list of licensed assessors please contact:

The BREEAM Office BRE

Garston Watford WD25 9XX Tel: 01923 664462 Fax: 01923 664103

e-mail: <u>ecohomes@bre.co.uk</u> web site: <u>www.ecohomes.org</u>