

# Multicarb Activated Carbon Discarb Units



## General Description

These filters are manufactured for ease of installation and incorporation into ducted air systems. They can be used on both supply for purifying incoming air, and can be used on the extract to remove toxic gasses and odours generated within a process.

## Construction

These modules are manufactured by mounting a series on carbon panel filters with a sealed case. The airflow is epitomize by presenting the filtering surfaces in a "V" formation.

Each carbon panel is sealed into the filter case so as to ensure no air can bypass the carbon granules.

The panels are manufactured using long established bonding techniques which hold the activated carbon granules in a rigid biscuit. The biscuit is encapsulated in a carbon impregnated cloth which prevents any leakage of granules or powder.

The unique bonding method used by Jasun Envirocare ensures that, unlike our competitors filters, that the panels will remain intact and rigid even if wet.



## Typical Applications

- Reduction of Cooking Odours
- Removal of Kerosene Exhaust Fumes
- General Odour Reduction
- Neutralisation of Ammonia and its Derivatives
- Removal of Formaldehyde
- Removal of Airborne Pollutants and Contaminants
- Removal of Acid Gases ( $H_2S$ ,  $SO_2$ ,  $NOX$ ,  $HCl$ )

Please check with our sales department when specifying carbon filters as most applications require a bespoke solution specifically tailored for the job in hand.



# Multicarb Cells STANDARD SIZES



No.	Nominal Size (Inches)	Height (mm)	Width (mm)	Depth (mm)	Weight of Carbon (Kg)	Cell Weight	Capacity @ 0.1 Second Dwell Time
DC-CF1	24 x 24 x 8	594	594	197	10	22	800
DC-CF1-HALF	24 x 12 x 8	594	291	197	5	11	400
DC242412/8	24 x 24 x 12	594	594	292	13	24	990
DC121212	12 x 12 x 12	297	297	297	6	12	450
DC181812	18 x 18 x 12	445	445	297	13	25	990
DC241212	24 x 12 x 12	594	297	297	13	25	990
DC242412	24 x 24 x 12	594	594	297	25	36	1900
DC-CF2	24 x 24 x 16	594	594	397	18	34	1370
DC-CF2-HALF	24 x 12 x 16	594	291	397	9	18	685
DC-WA15-208	24 x 6 x 18	144	600	440	7	13	533
DC121218	12 x 12 x 18	292	292	451	10	15	761
DC181818	18 x 18 x 18	445	445	451	19	26	1445
DC241218	24 x 12 x 18	594	297	451	18	26	1369
DC242418	24 x 24 x 18	594	594	451	36	52	2740
DC121224	12 x 12 x 24	292	292	597	13	19	990
DC181824	18 x 18 x 24	445	445	597	25	36	1900
DC241224	24 x 12 x 24	594	297	597	25	36	1900
DC242424	24 x 24 x 24	594	594	597	50	61	3800

Copyright © Jasun Envirocare Plc 2007-2012

LINEAR VELOCITY M/SECOND V'S PRESSURE DROP  
MULTICARB ACTIVATED CARBON CELLS

